



Bizgram Asia Pte Ltd
Retail Wholesale Factory Outlet
Address : #05-50 Sim Lim Square 1
 Rochor Canal Road Singapore
 188504
Operating Hours : Mon to Sun –
 10am to 7.30pm Public Holidays –
 OPEN
Tel : +65-63346455 / 63341373
Fax : NO MORE FAX SMS /
Whatsapp : +65 – 8777 6955

Warehouse Address / Office Address : Bizgram Asia Pte Ltd #07-01
 Mapletree Industrial, 10 Kaki Bukit Ave 1, Singapore 417942
Tel : +65-87742388
 Operating Hours Mon to Fri – 10am to 6pm Sat – 10am to 1pm Sunday /
 Public Holidays – Closed.
Email : sales @ bizgram.com
Web : www.bizgram.com

Product Name	Product Description	Width (mm)	Depth (mm)	Height (mm)
USB RFID READER 13MHz & 125kHz	External RFID Reader 13.56MHz + 125kHz (USB interface)	42	180	272
USB SEC RFID READER 13MHz & 125kHz	2N RFID secured reader 13.56MHz + 125kHz (USB interface), This USB reader reads the card serial number (CSN) and also secured PACs ID from HID smart cards	279	178	51
2N SIP MIC	2N SIP Mic allows paging to several zones with a simple push of a button. It is ideal for live or pre-recorded announcements. It has a built-in audio-management server for configuration, which means less equipment as well as flexible, easy and cost-efficient installation. The network microphone console has 12 buttons that can be configured with actions of your choice. 2N SIP Mic's 12 buttons give you a smart paging solution for up to 12 zones, and if your system grows you can easily connect the microphone console to a PBX system thanks to support for SIP. The microphone is based on open standards and connects to standard networks using PoE.	175	315	155
AXIS TA4711 Access Card 100 pcs	Contactless MIFARE® DESFire® EV3 8K smart card that uses advanced radio frequency identification (RFID) technology to deliver secure and reliable physical access to premises. The card is made of 100% recycled PET-G. One bulk pack comes with 100 cards.	95	100	60
AXIS TA4712 Key Fob 50 pcs	Contactless MIFARE® DESFire® EV3 8K key fob that uses advanced radio frequency identification (RFID) technology to deliver secure and reliable physical access to premises. The key fob is made of impact-resistant matt polycarbonate and ultrasonically welded in a stainless steel frame, making it stable and durable, with IP67 and IK09 rating – perfect for carrying on a keyring. One bulk pack comes with 50 key fobs.	80	130	50

AXIS TA1601 Mounting Plate	AXIS TA1601 Mounting Plate is compatible with AXIS TQ1808-VE Surveillance Cabinet and AXIS A1210-B Network Door Controller to build 4 door controller kit - AXIS A1214 Network Door Controller Kit AXIS TA1601 Mounting Plate is included in AXIS A1214 Network Door Controller Kit.	27	385	80
AXIS TA1801 Top Cover	AXIS TA1801 Top Cover is compatible with AXIS A1210-B Network Door Controller, ideal for installations that need a full enclosure for extra protection or in plenum spaces. AXIS TA1801 Top Cover is included in AXIS A1210 Network Door Controller.	130	170	110
AXIS TA1802 Top Cover	AXIS TA1802 Top Cover is compatible with AXIS A1610-B Network Door Controller, ideal for installations that need a full enclosure for extra protection or in plenum spaces. AXIS TA1802 Top Cover is included in AXIS A1610 Network Door Controller.	220	240	50
AXIS TA1901 DIN Rail Clip 10PCS	AXIS TA1901 DIN Rail Clip is for standard 35mm DIN rail, and compatible with Axis network door controller and network I/O relay modules.	100	120	43
AXIS TA1902 Connector Kit	Spare connectors for Axis access control products including network door controllers, readers, and network I/O relay modules. AXIS TA1902 Access Control Connector Kit includes 20pcs of 2pos, 20pcs of 4pos, 10pcs of 6pos, 10pcs of 8pos terminal block connectors for Axis network door controller and network I/O relay modules, and 10pcs of 4pos terminal block connector for AXIS A4010-E Reader and AXIS A4120-E Reader with Keypad.	105	150	40
AXIS TA4201 Weathershield	AXIS TA4201 Weathershield, accessory to AXIS A4120-E Reader with Keypad, to protect reader from extreme conditions, such as accumulation of encrusting snow or ice. Glass-fiber reinforced, and UV resistant plastic offers robustness for use in harsh outdoor environment, and easy on the environment with PVC/BCR/CFR free.	62	155	165
AXIS TA4401 BRAILLE LABEL 10P	AXIS TA4401 Braille Label, easy to install accessory to AXIS A4120-E Reader with Keypad, for assisting with keypad entry to sight limited. With the optimized visually impaired reader mode to avoid inadvertent PIN input. UV resistant material offers robustness for use in harsh outdoor environment. And easy on the environment with PVC/BCR/CFR free. One bulk pack comes with 10 units.	90	125	35
AXIS TA4601 Surface Mount	Designed specifically for use with concrete or reinforced concrete walls, AXIS TA4601 Surface Mount creates a cavity that allows for easy and secure cable termination, ensuring a clean and professional installation.	51	28	133
AXIS TA4602 Installation Back Box	AXIS TA4602 Installation Back Box is a mounting accessory, designed to create a cavity for concealing and terminating cables within a wall, ensuring a clean and organized installation.	60	73	126

AXIS TA9001 Wall Mount Bracket 10P	AXIS TA9001 Wall Mount Bracket is a metal bracket designed for AXIS A9210 Network I/O Relay Module and AXIS A9910 I/O Relay Expansion Module wall mounting. It is included in the AXIS A9210 and A9910 packages, sold separately as a spare part, and available in packs of 10.	150	110	40
AXIS TA9901 Cable Strain Relief 5 pcs	AXIS TA9901 Cable Strain Relief secures cables using regular cable ties, preventing plugs from being pulled out or cables becoming loose and disconnected. It is compatible with the AXIS A9910 I/O Relay Expansion Module and the AXIS A9210 Network I/O Relay Module. It is available in packs of 5.	63	170	30
AXIS TA8501 PHYSICAL TAMPERING SW	AXIS TA8501 Physical Tampering Switch is an accessory to be used when the AXIS A8105-E Network Video Door Station is combined with the AXIS A9801 Security Relay. This accessory is a fix to the known issue of the integrated accelerometer showing false tampering alerts.	153	105	39
AXIS A8105-E FLUSH MOUNT	Nice and easy recessed mount of AXIS A8105-E Network video door station suitable for most wall types.	165	240	60
AXIS A9801 SECURITY RELAY	AXIS A9801 Security relay box offer an easy and cost efficient way to improve security for doors controlled by an Axis network video door station. The product bridges the connection between door station and door lock and is placed on the secure side of the door. If an intruder attempt to tamper with the door station to access the door lock wires, AXIS A9801 Security relay will cut the connection and ensure that the door remains securely locked.	115	220	55
AXIS TI8901 FACE PLATE REPLACEMENT	Stainless steel face plate replacement sold as a spare part for AXIS I8016-LVE Network Video Intercom. It enables easy on-site replacement in case the original plate has been damaged or vandalized.	160	178	40
AXIS TI8603 Conduit Adapter 3/4"NPS	Cable protection attachment bracket for AXIS I8016-LVE Network Video Intercom, compatible with 3/4" Conduits.	105	150	40
AXIS TI8602 WALL MOUNT BACK BOX	Wall mount to be used together with AXIS I8016-LVE Network Video Intercom. Highly robust with IK10 and IP69 rating.	140	165	70
AXIS TI8202 RECESSED MOUNT	Recessed mount offering neat installation of AXIS I8016-LVE Network Video Intercom. Multiple mounting and wiring options along with a robust construction makes it suitable for most situations and wall types.	140	165	65
AXIS TI8203 ADAPTER PLATE	Stainless steel adapter plate for mounting AXIS I8016-LVE Network Video Intercom in Code Blue® and Talkaphone® emergency stations and help points. Suitable for new deployments and retrofitting existing installations, it combines intelligent video surveillance with emergency communication—all in a single device.	215	298	30
AXIS TI8204 Recessed Mount White	Nice and easy recessed mount of AXIS I8116-E Network Video Intercom suitable for most wall types.	160	240	80
AXIS TI8204 Recessed Mount Black	Nice and easy recessed mount of AXIS I8116-E Network Video Intercom suitable for most wall types.	160	240	80

AXIS TI8605 Protection Cover Safety	Nice and easy protection cover which increases the perceived robustness for AXIS I8116-E. Available in three colors (safety=orange, white and black)	85	177	70
AXIS TI8605 Protection Cover White	Nice and easy protection cover which increases the perceived robustness for AXIS I8116-E. Available in three colors (safety=orange, white and black)	85	177	70
AXIS TI8605 Protection Cover Black	Nice and easy protection cover which increases the perceived robustness for AXIS I8116-E. Available in three colors (safety=orange, white and black)	85	177	70
AXIS TI8606 Wedge Mount	Nice and easy wedge mount which positions the AXIS I8116-E either 30 degrees left or right when installing it on a wall. This wedge mount can also be used to mount the intercom on poles.	80	150	35
AXIS TI8905 Face Plate Replacement	Stainless steel face plate replacement sold as a spare part for AXIS I7010-VE Network Intercom. It enables easy on-site replacement in case the original plate has been damaged or vandalized.	175	160	38
AXIS A1210 Network Door Controller	A compact edge-based one door controller, suitable for plenum spaces, all powered by one PoE cable. It is fully integrated within Axis end-to-end solutions, this scalable product is optimized for both small and large installations and supports flexible authentication using different types of credentials. Furthermore, with built-in cybersecurity features, it prevents unauthorized access and safeguards your system.	127	169	110
AXIS A1210-B Network Door Controller	The barebone version of A1210, a compact edge-based one door controller, suitable for installation anywhere. It's possible to stack units, ideal for installation in small spaces such as existing or newly installed cabinets. Fully integrated within Axis end-to-end solutions, it's optimized for both small and large installations and supports flexible authentication using different types of credentials.	174	130	64
AXIS A1610 Network Door Controller	This advanced and robust door controller includes everything needed to control two doors—all powered by one PoE cable, featuring four reader connections as well as two Form C relays to power the onboard lock. You can store up to 250k credentials and 250k event logs on the device itself. With built-in cybersecurity features, this smart door controller can internally handle all tasks related to door access—even if the network is down.	260	240	90
AXIS A1610-B Network Door Controller	Barebone version of A1610 Network Door Controller. Sold without a top cover, it offers easy installation with Axis or 3rd party cabinet. This advanced door controller includes everything needed to control two doors—all powered by one PoE cable, featuring four reader connections as well as two Form C relays to power the onboard lock. You can store up to 250k credentials and 250k event logs on the device itself. With built-in cybersecurity features, this smart door controller can internally handle all tasks related to door access—even if the network is down.	260	240	90

AXIS A1214 Door Controller Kit	This all-in-one, out-of-the-box-ready kit can control up to four doors. It includes four AXIS A1210-B units enclosed in AXIS TQ1808-VE, a robust, vandal-resistant IK10- and NEMA 4x-rated cabinet. Fully integrated within Axis end-to-end solutions, it offers fast and easy installation	285	500	395
AXIS A1710-B Network Door Controller	This compact, cost-efficient door controller gives you full control for up to four doors including support for up to eight OSDP readers and eight locks. With onboard lock power, this all-in-one multi-door controller simplifies complex installations	166	39	210
AXIS A1810-B Network Door Controller	This compact, cost-efficient door controller gives you full control for up to eight doors including support for up to 16x OSDP readers and 16x locks. With onboard lock power, this all-in-one multi-door controller simplifies complex installations.	166	29	327
AXIS Door Controller Extension	Single unit e-license for AXIS Door Controller Extension This AXIS Camera Application Platform (ACAP) based application empowers Axis network door controllers to support additional features or integrations to extend the capability of the door controller. For example, wireless locks integration to support up to additional 16x wireless doors per door controller. Delivered as eLicense key. One license key per unit. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
AXIS A1601	With door controllers from Axis, you install one smart, independent device by each door to create a scalable access control system. The open platform allows you to mix and match best-of-breed software and hardware, and enables easy integration with other systems such as video surveillance, intrusion detection, and time and attendance. AXIS A1601 Network Door Controller is ideal for advanced access management in mid-sized and large, multi-site installations using third-party software (no embedded Entry Manager software). It has a powerful processor, expanded storage and memory, relays, and I/O ports. AXIS A1601 is powered by PoE+ and can also power connected equipment	240	255	90
AXIS A1001 Network Door Controller	AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS)	225	220	75

AXIS A1001 BULK 10PCS Network Door Controller	AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	360	430	240
AXIS A9210 Network I/O Relay Module	AXIS A9210 offers ten I/O ports including two configurable I/Os, five inputs, three outputs, and one form C relay output, allowing you to extend the functionality of any Axis product or third-party system. You can monitor inputs from cameras, analytics, alarm buttons, environmental sensors, and more, it's easy to integrate with third-party advanced security systems such as VMSs, and alarm and intrusion systems. Furthermore, with multi-drop technology, you can add up to 16 expansion modules, AXIS A9910, for 128 I/Os, and 64 relays using just one IP connection.	113	166	50
AXIS A9910 I/O Relay Expansion Module	Featuring multi-drop technology, it's possible to connect up to 16 AXIS A9910 I/O Relay Expansion Modules to one AXIS A9210 device. 128 I/Os and 64 relays using just one PoE cable—no need for an extra network cable drop. This ensures a cost-effective installation and saves you time and effort. Plus, Modbus sensor ports let you integrate environmental sensors such as temperature and humidity sensors.	180	145	50
AXIS A9161 NETWORK I/O RELAY MODULE	AXIS A9161 Network I/O Relay Module has 6 configurable I/Os with supervised inputs and a relay. The module reacts on inputs, such as signals from PIR motion detectors or switches, to trigger actions. Supplying power to I/O devices, it can extend the functionality of Axis products where additional I/Os or relays are needed. Its enclosure makes installation easy and flexible. -6 I/Os and 1 form C relays -12 and 24 V DC output/input or PoE+ -Based on Axis open platforms, VAPIX and ACAP -Used with AXIS Camera station or third-party software	165	245	80

AXIS A9188 NETWORK I/O RELAY MODULE	AXIS A9188 Network I/O Relay Module is an intelligent module with 8 configurable I/Os and 8 form C relays and supports supervised inputs. Open API, including VAPIX, for software integration. High level of integration with AXIS A1001 Network Door Controller for elevator control for floor management etc. Supported by AXIS Video Hosting System, AXIS Camera Station and third party partner software. The module provides 12 and 24 V DC output to I/O devices and can extend the functionality of any Axis product where you need additional I/Os or relays. Powered by PoE+ or 12 and 24 V DC input	165	240	80
AXIS A9188-VE NETWORK I/O RELAY MODULE	AXIS A9188-VE Network I/O Relay Module comes with AXIS T98A15-VE Surveillance Cabinet making it outdoor-ready, vandal-resistant, and UL294-approved. With its 8 configurable I/Os and relays, its open platform enables a high level of integration with AXIS A1001 Network Door Controller and other facility systems. -8 I/Os with supervised inputs and 8 form C relays -UL294-approved with cabinet AXIS T98A15-VE Surveillance Cabinet -12 and 24 V DC output/input or PoE+ -Open API, support for VAPIX, ACAP -Used with AXIS Camera station or third-party software	300	395	155
AXIS I8016-LVE	AXIS I8016-LVE Network Video Intercom is a compact and highly robust network intercom for two-way communication, video and remote entry control. with exceptional audio quality, including echo and noise cancellation, and a 5MP camera with invisible IR night vision and 140° FOV, the unit offers reliable 24/7 identification and remote entry control also in the most demanding situations. Based on open IP standards and interfaces such as ONVIF, PoE and SIP, AXIS I8016-LVE Network Video Intercom offers great integration possibilities and is a perfect complement to any video surveillance system.	150	155	68
AXIS I8116-E White	AXIS I8116-E is a small and powerful network video intercom. It operates as a communication device and full-fledged security camera at the same time, providing 5MP video, audiovisual identification, two-way communication and remote entry control as an intrinsic part of video surveillance. Open standards such as ONVIF and Session Initiation Protocol (SIP) in combination with its small size, give unique opportunities for system design, integration and installation. Wide Dynamic Range (WDR) and efficient noise cancellation ensure uncompromised performance in demanding situations, such as strong backlight or surrounding noise.	110	165	55

AXIS I8116-E Black	AXIS I8116-E is a small and powerful network video intercom. It operates as a communication device and full-fledged security camera at the same time, providing 5MP video, audiovisual identification, two-way communication and remote entry control as an intrinsic part of video surveillance. Open standards such as ONVIF and Session Initiation Protocol (SIP) in combination with its small size, give unique opportunities for system design, integration and installation. Wide Dynamic Range (WDR) and efficient noise cancellation ensure uncompromised performance in demanding situations, such as strong backlight or <u>surrounding noise</u> .	110	165	55
AXIS I7010-VE	With 92db SPL, this robust intercom delivers great audio quality with echo cancellation and noise reduction. It doesn't include a camera, so privacy is always guaranteed. Featuring an anti-ligature design, IP66/IP69-rated and a vandal-resistant IK10-rated casing, makes this intercom a <u>perfect fit in high security environments</u> .	150	150	65
AXIS I7010-VE Safety	With 92db SPL, this robust intercom delivers great audio quality with echo cancellation and noise reduction. The orange color in RAL 2004 ensures high visibility for various safety application. IP66/IP69-rated and a vandal-resistant IK10-rated casing, makes this intercom a <u>perfect fit in high security environments</u> .	158	155	65
AXIS I7020	This cleanable intercom in a 2-gang form factor is the perfect fit for various indoor applications with high requirements for air cleanliness. With a certification for ISO 14644-14 grade 3-9 it suits applications within the pharmaceutical industry or clean rooms for example.	55	52	60
AXIS A4020-E Reader	AXIS A4020-E Reader is designed to perfectly match Axis network door controllers and Axis credentials, Ideal for use in harsh environments both indoors and outdoors, it features a mullion-mount design to fit perfectly in narrow spaces and door frame installations. It supports most types of smart RFID card standards with 13.56MHz credential technologies and includes out-of-the-box support for Open Supervised Device Protocol (OSDP). Packed with built-in cybersecurity features, it helps prevent unauthorized access and safeguards your system. Furthermore, this smart reader supports Secure Communication Protocol (SCP) enabling secure communications and connections. COO: European Community	165	110	40

AXIS A4120-E Reader with Keypad	AXIS A4120-E Reader with Keypad, offers secure and seamless entry, designed to perfectly match Axis network door controllers and Axis credentials. IP66, IK07 ratings for use in harsh environments and the intuitive touch keypad offers unlimited touches. It supports most types of smart RFID card standards with 13.56MHz technologies and includes out-of-the-box support for Open Supervised Device Protocol (OSDP) and Secure Channel Protocol (SCP).	150	168	40
	COO: European Community			
AXIS A4612 Network Bluetooth® Reader	AXIS A4612 Network Bluetooth® Reader offers convenient access using your mobile phone. It supports most types of RFID card standards with 13.56MHz credentials. IP55-rated, ready for installation both indoors and outdoors. With PoE, you can connect to the closest network switch with a single cable for both power and connectivity- no need to wire back to the door controller.	50	27	133
AXIS BARCODE READER	Single unit e-license for AXIS Barcode Reader Convenient and cost-effective, AXIS Barcode Reader seamlessly turns Axis intercom or camera into a QR code reader for reliable credential or access control management. This IP- and AXIS Camera Application Platform (ACAP)-based application is fully integrated with AXIS Camera Station Secure Entry for reliable QR code entry for visitors. Visit www.axis.com for supported products and application download. Delivered as eLicense key. One license key per unit. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
AXIS 4IN1 SECURITY SCREWDRIVER	The AXIS 4-in-1 Security Screwdriver Kit is a great tool for installing Axis products. The kit features two double-sided insert bits type that match Axis products using tamper resistant torx and standard philips head. The kit comes with a quick-release, non-slip rubber handle, and a velcro-sealed polyester pouch with belt clip. Insert bits material in chrome vanadium (TR10+PH1) and in stainless steel (TR20+TR30).	165	180	45
AXIS Q17 FRONT WINDOW KIT B	Accessory front window assembly in polycarbonate for AXIS Q1785/86-LE, IK10 rated. Not recommended for installation that requires more than 22x optical zoom.	180	160	30
GASKET A CABLE 3,5-7MM 10PCS	M20 Gasket for cable diameter 3,5mm to 7mm. 10 pcs.	110	165	20
ACC TOOL STEEL STRAP	Tool for steel strap tensioning. For use with 21764 and AXIS T91A67	95	310	60
AXIS GASKET M16 5-8 MM 10PCS	IP66 cable gasket for M16 holes (max 17mm). By using the included CONNECTOR GUARD A over the RJ45 connector, you do not need to re-terminate the network cable which gives a much faster and more secure installation. Suitable for cable diameters between 5-8mm. Black color. 10 pieces (bulk pack).	100	130	30
GASKET B M20 CABLE 6-13MM 10PCS	M20 Gasket for cable diameter 6-13mm, 10 pcs.	110	160	20
GASKET C M25 CABLE 8-17MM 10PCS	M20 Gasket for cable 8-17mm, 10 pcs.	110	170	20

AXIS TQ3901 Gasket M20 Cable	10 cable gaskets compatible with Q3819-PVE, Q1951-E, Q1952-E. 10 pcs of 2013186 GASKET CABLE 21,5x4 and 1 pcs of 1327329 TOOL MOUNTING RJ45 E1.	70	115	52
CABLE GLAND A M20 5PCS	M20 cable gland, 5 pcs.	150	175	25
GASKET C M20 10PCS	This gasket is specially made for flexible and easy installation. By using the included CONNECTOR GUARD A over the RJ45 connector, you do not need to re-terminate the network cable which gives a much faster and more secure installation. Made for M20 holes and cables from 5 to 15mm in outer diameter. 10 pcs.	100	150	10
CABLE GASKET M20 3MM 10PCS	M20 gasket for small cables like I/O and audio cables. 10 pcs	105	155	35
LENS TOOLKIT P39XX-R 4 PCS	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS P39xx-R cameras with the standard lens and the 2.8 mm accessory lens. Content: Lens tool, Allen key and Opening tool. 4 pcs of each.	100	150	2
CABLE GLAND A M25 5PCS	M25 Cable gland, 5 pcs.	150	170	30
CABLE GLAND M20x1.5 RJ45 5PCS	M20 cable gland for RJ45. Ease of installation, no need of cutting the cable.	150	245	30
AXIS M3025-VE LENS M12 6MM	Optional lens for AXIS M3025-VE, 6mm. Including focus ring.	105	155	35
LENS M12 6MM F1.9 4PCS	Accessory lens 6 mm, F1.9 with M12 thread and built in IR-cut filter for AXIS F1005-E and FA1105. Tool for removing the standard lens is included. 4 Pcs.	105	150	37
LENS M12 16MM F1.8 4PCS	Accessory lens 16 mm, F1.8 with M12 thread and built in IR-cut filter for AXIS F1005-E and FA1105. Tool for removing the standard lens is included. 4 Pcs.	105	150	37
LENS M12 12MM F1.6 4P	LENS M12 12MM F1.6 Q6100-E, Q6010-E	165	180	45
LENS M12 25MM F2.4 4P	LENS M12 25MM F2.4 4P Q6100-E	165	180	45
LENS M12 16MM F1.8 4P	LENS M12 16MM F1.8 Q6010-E Q6100-E	165	180	45
LENS M12 6MM F2.0 4P	LENS M12 6MM F2.0 Q6010-E Q6100-E	165	180	45
AXIS WEATHERSHIELD K	Weathershield for AXIS P14 Series designed for use in rainy and windy environments.	58	240	100
LENS M12 2.8 MM F1.2 10P	Megapixel lens 2.8 mm, F1.2 with M12 thread for AXIS P3904-R Mk II and P3905-R Mk II cameras that provides 110° horizontal FOV and excellent low light performance. Coated with IR-cut filter. 10 pieces bulk pack.	160	235	80
ACC LENS M12 6MM F1.6 10 PCS	Megapixel lens 6 mm, F1.6 with M12 thread for AXIS P39-R Series that provides 52° horizontal FOV with these cameras. With IR filter. 10 pieces.	165	240	80
ACC LENS M12 8MM F1.6 10 PCS	Megapixel lens 8 mm, F1.6 with M12 thread for AXIS P39-R Series that provides 40° horizontal FOV with these cameras. With IR filter. 10 pieces.	165	240	80
ACC LENS M12 3.6MM F2.0 10PCS	Megapixel lens 3.6 mm, F2.0 with M12 thread for AXIS P39-R Series that provides 87° horizontal FOV with these cameras. With IR filter. 10 pieces. Can be used as a spare part for AXIS P39-R or as a wider FOV option for P3905-RE.	165	240	80
AXIS LENS M12 2.1MM F2.2 10PCS	Megapixel lens 2.1mm, F2.2 with M12 thread for AXIS P39-R Series that provides 147° horizontal FOV with these cameras. With IR filter. 10 pieces. Lens tool included.	110	155	35
AXIS LENS M12 2.1 MM F1.8 IR 10P	2.1 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	160	243	80

AXIS LENS M12 3.6 MM F1.8 IR 10P	3.6 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	160	243	80
AXIS LENS M12 6.0 MM F1.9 IR 10P	6.0 mm accessory lens, F1.9 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	160	243	80
AXIS LENS M12 8.0 MM F1.8 IR 10P	8.0 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	160	243	80
ACC LENS M12 MEGAPIXEL 6PCS	2 pieces each of 2.8 mm (F2.0), 6 mm (F1.6) and 8 mm (F1.6) Megapixel lenses with M12 thread. For use with AXIS P39-R cameras. Includes lens tools.	165	180	40
THEIA LENS CS VARIF 1.8-3MM DC-IRIS	Barrel distortion corrected and IR corrected wideangle lens for cameras up to 5 mega pixel resolution. Compatible with e.g. AXIS M1114/-E, AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.	120	130	95
LENS CS VARIF 9-40MM DC-IRIS D/N	Varifocal IR-corrected lens for cameras up to 5 mega pixel resolution. Compatible with e.g. AXIS M1114/-E, P1354/-E, P1355/-E, P1357/-E, Q1602/-E, Q1604/-E.	120	130	95
LENS CS VARIF 9-40MM P-IRIS D/N	Varifocal IR-corrected P-iris tele lens compatible with AXIS P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.	120	130	95
LENS COMPUTAR CS 12.5-50MM DC-IRIS	Varifocal IR-corrected lens with DC-Iris. Compatible with e.g. AXIS P1353/-E, P1354/-E. Axis Q1602/-E, Q1604/-E.	120	130	95
LENS COMPUTAR CS 12.5-50MM P-IRIS	Varifocal IR-corrected lens with P-Iris. Compatible with e.g. AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E, AXIS P1355/-E, P1357/-E.	120	130	95
LENS COMPUTAR i-CS 2.8-8.5MM	Standard lens for AXIS Q1615 MkII with remote zoom based on the new standard i-CS.	120	130	95
LENS FUJINON C CS 8-80MM DC	Varifocal IR-corrected lens with DC-Iris. For use with both C-mount and CS-mount cameras thanks to the included adapter. Compatible with e.g. AXIS Q1635.	120	130	95
RICOM 2MP LENS DC-IRIS 8-26MM F0.9	Lens RICOM 2 MP DC-iris CS-Mount Varifocal 8-26MM F0.9. Recommended for AXIS Q1645/-LE.	120	170	125
LENS CS 12-50 MM F1.4 P-IRIS 8MP	Varifocal IR-corrected 12-50 mm P-Iris lens for cameras up to 8 megapixel resolution and 1/1.8" sensor . Compatible with e.g. AXIS Q1615/-LE MK II, AXIS Q1645/-LE, AXIS Q1647/-LE, AXIS P1377/-LE and P1378/-LE.	120	130	95
LENS I-CS 9-50 MM F1.5 8MP	Varifocal IR-corrected 9-50 mm i-CS lens for cameras up to 8 megapixel resolution and 1/1.8" sensor. Motorized zoom, focus and P-iris. Compatible with e.g. AXIS Q1645/-LE, AXIS Q1647/-LE, AXIS P1377/-LE and P1378/-LE.	132	121	94
Lens i-CS 3.9-10 mm F1.5 8 MP	Spare varifocal i-CS lens for AXIS Q1645/-LE and AXIS Q1647/-LE.	120	130	95
Lens CS 2.8 - 13 mm F1.4 DC-Iris 5 MP	Tamron varifocal CS mount lens with DC-Iris and focal length 2.8 – 13 mm F1.4. It supports cameras up to 5 megapixels and is compatible with selected cameras from AXIS M11 Network Camera Series.	120	130	95

AXIS TM3808-E Skin Cover Black 4P	4 pack of outdoor-ready skin covers compatible with AXIS M3077-PLVE for changing the appearance of the camera, simplify re-painting and covering screws. Black color. 4 pcs per pack.	165	175	145
LENS CS 3-10.5 MM DC-IRIS 2 MP	Ricom varifocal CS mount lens with DC-Iris and focal length 3 - 10.5 mm F1.4. It supports cameras up to 2 megapixels and is compatible with selected cameras from AXIS M11 Network Camera Series.	120	130	95
AXIS LENS CLOTH 10PCS	Axis accessory lens cloth. 10 pack	165	180	40
AXIS LENS CLOTH 50PCS	Axis accessory lens cloth. 50 pack	165	240	80
SURVEILLANCE STICKER ENG 10PCS	Axis branded sticker showing a Camera. Text: Video surveillance in operation	205	150	5
SURVEILLANCE STICKER ENG 50PCS	Axis branded sticker showing a Camera. Text: Video surveillance in operation	205	150	15
RADAR DETECTION STICKER EN 10PCS	Axis branded sticker showing a radar detection illustration. Text: Radar detection in operation	220	150	3
AXIS WEATHERSHIELD KIT C	Heavy duty outdoor weathershield for wall mounted AXIS fixed dome cameras. Designed to protect the dome from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use with camera's built-in IR LEDs.	177	211	168
AXIS PT IR ILLUMINATOR KIT C	850nm IR LED illuminator kit compatible with AXIS T99A Positioning Units for visual cameras. Kit includes one pair of IR illuminators, one metal mounting bracket, and three different diverging lenses. Note: this is the same illuminator kit as used in AXIS Q8685-LE PTZ Network Camera.	440	260	150
AXIS T99 ILLUMINATOR BRACKET KIT A	Bracket kit for installing a pair of compatible illuminators to Axis positioning cameras and positioning units. Designed for use with AXIS Q8685-E and AXIS T99A10. Compatible with selected T90 white-LED and IR-LED illuminators. Includes fitting brackets, illuminator connectors, screws, washers, cable glands and cable ties. Illuminators sold separately.	265	440	145
AXIS WASHER KIT B	Washer kit for spraying cleaning fluid on the windows of AXIS positioning cameras and positioning units. The kit contains a 23 litre tank, pump for delivery up to 11m (36ft), tube, nozzle and custom-made mounting bracket for the nozzle.	325	385	505
AXIS TQ6905-E WASHER KIT	Washer kit for spraying cleaning fluid on the windows of AXIS positioning cameras and positioning units. The kit contains a 23 litre tank, pump for delivery up to 11m (36ft), tube, nozzle and custom-made mounting bracket for the nozzle. This washer kit compatible with Q6215 and as well requires seperate ordering of T6101 I/O since Q6215 does not have I/O.	330	390	515
AXIS BIRD CONTROL SPIKE 10P	Bird control spikes made of flexible UV-resistant polymer preventing birds from landing on cameras or mounts. Each module has five spikes and can be mounted on flat or curved surfaces using the pre-mounted adhesive or cable ties (not included). The modules can be connected lengthwise and/or widthwise to cover a larger area. 10 pcs.	120	115	115
AXIS SAFETY WIRE 3M 5P	Stainless steel safety wire 3 m (10 ft) long, with a fixed loop in one end and an adjustable loop with a plated brass wire lock in the other. Suitable for both indoor and outdoor use.	125	135	35

AXIS F7301 CABLE BLACK 1M 4PCS	Black cable with RJ12 and micro USB connectors for indoor Sensor Units. Length 1 m (39 in.) 4 pcs.	150	150	37
AXIS F7315 CABLE WHITE 15M 4PCS	AXIS F7315 comes in packs of four. 15-m (49 ft.) white cable with an RJ12 connector for connection to an AXIS F1004 Sensor Unit or AXIS FA-series sensors.	190	185	120
AXIS P13 WEATHERSHIELD EXTENSION A	AXIS P13 Weathershield Extension A for AXIS P1375-E. For mounting on AXIS P13 Series camera providing additional protection against rain, snow and sunlight.	320	180	150
M12(F)-RJ45(M) CABLE 0.5M (1.6FT)	M12 D-Code 4-pin (Female) to RJ45 (Male) Ethernet cable, CAT5E. Length: 0.5m (1.6ft). Cable outer diameter: 6.2mm (0.25"). Color: Black. Outdoor UV and sunlight resistant. Tested operational for shock and vibration according to requirements for rolling stock and ground vehicle installations. Compatible with all Axis network video products with female RJ45 Ethernet port 802.3af and 802.3at (up to 30W).	130	140	35
AXIS TM1803 WEATHERSHIELD EXTENSION	weathershield extension over M1135/37-E where entire top cover kit not wanted (TM1802)	160	175	40
AXIS TV5901 Control Board Adapter	AXIS TV5901 Control Board Adapter is a cable to connect AXIS V5925 and AXIS V5938 to joystick, keypad and other controllers supporting VISCA protocol.	140	100	30
TP6901-E ADAPTER BRACKET P56	Adapter bracket that allows Axis P56-series to be connected to Q6100. The material is PC+ABS Cyclicoloy C6600 GY8D352 and comes in Axis White.	150	180	30
AXIS TD4801 Sunshield 4pcs	AXIS TD4801 Sunshield is the perfect accessory for when AXIS D4100-E Network Strobe Siren is used in conditions where sunlight would shine directly on the device. It is easy to mount, without the need to take AXIS D4100-E down. The accessory comes in a 4 pack.	260	250	130
AXIS TQ6906-E Protection Ring	Additional protective ring for AXIS Q6215-LE and AXIS Q6225-LE. The purpose of it is to stop rain, melt water, sleet and snow from entering the gap between the moving parts in sub-zero environments, preventing the pan axle to be frozen solid. Pan movement protection instead. Protects against water, and large pieces from entering the gap.	160	178	37
AXIS TP3818-E CASING BLACK	AXIS TP3818-E Casing Black, is a black casing and is offered as an optional accessory for AXIS P4705-PLVE and P4707-PLVE. Does not include dome.	140	230	95
AXIS TU6004-E CABLE 8M	AXIS TU6004-E Cable 8m is a 8m (26ft) cable used for the 2nd generation F-series. It has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6004-E Cable 8m is outdoor rated and complies with IP66 and IP6K9K. It has a 5mm (0,2 in) diameter and a 40mm (1,6 in) bending radius. AXIS TU6004-E Cable 8m can be shorten and re-crimped on the FAKRA side only thanks to AXIS TU6003 Conn kit FAKRA, 10P (sold separately).	210	210	40

AXIS TU6004-E CABLE 30M	AXIS TU6004-E cable 30m is a 30m (98ft) cable used for the 2nd generation F-series. It has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6004-E Cable 30m is outdoor rated complying with the IP66 and IP6K9K standards. It has a 5mm (0,2 in) diameter and a 40mm (1,6 in) bending radius. AXIS TU6004-E Cable 30m can be shorten and re-crimped on the FAKRA side only thanks to AXIS TU6003 Conn kit FAKRA, 10P (sold separately).	260	260	60
AXIS TU6004-E CABLE 1M 4P	AXIS TU6004-E Cable 1m 4P is a bulk pack of 4x 1m (3ft) cables used for the F-series. TU6004-E Cable 1m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6004-E Cable 1m is outdoor rated and complies with the IP66 and IP6K9K standards. It has a 5mm (0,2 in) diameter and a 40mm (1,6 in) bending radius. AXIS TU6004-E Cable 1m can be shorten and re-crimped on the FAKRA side only thanks to AXIS TU6003 Conn kit FAKRA 10P (sold separately).	160	160	50
AXIS TU6004-E CABLE 8M 4P	AXIS TU6004-E Cable 8m 4P is a bulk pack of 4x 8m (26ft) cables used for the F-series. TU6004-E Cable 8m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6004-E Cable 8m is outdoor rated and complies with the IP66 and IP6K9K standards. It has a 5mm (0,2 in) diameter and a 40mm (1,6 in) bending radius. AXIS TU6004-E cable 8m can be shorten and re-crimped on the FAKRA side only thanks to AXIS TU6003 Conn kit FAKRA, 10P (sold separately).	175	220	222
AXIS TU6002 RIGHT-ANGLE SMA ADP 10P	AXIS TU6002 Right Angle SMA ADP 10p is a bulk pack of 10x 90° angle adapters. The accessory is an accessory of the AXIS F21 sensors. The 90° angle adapter helps installing a sensor in tight space without bending AXIS TU6004, AXIS TU6007 and AXIS TU6005 cable <u>and potentially damaging it.</u>	68	118	29
AXIS TU6003 Conn Kit FAKRA 10P	AXIS TU6003 Conn Kit FAKRA 10p is a bulk pack of 10x replacement FAKRA connectors. In this kit, you have all the necessary accessories to re-crimp AXIS TU6004-E Cable with the new FAKRA connector. AXIS TU6004-E Cable can only be cut and re-crimped on the FAKRA connector end.	105	150	38
AXIS TU6009 CONN 6-PIN 2.5MM 10P	AXIS TU6009 Conn 6-pin is a male connector for I/O port . Pitch: 2.50 mm. 6pos terminal block. 10pack	70	120	30
AXIS TU6008 CONN 5-PIN 2.5MM 10P	AXIS TU6008 Conn 5-pin is a male connector for RS port . Pitch: 2.50 mm. 5pos terminal block. 10pack	70	120	30

AXIS TP6902-E ADAPTER BRACKET	Adapter bracket that allows Axis P5676-LE to be connected to Q6100. The material is PC+ABS Cycology C6600 GY8D352 and comes in Axis White.	145	175	30
AXIS TU9004 Wireless Dongle	Wireless USB dongle for AXIS M1075-L Box Camera. This allows the camera to communicate with 2.4 GHz and 5 GHz frequency. The wireless adapter supports 802.11ac/b/g/n. Requires PoE injector to power the camera.	7	52	15
AXIS TU6007-E CABLE 1M 4P	AXIS TU6007-E Cable 1m 4P is a bulk pack of 4x 1m (3ft) thin cables used for the 2nd generation F-series. AXIS TU6007-E Cable 1m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6007-E Cable 1m is indoor/outdoor rated and complies with the IP66 standard. It has a 3mm (0,1 in) diameter with a 30mm bending radius. This cable is ideal when used in very tight spaces and when the cable needs to be bended.	160	150	30
AXIS TU6007-E CABLE 8M	AXIS TU6007-E Cable 8m is a 8m (26ft) thin cable used for the 2nd generation F-series. AXIS TU6007-E Cable 8m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6007-E Cable 8m is indoor/outdoor rated and complies with the IP66 standard. It has a 3mm (0,1 in) diameter with a 30mm bending radius. This cable is ideal when used in very tight spaces and when the cable needs to be bended.	160	150	30
AXIS TU6007-E CABLE 8M 4P	AXIS TU6007-E Cable 8m 4P is a bulk pack of 4x 8m (26ft) thin cables used for the 2nd generation F-series. AXIS TU6007-E Cable 8m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6007-E Cable 8m is indoor/outdoor rated and complies with the IP66 standard. It has a 3mm (0,1 in) diameter with a 30mm bending radius. This cable is ideal when used in very tight spaces and when the cable needs to be bended.	155	165	80
AXIS TS3901 Rail Extensions	AXIS TS3901 Rail Extensions allow AXIS S3016 Recorder to be mounted in deep server racks with a post to post distance between 499mm (19.6in) and 690mm (27.1in). No rails extensions are needed for a post to post distance between 376mm (14.8in) and 499mm (19.6in). Each rail extension is composed of two parts which replace two segments of the original rails provided with AXIS S3016 Recorder.	65	545	40
AXIS TU6011 Mains Cable	AXIS TU6011 Mains Cable is compatible with AXIS TU8004 90 W Midspan. It comes with a country specific power cord and plug.	105	260	60

AXIS TU6011 Mains Cable 10 pcs	AXIS TU6011 Mains Cable is compatible with AXIS TU8004 90 W Midspan. It comes with a country specific power cord and plug. 10 pcs package.	230	215	95
LENS M12 2.8 mm F1.2 10 pcs	Megapixel lens 2.8 mm, F1.2 with M12 thread for AXIS P3905-R Mk III and AXIS M3905-R cameras. It provides that provides 110° horizontal FOV and excellent low light performance. Coated with IR-cut filter. 10 pieces bulk pack.	160	235	80
AXIS TQ1930-E Front Window Kit	Accessory front window kit compatible with: AXIS Q1805-LE, AXIS Q1806-LE. Includes 4 TX10 screws and window assembly. Includes window front that TQ1929-E doesnt have.			
AXIS TQ1932-E Front Window Kit	Accessory Window Kit compatible with AXIS Q1808-LE 150 mm. Includes IR window, adhesive window, and optical window.			
AXIS TQ6903-E ADAPTER Q60 SERIES	Mounting adapter bracket for AXIS Q6074-E, AXIS Q6075-E, AXIS Q6078-E.	160	245	76
AXIS TQ6904-E ADAPTER Q61 SERIES	Mounting adapter bracket for: AXIS Q6135-LE, AXIS Q6315-LE, AXIS Q6318-LE.	160	245	76
AXIS T92E05 PROTECTIVE HOUSING	Protective camera housing for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	240	550	220
AXIS T92E20 OUTDOOR HOUSING	Outdoor PoE camera housing with window-/camera heaters and fan for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X-, Vibration 4M3 rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	240	550	220
AXIS T92F10 OUTDOOR HOUSING 6PCS	Metal camera housings with heater and blower for Axis Network Cameras. Weathershields included. Housings can be powered with 24VAC. 6-piece pack. Required accessory: AXIS T94X01A Wall Mount 6PCS (sold separately) Optional accessory: AXIS T94Y01G Pole Mount 6PCS (sold seperately)	205	540	185
AXIS TQ1809-LE HOUSING T92G	Outdoor PoE+ camera housing with IR illumination, window & camera heaters, and fan. Compatible with AXIS P1375, AXIS P1377, AXIS P1378, AXIS Q1615 Mk III, AXIS Q1615-LE Mk III, AXIS Q1645, AXIS Q1647, AXIS Q1715. Polycarbonate sunshield, aluminum wall mount and torx screwdriver included.	290	710	270
AXIS T93C10 OUTDOOR HOUSING	Outdoor camera housing for Axis cameras with EF lenses (e.g.:Q1656, Q1656-B, P1375, P1377, P1378). Made of IK10 impact resistant thermoplastic with dual-layer UV protection. IP66, NEMA 4X rated and UL listed. Powered by 24 VDC (power supply not included). Heavy duty wall mount included.	339	573	225
AXIS T93C EXTENSION KIT	Extension kit to allow mounting of longer lenses in AXIS T93C10 Outdoor Housing (e.g.: compatible with AXIS Q1659 55-250 mm). Includes built-in sunshield and front window. The extension kit provides an extra space of 80mm in length within the housing, giving a total length of 380mm for the camera and lens. The part of the lens within the extension kit can have maximum diameter of 75mm.	140	190	140

AXIS T93F05 PROTECTIVE HOUSING	Fixed box protective camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Compatible with AXIS P13 Series and AXIS Q16 Series. AXIS T94Q01A Wall mount included.	158	386	128
AXIS T93F10 OUTDOOR HOUSING 24VAC/12-24VDC	Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by 24 V AC or 12-24 V DC. Compatible with AXIS P13 Series, AXIS Q16 Series, and M11 Series. AXIS T94Q01A Wall mount included. AXIS P1353/P1354/P1355/P1357 and AXIS Q1604/Q1614: -40 °C to 50 °C (-40 °F to 122 °F) AXIS P1365 and AXIS Q1615/Q1635: -40 °C to 55 °C (-40 °F to 131 °F). AXIS Q1645/Q1647: -40 °C to 40 °C (-40 °F to 104 °F) AXIS M1124/M1125: -40 °C to 55 °C (-40 °F to 131 °F)	158	386	128
AXIS T93F20 OUTDOOR HOUSING POE	Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by PoE IEEE802.3af. Compatible with AXIS P13 Series, AXIS Q16 Series and M11 Series. AXIS T94Q01A Wall mount included. Temperature range: AXIS P1353/P1354/P1355/P1357 and AXIS Q1604/Q1614: -40 °C to 50 °C (-40 °F to 122 °F), AXIS P1365 and AXIS Q1615/Q1635: -40 °C to 55 °C (-40 °F to 131 °F), AXIS Q1645/Q1647: -40 °C to 40 °C (-40 °F to 104 °F), AXIS M1124/M1125: -40 °C to 55 °C (-40 °F to 131 °F).	158	386	128
AXIS SUNSHIELD A	Accessory sunshield and weather protection for AXIS T93F Housing Series	163	420	93
AXIS T98A15-VE SURVEILLANCE CABINET	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included.	327	378	169
AXIS T98A16-VE SURVEILLANCE CABINET	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS M111X-E, P13XX-E, Q16XX-E, Q1755-E, Q191X-E Q192X-E.	327	378	169
AXIS T98A17-VE SURVEILLANCE CABINET	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS P33-VE/-LVE.	327	378	169

AXIS T98A18-VE SURVEILLANCE CABINET	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS T91B61 Wall bracket for use with AXIS P55, P56, Q60 and Q61-series or fixed dome pendant kits.	327	378	169
AXIS T98A19-VE SURVEILLANCE CABINET	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS P5414-E/15-E.	327	378	169
AXIS T98A SUNSHIELD	Metal sunshield for AXIS T98A-VE Surveillance Cabinet series. Reduces the temperature inside the cabinet, caused by sun radiation, with up to 15°C (27°F).	160	315	370
AXIS CABINET LOCK A	Door lock for AXIS T98A surveillance cabinet. Uses a generic key but it is possible to change locking cylinder to a unique key solution (not supplied from Axis)	70	220	50
CORRIDOR FORMAT BRACKET A	The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F05 and AXIS T93F20 housings to enable a vertically oriented, "portrait"-shaped video stream from the camera. Includes built-in camera heater (only applicable when mounted in AXIS T93F20).	120	135	95
CORRIDOR FORMAT BRACKET B	The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F10 housing to enable a vertically oriented, "portrait"-shaped video stream from the camera. Included with built-in camera heater.	120	130	95
AXIS T92E CAMERA HOLDER PLATE C	Camera holder plate for mounting an AXIS Q1614 in a AXIS T92E05 and AXIS T92E20 housing. Or change the camera unit inside an AXIS P135X-E outdoor camera.	105	155	35
AXIS T92E CAMERA CHANGE KIT A	Kit for mounting an AXIS Q1614 in a AXIS T92E05/AXIS T92E20 housing produced before 2014. Or change the camera unit inside an AXIS P134X-E outdoor camera.	210	325	100
AXIS TQ1808-VE SURVEILLANCE CABINET	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, and midspan from tough weather and vandalism. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Similar to T98A15 but door is deeper by 4" allowing door to be shut with power supply and switch in it.	315	410	275
AXIS TP3826-E housing	AXIS TP3826-E housing is an outdoor housing for selected AXIS M39 and P39 cameras. It enables the cameras to be mounted outside vehicles such as buses, trams, trucks or emergency vehicles.	185	200	80

AXIS TQ1817-VE Surveillance Cabinet	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, and midspan from tough weather and vandalism. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Similar to T98A17 compatible with dome, fixed, thermal cameras but door is deeper by 4" allowing door to be shut with power supply and switch in it.	410	320	270
AXIS TM1804-LE Housing 6 pcs	6 pack Outdoor AC/DC powered camera housing with window/camera heaters and fan compatible with: AXIS M1135 Mk II, AXIS M1137 Mk II, AXIS P1385-B, AXIS P1387-B, AXIS P1388-B. Die cast aluminum casing and polycarbonate sunshield. The housing is IP66-, Nema 4X-, Vibration 4M3 rated and IK10 impact-resistant. Note wall mount purchased separately (AXIS T94X01A Wall Mount).	563	628	390
AXIS M3044-VI45-VI46-V VIEW PROT 5P	Viewing protector that makes it harder to see where the camera is aiming. For use when the camera is used without dome. 5 pcs.	140	200	40
AXIS M30 SKIN COVER A BLACK 4P	4-pack. Outdoor-ready skin covers compatible with AXIS M3057/58-PLVE cameras for changing the appearance of the camera, simplify re-painting and covering screws. Black color.	165	185	160
AXIS M30 CASING A BLACK 5P	Black accessory casing for AXIS M3044-VI45-VI46-V. Replaces the white original casing. 5 pcs.	162	406	120
AXIS M42 SMOKED DOME A 4P	Smoked dome with anti-scratch hard coating. Compatible with AXIS M42 series. 4x domes per pack.	55	365	100
AXIS TP3804-E Metal Casing White 4P	A white metal casing for indoor/outdoor use that is compatible with: M3205-LVE, M3206-LVE, P3245-LVE, P3245-VE, P3247-LVE, AXIS P3248-LVE. It is IK 10/IP66, has a 3/4 conduit entry and is easy to install. This casing targeted for corrections and other segments that require a tough metal casing.	380	380	85
AXIS P56 SKIN COVER D	Spare part skin covers for the AXIS P56 Series. Both the camera cover and the ring around the dome are included. 5 pcs.	395	525	145
AXIS P39-R SKIN COVER WHITE 10P	Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. White color. 10 pcs.	153	385	155
AXIS P39-R SKIN COVER BLACK 10P	Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. Black color. 10 pcs.	153	385	155
AXIS M3044-VI45-VI46-V SM DOME 5P	Smoked dome for AXIS M3044-VI45-VI46-V SM DOME. 5 pcs.	80	370	40
AXIS M3104/5/6-LVE BLACK CASING 5P	Black accessory casing for AXIS M3104-LV/5-LV/6-LV. Replaces the white original casing. 5 pcs.	160	220	110
AXIS P54 SMOKED DOME	Smoked dome for AXIS P54-series.	195	195	110
AXIS TP5801-E Smoked Dome	Smoked dome for AXIS P56 Series cameras.	220	240	105
AXIS Q35 SMOKED DOME A 5PCS	Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3517-LV/-LVE. 5x domes per pack.	160	670	85
AXIS Q36-VE SMOKED DOME	Smoked dome with anti-scratch hard coating. Compatible with AXIS P38 and AXIS Q36 series.	180	180	130
AXIS TQ6810 HARD COATED SMOKED DOME	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q6074, 75, 78-E cameras. Weather-resistant and chemical-resistant. Replacement dome only.	120	185	185

AXIS TQ6811-E DOME CL HYDROPHILIC	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with Q6315-LE.	202	202	137
AXIS Q60-S SMOKED DOME A	Smoked dome in a special nylon blend with superior stress and chemical resistance. Compatible with AXIS Q604x-S and Q6055-S cameras. Single-pack.	190	250	105
AXIS TM3801 BLACK CASING 4P	4 Pack black casing to change the appearance of the product.	105	140	105
AXIS TM3803 BLACK CASING 4P	Cover top black casing for M3067/68 4P.	130	100	110
AXIS TM3804 SM DETECT CASING C 4P	SMOKE DETECTOR CASING - COVER TOP ASS SMOKE M3067/68	130	110	110
AXIS TM3805 VANDAL CASING C 4P	Vandal Casing COVER TOP ASS DOME M304X-PV.	140	110	110
AXIS TM3807 BLACK CASING 4P	4P Black casing for M3115/6 LVE. Black accessory casing that replaces the white original casing for changing the appearance of the camera.	175	225	110
AXIS TM3809-E SKIN COVER BLACK 4P	4 pack of outdoor-ready skin covers compatible with AXIS M4308-PLE for changing the appearance of the camera, simplify re-painting and covering screws. Black color. 4 pcs per pack.	178	158	158
AXIS TM3818 CASING BLACK 4p	4 Pack black casing to change the appearance of the product. Compatible with M3085-V, M3086-V, M3088-V.	110	150	110
AXIS TP3801 BLACK CASING 4P	Accessory black casing for selected AXIS P32 indoor cameras. 4pcs bulk pack.	160	212	158
AXIS TP3801-E BLACK CASING 4P	Accessory black casing for selected AXIS M32 and P32 outdoor cameras. Pre-assembled with anti-loss screws. 4pcs bulk pack.	160	212	158
AXIS TP3802 SMOKED DOME 4P	Smoked dome with anti-scratch hard coating. Compatible with selected AXIS P32 indoor cameras. 4pcs bulk pack.	194	294	70
AXIS TP3802-E SMOKED DOME 4P	Smoked dome with anti-scratch hard coating. Compatible with selected AXIS M32 and P32 outdoor cameras. 4pcs bulk pack.	194	294	70
AXIS TP3806 DOME COVER BLACK 4P	4 pack black dome cover for AXIS P3925-R. Replaces the standard white dome cover.	282	192	199
AXIS TP3808 DOME COVER BLACK 4P	4 pack black dome cover for AXIS P3935-LR. Replaces the standard white dome cover.	282	192	199
AXIS TP3813-E Ventless Metal Casing	A ventless metal casing for P3717/19-PLE and following products. USP 797/800 has very strict cleaning requirements for Hazardous, non-Hazardous and Ante rooms in an infusion or inpatient pharmacy setting. Ventless metal casing allows cleaning agent to wipe down the cameras easily.. It is easy to install in a fast way and is IK9/IP66 rated.	265	265	70
AXIS TP3814-E BLACK DOME CASING	Accessory black dome casing for AXIS P3727-PLE. The dome and casing are included.			
AXIS TP3815-E SMOKED DOME	Smoked dome for AXIS P3717-PLE, AXIS P3719-PLE, AXIS P3727-PLE. The smoked dome can replace the clear dome delivered with the camera.	115	320	340
AXIS TP3817-E CASING BLACK	Accessory casing compatible with AXIS P3818-PVE. Includes anti loss screws, weather cover, cover lid, and cover top.	215	215	170
AXIS TP3816-E CASING BLACK 4P	Black accessory casing for AXIS P3807-PVE. Replace the original white casing to change the appearance of the camera. Sold in packs of 4.	485	500	215

AXIS TP3820 CASING BLACK 4P	Accessory black casing for AXIS P3265-LV, V. 4pcs bulk pack.	160	212	158
AXIS TP3820-E CASING BLACK 4P	Accessory black casing for AXIS P3265-LVE 9 mm. Pre-assembled with anti-loss screws. 4pcs bulk pack.	160	212	158
AXIS TQ3801 HYDROPHILIC CLEAR DOME	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with AXIS P3807-PLE, AXIS Q3615-VE and AXIS Q3617-VE. Single pack	180	180	130
AXIS TP3821-E CASING BLACK 4P	Accessory black casing for AXIS P3265-LVE 22 mm, P3267-LV, P3267-LVE, P3268-LV, P3268-LVE. Pre-assembled with anti-loss screws. 4pcs bulk pack.	160	212	158
AXIS TQ3805-E CASING BLACK	Accessory casing compatible with Q3819-PVE. Includes anti loss screws, weather cover, cover lid, and cover top.	215	215	170
AXIS TQ3807-E DOME SMOKED	Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3536-LVE, AXIS Q3538-LVE. 5x domes per pack.	270	380	100
AXIS TQ6802 HYDROPHILIC CLEAR DOME	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with selected cameras from AXIS Q61 series that support IR illumination, e.g.: AXIS Q6125-LE. Single pack.	165	170	95
AXIS TQ6809 HARD COATED SMOKED DOME	Standard smoked dome with anti-scratch hard coating. Compatible with AXIS Q60-E cameras. Weather-resistant and chemical-resistant. Rubber gasket, ring compass, ring support included. Single pack.	235	230	135
AXIS TP3823-E WEATHERSHIELD BL 2P	Outdoor accessory weathershield for AXIS P3265-LVE, P3267-LVE, P3268-LVE. A black accessory weathershield that goes well with black casing and smoked dome. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Anti-loss screws included. Bulk 2 pack.	135	204	74
AXIS TM5801 DOME COVER BLACK	Accessory black dome cover for AXIS M5000 & AXIS M5000-G. Includes dome and cover, 4 SCREW TX+ 8 DOME FLANGE, and 2 spring clips.	255	265	157
AXIS TP3824-E DOME SMOKED 4P	Accessory smoked dome with anti-scratch hard coating. Compatible with AXIS P3265-LVE 22 mm, P3267-LV, P3267-LVE, P3268-LV, P3268-LVE. 4pcs bulk pack.	295	294	74
AXIS TM3815-E DOME SMOKED 4P	Smoked dome accessory with anti-scratch hard coating. Compatible with:AXIS M3215-LVE, AXIS M3216-LVE. 4pcs bulk pack.	295	295	70
AXIS TP3819-E DOME SMOKED	AXIS TP3819-E Dome Smoked, is a smoked dome and is offered as an optional accessory for AXIS P4705-PLVE and P4707-PLVE.	120	200	65
AXIS TP3825-E WEATHERSHIELD BLACK	AXIS TP3825-E Weathershield Black, is a black weathershield and is offered as an optional accessory for AXIS P4705-PLVE and P4707-PLVE.	170	240	80

AXIS TF1803-RE LENS PROTECTOR 4P	AXIS TF1803-RE Lens Protector 4P is a bulk pack of 4x Lens Protectors for AXIS F2135-RE. AXIS TF1803-RE is highly recommended to protect the sensor lens when AXIS F2135-RE is installed in harsh environments such as on the coast line, hot places with direct sun exposure on the sensor or if the sensor is subject to strong detergents. AXIS TF1803-RE is IK10 rated.	100	120	45
AXIS TF1802-RE LENS PROTECTOR 4P	AXIS TF1802-RE Lens Protector 4P is a bulk pack of 4 Lens protectors for AXIS F2105-RE standard sensor. AXIS TF1802-RE Lens Protector is highly recommended to protect the sensor lens when AXIS F2105-RE is installed in harsh environments such as on the coastline, hot places with direct sun exposure on the sensor or if the sensor is subject to strong detergents. AXIS TF1802-RE is IK10 rated.	100	120	45
AXIS TF1801-R LENS HOOD 4P	AXIS TF1801-R Lens Hood 4P is a bulk pack of 4x Lens Hood for AXIS F2105-RE standard sensor and AXIS F2135-RE fisheye sensor. The Lens Hood avoids reflections on the sensor unit lens when used as front facing camera onboard a vehicle. Lens Hood is made of silicone.	45	105	120
AXIS TP3827 Clear Dome Cover 10p	AXIS TP3827 Clear Dome Cover 10p is bulk pack of 10 original top cover with dome for AXIS M3905-R and AXIS P3905-R MkIII cameras.	120	310	115
AXIS TP3830 Top Cover Black 10p	AXIS TP3830 Top Cover Black 10p is a bulk pack of 10 top covers black without dome compatible with AXIS M3905-R and P3905-R MkIII cameras.	120	220	117
AXIS TQ3809-E Dome Smoked	Smoked dome accessory with anti-scratch hard coating. Compatible with AXIS Q3626/8-VE.	145	145	95
AXIS TQ3811-E Casing	Accessory casing with ring, and 4 anti-loss screws.	205	190	85
AXIS TM3814-E Skin Cover Black 4P	AXIS TM3814 Skin Cover Black 4-Pack, are outdoor-ready skin covers compatible with AXIS M4317/M4318-PLVE cameras for changing the appearance of the camera, simplify re-painting and covering screws. Black color.	155	180	160
AXIS TM3821 CASING BLACK 4P	Black accessory casings for AXIS M42 series. Replaces the original white casings. 4-piece bulk pack.	130	135	135
AXIS TM3819 CASING BLACK 4P	Cover top black casing for AXIS M4327-P and AXIS M4328-P. Comes in 4 Pack.	150	110	110
AXIS TM3820 VANDAL CASING 4P	Vandal case accessory with dome for AXIS M4327-P and M4328-P. Comes in 4 pack.	110	110	150
AXIS TQ6813 HARD COATED CLEAR DOME	Hard coated clear dome for AXIS Q6114-E/Q6115-E. Includes an O-ring.	195	185	120
AXIS TQ6814 HARD COATED SMOKED DOME	Hard coated scratch resistant smoked dome for AXIS Q6124-E, Q6128-E, Q6154-E, Q6155-E. Includes O-Ring.	195	185	120
AXIS TP3833-E Dome Casing Black	Accessory black dome casing for AXIS P3735-PLE, AXIS P3737-PLE, AXIS P3738-PLE. Casing with 4 screws anti loss TR20 included. Dome not included..	260	260	85
AXIS TP3832-E Dome Smoked	Accessory Smoked dome for AXIS P3735-PLE, AXIS P3737-PLE, AXIS P3738-PLE. The smoked dome can replace the clear dome delivered with the camera.	320	340	115
AXIS TM3822 Casing Black 4 pcs	4 pack black casing accessory compatible with AXIS M3086-V Mic. Changes the appearance of the product.	105	140	105

AXIS TM5805-E DOME SMOKED	Accessory smoke dome in polycarbonate. IK09 vandal resistant. Compatible with AXIS M5525-E, AXIS 5526-E. Single pack. 4 anti-loss TX20 screws in pack.	170	170	100
AXIS TP9801 Cover Steel 4 pcs	Accessory skin cover for AXIS P9117-PV. Steel finish and easy to repaint. Magnetically attached. Suitable for AXIS P9117-PV White model. Comes in a 4 pack.	205	370	170
AXIS TP3834-E CASING BLACK 4 pcs	Accessory black casing for AXIS P3267-LVE Mic. Pre-assembled with anti-loss screws. 4pcs bulk pack.	160	210	155
AXIS TP3835-E DOME SMOKED 4 pcs	Accessory smoked dome with anti-scratch hard coating. Compatible with AXIS P3267-LVE Mic. 4pcs bulk pack.	295	295	75
AXIS TM1903 Privacy Cover 10 pcs	A 10pack of privacy covers compatible with AXIS M1055-L, AXIS M1075-L. Fits easily over the camera area. Made of silicon and is coloured white. Easily adjust surveillance based on privacy needs. Ensure privacy is respected when needed. Quick and easy to deploy. Protects the lens from dust and fingerprints.			
AXIS TM3824-E Weathershield 2 pcs	A 2 pack accessory weathershield in white using anti reflective material. Gives weather protection to AXIS M3125-LVE, AXIS M3126-LVE, AXIS M3128-LVE. Easy to install.			
AXIS TP5803-E Hard-Coated Smoke	Accessory Hard coated smoked dome compatible with P5676-LE. Standard smoked dome with anti-scratch hard coating. Weather-resistant and chemical-resistant. Single pack that includes dome and IR cover.	185	185	125
AXIS TQ1001-E WALL MOUNT	Wall mount in electro-polished 316L stainless steel for AXIS XPQ1785, designed for harsh industrial environments. Max load 150 kg / 331 lb.	200	400	220
AXIS TQ1301-E POLE MOUNT 50-150mm	Pole mount in electro-polished 316L stainless steel for use together with AXIS TQ1001-E WALL MOUNT, designed for harsh industrial environments. Pole diameters 50-150 mm (2" - 6"). Max load 150 kg / 331 lb.	240	320	100
AXIS TQ1303-E CORNER MOUNT	Corner bracket for AXIS XPQ1785 Explosion-protected PTZ Camera, to be used with AXIS TQ1001-E Wall Mount. Electro-polished stainless steel (316L) for harsh industrial and maritime environments. Max load 150 kg / 331 lb.	30	50	20
AXIS TQ1604-E Conduit Back Box Gray	Backbox for AXIS P1468-XLE and AXIS Q1961-XTE Zone/Div 2 explosion-protected cameras, which enables safe cabling through 1/2" (M20) conduits. Compatible with AXIS T91B47 Pole Mount and AXIS T94P01B Corner Bracket.	160	180	40
EX WALL MOUNT XF40	Electro-polished 316L stainless steel wall mount for XF40, designed for onshore, offshore, marine and heavy industrial applications. Can also be used in conjunction with Bracket Pole Clamp Adaptor XF40 EX for pole mounting. It features a swivel movement of pan $\pm 90^\circ$ and tilt $\pm 45^\circ$ and its weight is 2.5 kg.	290	288	380
EX POLE MOUNT XF40	Pole mounting explosion protected fixed network cameras is made simple using this electro-polished 316L stainless steel Ex Pole mount XF40, accompanied by the requisite Ex Wall Mount XF40. The Ex Pole Mount XF40 is specifically designed to mount Ex Wall Mount XF40 to poles of a diameter from 90mm to 120mm. Weight 4.2 kg.	185	265	215

ASKDP03-T ARMORED CABLE EXCAM 10M	10m armored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 17.0mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C, Ex d IIC / Ex e II / Ex tD A21 IP66, IP67, IP68, M20x1.5. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland Ex d with compound Ex db eb IIC / Ex tb IIIC / Ex e II / Ex tD IP66/67/68, 1x cable gland Ex e II 2 G Ex e IIC Gb / II 1 D Ex ta IIIC Da IP66 M20x1.5.	370	350	115
ASKDP03-T ARMORED CABLE EXCAM 25M	25m armored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 17.0mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C, Ex d IIC / Ex e II / Ex tD A21 IP66, IP67, IP68, M20x1.5. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland Ex d with compound Ex db eb IIC / Ex tb IIIC / Ex e II / Ex tD IP66/67/68, 1x cable gland Ex e II 2 G Ex e IIC Gb / II 1 D Ex ta IIIC Da IP66 M20x1.5.	360	355	165
ASKDP03-T ARMORED CABLE EXCAM 95M	95m armored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 17.0mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C, Ex d IIC / Ex e II / Ex tD A21 IP66, IP67, IP68, M20x1.5. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland Ex d with compound Ex db eb IIC / Ex tb IIIC / Ex e II / Ex tD IP66/67/68, 1x cable gland Ex e II 2 G Ex e IIC Gb / II 1 D Ex ta IIIC Da IP66 M20x1.5.	565	565	275
SKDP03-T CABLE EXCAM 10M	10m unarmored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 12.3mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland with compound Ex d IIC / Ex e II / Ex tD A21 IP66/67/68. M20x1.5.	355	365	115
SKDP03-T CABLE EXCAM 25M	25m unarmored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 12.3mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland with compound Ex d IIC / Ex e II / Ex tD A21 IP66/67/68. M20x1.5.	355	365	115

SKDP03-T CABLE EXCAM 95M	95m unarmored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 12.3mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland with compound Ex d IIC / Ex e II / Ex tD A21 IP66/67/68, M20x1.5.	440	440	250
EXCONNECTION RAIL 4 POE PS24	Explosion-protected PoE switch and power supply for use with up to 4 ExCam cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.4-D-4PoE+-100BaseFX. Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, output power 4x 24VDC@30W, network uplink 1x 100BaseFX, 1x 100BaseTX, network output 4x PoE+ (10/100BaseT(X), IEEE802.3at, max 30W/port). 2x cable glands M25x1.5 included. Multi mode fiber version.	440	570	290
EX CONNECTION RAIL 4-PORT POE SM	Explosion-protected PoE switch and power supply for use with up to 4 ExCam cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.4-D-4PoE+-100BaseFX. Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, output power 4x 24VDC@30W, network uplink 1x 100BaseFX, 1x 100BaseTX, network output 4x PoE+ (10/100BaseT(X), IEEE802.3at, max 30W/port). 2x cable glands M25x1.5 included. Single mode fiber version.	440	570	290
EXCONNECTION RAIL 8 POE PS24	Explosion-protected PoE switch and power supply for use with up to 8 ExCam cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.5-D-8PoE+-1000Base-SX (multimode 850nm, LC). Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, output power 8x 24VDC@30W, network uplink 2x 1000BaseFX, 1x 1000Base-SX, network output 8x PoE+ (10/100BaseT(X), IEEE802.3at, max 30W/port). 2x cable glands M25x1.5 included.	440	570	290
EXCONNECTION RAIL 4-PORT POE++	Explosion-protected PoE++ switch and for use with up to 4 cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.5-D.BOR-4PoE+-1000BaseXX. Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, network uplink 2x 10BASE-T/100BaseTX/1000BASE-T, 2x SFP, network output 4x PoE++ IEEE802.3at/bt, max 60W/port).	550	450	290

EXCONNECTION RAIL 8-PORT POE++	Explosion-protected PoE++ switch and for use with up to 8 cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.6-D.BOR-8PoE++-1000BaseXX. Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, network uplink 2x 10BASE-T/100BaseTX/1000BASE-T, 2x SFP, network output 8x PoE++ IEEE802.3at/bt, max 60W/port).	800	600	570
EXTB-3 JUNCTION BOX EXCAM	Terminal box for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Ex II 2 G Ex eb IIC T5 Gb, Ex II 2 D Ex tb IIIC T95°C Db, glass fiber reinforced polyester resin, 10x terminal PT 2.5, 3x terminal PT 2.5 PE. 1x M20 gland for armored cables, 2x M20 gland for unarmored cables.	265	300	135
WALL MOUNT EXCAM XPT	Wall mount for EXCAM XPT Q6055 in stainless steel with protective hood for cable glands.	440	570	295
POLE MOUNT EXCAM XPT	Pole mount for EXCAM XPT Q6055 in stainless steel for pole diameters 110-150mm, requires Wall Mount ExCam XPT.	450	570	180
CEILING MOUNT EXCAM XPT	Ceiling mount bracket for ExCam XPT Q6075. Stainless steel 1.4404, load rating 50kg. Dimensions 290x220x190 mm.	440	440	330
WALL MOUNT EXCAM XF	Stainless steel (1.4404 / 316L) wall bracket for fixed explosion-protected cameras in the ExCam range, includes hinge and mounting material.	270	570	190
POLE MOUNT EXCAM XF	Stainless steel (1.4404 / 316L) pole mount, to be used with Wall Mount Excam XF. Mounting material included.	265	565	190
WEATHERSHIELD EXCAM XF	Weather protection shield for ExCam XF P1367 in stainless steel. 0.9kg, installation material included. Built to order.	270	570	190
WEATHERSHIELD EXCAM XF M30	Weather protection shield for ExCam XF M3016 in stainless steel. 0.15kg, installation material included. Built to order.	265	570	190
WALL MOUNT EXCAM XF M30	Wall bracket for ExCam XF M3016 in stainless steel, 0.5kg, pan angle 360°, tilt angle 90°. Including hinge and mounting material. Built to order.	265	570	190
EX E CABLE GLAND M20 NON-ARMORED	Ex e cable gland in black polyamide, for non-armored cables, diameter 7-13mm, suitable for SKDP03-T CABLE EXCAM. ATEX/IECEx certified II 2 G Ex eb IIC Gb, II 2 D Ex tb IIIC Db. Operating temp -60°C to +75°C. Built to order.	95	110	110
EX E CABLE GLAND M20 ARMORED	Ex e cable gland in nickel-plated brass, for armored cables, diameter 12.5-20.9mm, suitable for ASKDP03-T CABLE EXCAM. ATEX/IECEx certified II 2 G Ex eb IIC Gb, II 2 D Ex tb IIIC Db. Operating temp -60°C to +130°C. Built to order.	95	110	110
EX D CABLE GLAND M20 NON-ARMORED	Ex d cable gland in nickel-plated brass, for non-armored cables diameter 6.5-14mm, suitable for SKDP03-T CABLE EXCAM. ATEX/IECEx certified II 2 G Ex db IIC Gb, II 1 D Ex ta IIIC Da. Operating temperature -60°C to +85°C. Built to order.	95	110	110
EX D CABLE GLAND M20 ARMORED	Ex d cable gland in nickel-plated brass, for armored cables diameter 13.5-21mm, suitable for ASKDP03-T CABLE EXCAM. ATEX/IECEx certified II 2 G Ex db IIC, II 2 D Ex tb IIIC. Operating temperature -60°C to +140°C. Built to order.	95	110	110

EXCAM XF WIPER BLADE 10 PACK	Replacement wiper blade for ExCam XF Q1785. Natural black rubber, 54mm, 10-pack.	100	105	110
FRONT GLASS PROTECTIVE FILM F101-A	Plastic protective film for the front glass of the F101-A explosion-protected cameras. For use in highly corrosive atmospheres like hydrogen fluoride (HF) gas. Set of 5.	110	120	35
AXIS TQ1812-E WEATHERSHIELD	Stainless steel (316L) weather shield for AXIS XPQ1785.	200	310	150
AXIS TQ1814-E WEATHERSHIELD	Stainless steel (316L) weather shield for AXIS XFQ1656.	380	220	155
AXIS TQ1915 PLUG THREAD M25x1.5	Ex d certified (ATEX, UL, IECEx, INMETRO, PESO, KCs, INMETRO) M25x1.5 blanking plug for Ex d enclosures. Nickel-plated brass.	155	110	40
AXIS TQ1916 PLUG THREAD M20x1.5	Ex d certified (ATEX, UL, IECEx, INMETRO, PESO, KCs, INMETRO) M20x1.5 blanking plug for Ex d enclosures. Nickel-plated brass.	155	110	40
AXIS TQ1917 ADAPTER M25x1.5-3/4 NPT	Explosion-protection certified "Ex d" M25x1.5 to 3/4" NPT nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	155	110	40
AXIS TQ1918 ADAPTER M20x1.5-3/4 NPT	Explosion-protection certified "Ex d" M20x1.5 to 3/4" NPT nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	155	105	40
AXIS TQ1920 ADAPTER M25x1.5-1/2 NPT	Explosion-protection certified "Ex d" M25x1.5 to 3/4" NPT nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	155	105	40
AXIS TQ1921 ADAPTER M20x1.5-1/2 NPT	Explosion-protection certified "Ex d" M20x1.5 to 1/2" NPT nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	155	105	40
AXIS TQ1925 ADAPTER M25x1.5-M20x1.5	Explosion-protection certified "Ex d" M25x1.5 to M20x1.5 nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	155	105	40
AXIS TQ1922-E SWIVEL JOINT	Swivel joint in stainless steel (316L) for flexible mounting of AXIS XFQ1656 on AXIS TQ1001-E Wall Mount.	240	160	80
AXIS TQ1923-E WIPER BLADE 5P	Silicon wiper blade spare part for AXIS XFQ1656, sold in quantity of 5.	155	110	40
AXIS TQ1924-E WASHER NOZZLE	Replacement washer nozzle in stainless steel (316L) for AXIS XFQ1656.	155	110	40
AXIS TQ1943-E Cbl Gld Ex d Armd M20	Explosion-protected cable gland for armored cables. II 2G 1D Ex db IIC, Ex ta IIIC Da, ATEX, IECEx, PESO, INMETRO, IA. M20 thread.	105	150	38
AXIS TQ1943-E Cbl Gld Ex d Armd M25	Explosion-protected cable gland for armored cables. II 2G 1D Ex db IIC, Ex ta IIIC Da, ATEX, IECEx, PESO, INMETRO, IA. M25 thread.	80	132	47
AXIS TQ1944-E Gld Ex d Non-armd M20	Explosion-protected cable gland for nonarmored cables. II 2G 1D Ex db IIC, Ex ta IIIC Da, ATEX, IECEx, PESO, INMETRO, IA, KCs. M20 thread.	105	150	38
AXIS TQ1944-E Gld Ex d Non-armd M25	Explosion-protected cable gland for nonarmored cables. II 2G 1D Ex db IIC, Ex ta IIIC Da, ATEX, IECEx, PESO, INMETRO, IA, KCs. M25 thread.	105	150	38
AXIS TQ1952-E Cbl Gld Non-armd M20	Explosion-protected 'Ex e' nickel-plated brass cable gland for Zone/Division 2 certified explosion-protected cameras. ATEX/IECEx certified II 2 G Ex eb IIC Gb, II 2 D Ex tb IIIC Db. M20 thread, IP 66/67/68.	110	152	37

AXIS TU6012 CONN 2-PIN 7.62 ST	Replacement 2-pin power connector with 7.62mm pitch, for AXIS XFQ1656.	60	80	20
AXIS TU6013 CONN 2-PIN 5.08 ST	Replacement 2-pin AUX connector with 5.08mm pitch, for AXIS XFQ1656.	60	80	20
AXIS TU6014 CONN 6-Pin 3.81 ST	Replacement 6-pin I/O connector with 3.81mm pitch, for AXIS XFQ1656.	60	80	20
AXIS 1.5" NPS/NPT MALE COUPLER	1.5" NPT Male-to-Male coupler used to connect any AXIS Pendant Kit (e.g.: AXIS T94A01D) to a legacy mount with Female NPT or NPS thread (e.g.: 3rd party wall mount). Useful in retrofitting legacy cameras in existing installations. Lock nut included. Material: Aluminum with black anodizing. Note: The National Pipe Taper (NPT) is a U.S. standard for tapered threads used on threaded pipes and fittings. The National Pipe Straight (NPS) threads are straight (parallel). Both NPT and NPS have the same thread angle, shape, and pitch (threads per inch).	84	120	60
AXIS T8640 WALL MOUNT BRACKET	Wall mount bracket for AXIS T8640 Ethernet over Coax adapter base or device unit.	95	60	35
AXIS T8640 DIN RAIL CLIP	DIN rail clip for AXIS 8640 Ethernet over Coax adapter.	125	60	45
AXIS T8640 RACK MOUNT BRACKET	Rack mount bracket for AXIS T8640 Ethernet over Coax adapter (8 units in 1U).	500	77	50
AXIS T91A02 DIN RAIL CLIP 77MM	DIN rail clip for AXIS Q7401, AXIS P8221 and AXIS 7701.	37	110	70
AXIS T91A02 DIN RAIL CLIP 86MM	DIN rail clip for AXIS M7014 and AXIS P7214	37	110	70
TF9904 Swivel Mount 5P	AXIS TF9904 Swivel Mount allows to mount the sensor unit in different horizontal and vertical angles. It is sold a pack of 5.	155	120	60
AXIS T91A03 DIN RAIL MOUNT	DIN rail clip for AXIS Q7424-R.	120	150	40
AXIS T91A04 CAMERA HOLDER 3/4" NPS	Holding device for pendant mounted cameras. For use with 3/4" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	120	130	95
AXIS T91A05 CAMERA HOLDER 1.5" NPS	Holding device for pendant mounted cameras. For use with 1.5" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	120	130	95
AXIS T91A06 PIPE ADAPTER 3/4-1.5"	Pipe adapter step up from 3/4" NPT thread to 1.5" NPS thread. Compatible with all pendant kits that are made for the AXIS T91A range of brackets.	150	200	2
AXIS T91A10 MOUNTING KIT	Plastic mounting kit with stand and clamp for flexible mounting of Axis products with tripod thread.	105	155	35
AXIS T91A11 STAND WHITE	Plastic camera stand. Original stand for the AXIS M11-series.	80	80	140
AXIS T91A13 THREADED CEIL MOUNT 10P	10-pack threaded ceiling mount for quick installation under ceiling tiles. Compatible with cameras with standard 1/4"-20 UNC tripod thread. Total length 80mm (3") with thread length 65mm (2.5"). Threaded rod in nylon, counter nut with friction pad. 10-piece bulk pack.	165	180	45
AXIS T91A23 TILE GRID CEIL MNT 4P	4-pack of ceiling mount accessory for mounting Axis cameras and stands on a variety of drop-ceiling tile grid system. Compatible with Axis Safety Wire. Color: Axis white. Bulk pack. Suitable tile grid (T-bar) dimensions: 15mm(0.6in)/24mm(0.9in)/35mm(1.4in). Suitable ceiling tiles type: square-edge, tegular edge.	125	175	100

AXIS T91A33 LIGHT TRACK MNT 4P	4-pack of lighting track mounts. Color: white. Compatible with universal 3-circuit lighting track systems and selected linear trunking systems. Compatible with a wide range of Axis cameras and camera stands.	123	175	95
AXIS T91A33 LIGHT TRACK MNT BLK 4P	4-pack of lighting track mounts. Color: black. Compatible with universal 3-circuit lighting track systems and selected linear trunking systems. Compatible with a wide range of Axis cameras and camera stands.	123	175	95
AXIS T85 RACK MOUNT KIT A	Rack mount kit for AXIS T8508 PoE+ Network Switch	80	190	57
AXIS T91B21 STAND BLACK	Black aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	200	150	80
AXIS T91B21 STAND WHITE	White aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	210	175	90
AXIS T91A27 POLE MOUNT 10PCS	Pole mount bracket compatible with all cameras with standard tripod threading (1/4"-20 UNC)	285	110	55
AXIS T91B47 100-410MM	AXIS T91B47 Pole Mount for indoor and outdoor installations, for poles with diameter between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B47 is directly compatible with a wide range of Axis cameras.	220	260	75
AXIS T91B47 50-150MM	AXIS T91B47 Pole Mount for indoor and outdoor installations, for poles with diameter between 50-150mm (2"-6"). Includes 1 pair of AXIS Stainless Steel Straps 570mm (22.5") with TX30 screw interface for ease-of-installation. AXIS T91B47 is directly compatible with a wide range of Axis cameras.	220	260	75
AXIS T91B57 POLE MOUNT 100-410MM	Aluminum Pole Mount for indoor and outdoor installations, for poles with diameter between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B57 is compatible with mounts such as AXIS T91G61, T91H61, and AXIS T98A Surveillance Cabinet series. Color: Axis white.	243	285	102
AXIS T91B57 POLE MOUNT GREY	Aluminum Pole Mount in Urban Grey color. For indoor and outdoor installations. Suitable for poles diameters between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B57 is compatible with mounts such as AXIS T91G61, T91H61, and AXIS T98A Surveillance Cabinet series.	245	285	105
AXIS T91B67 POLE MOUNT 65-165MM	Outdoor-ready, powder-coated aluminum pole mount with 1.5" NPS thread for fixed dome pendant kits. Includes insect-proof cable gasket and 1 pair of stainless steel straps (with TX30 screw) for pole diameter between 65-165mm (2.5"-6.5"). White in color.	322	246	202
AXIS T91M47 POLE MOUNT	Pole mount for our outdoor midspans and switch.	200	285	45

AXIS TD9301 OUTDOOR MIDSPAN POLE MOUNT	AXIS TD9301 Outdoor Midspan Pole Mount for outdoor midspans, like AXIS 30W Outdoor Midspan.	150	255	40
AXIS T91D61 WALL MOUNT	Chromated and powder coated aluminum wall mount with 1.5" NPS thread for fixed dome pendant kits. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal and conduit hole cover. Color: White	250	325	150
AXIS T91E61 WALL MOUNT	Wall mount with internal cable canal for dome cameras with 1.5" NPS thread, compatible with Axis pendant kits. IK10 and NEMA 4X rated. Powder coated aluminum for indoor and outdoor installations.	135	190	92
AXIS T91G61 WALL MOUNT	Aluminum wall mount with IP66 compartment to safely accommodate power and connectivity accessories (e.g. PoE midspan). IK10 and NEMA 4X rated in Axis white color. Includes a pre-terminated IP66 rated RJ45 connector. Compatible with wide range of Axis cameras, incl. AXIS M55, P56, Q37, Q60, Q61 Series.	275	435	275
AXIS T91G61 WALL MOUNT GREY	Aluminum wall mount with IP66 compartment to safely accommodate power and connectivity accessories (e.g. PoE midspan). IK10 and NEMA 4X rated in Urban Grey color to match AXIS Q62 series. Includes a pre-terminated IP66 rated RJ45 connector. Compatible with wide range of Axis cameras.	285	445	230
AXIS TS2901 APPLIANCE STAND	AXIS TS2901 Appliance Stand is a stand compatible with AXIS S2208 and AXIS S2212 Appliances which allows the unit to be mounted vertically, on a table or shelf. The appliance is secured to the stand with the 4 included screws. Mounted vertically, the appliance will take even less space than it usually does, leaving more space for other activities. The stand itself can be screwed to the table/shelf, which is a simple way to secure the appliance against light thefts and from falling. It can also lie on the table, when using the included rubber feet.	160	395	40
AXIS T91H61 WALL MOUNT	AXIS T91H61 Wall Mount is designed with a built-in RJ45 cable and connection to, and spacious compartment for connectivity accessories such as midspans and media converters. The wall mount is impact-resistant (IK10) and weather-resistant (IP66, NEMA 4X) for indoor and outdoor use. The 1.5" NPS thread mount ensures compatibility with all pendant kits for Axis fixed dome cameras.	235	435	285
AXIS T91F61 WALL MOUNT STAINLESS STEEL	Wall mount for AXIS Q3505-SVE, made of stainless steel.	230	215	95
AXIS T91K61 WALL MOUNT	Marine-grade stainless steel wall mount for AXIS Q6055-S PTZ Network Camera. Compatible with stainless steel pole mount (sold separately).	120	170	66
AXIS T94J01A WALL MOUNT	Aluminum wall mount for Axis positioning cameras and positioning units. Robust and impact-resistant. Compatible with Axis ACI 3/4" conduit adapters, and offers multiple cable entries. Cables can be routed through the back or, by using a conduit connection, from each side or from the bottom. Suitable for indoor and outdoor use.	630	270	290

AXIS T94J01A WALL MOUNT GREY	Robust and impact-resistant aluminum wall mount for selected Axis PTZ and positioning cameras. Multiple cable entry points for 3/4" (M25) conduit pipes. Suitable for indoor and outdoor use. Color: Urban Grey.	260	430	280
AXIS T91D62 TELESCOPIC PARAPET MNT	Made for parapet and wall installations. Telescopic arm with adjustable length between 783 mm (30.1 in) to 1033 mm (40.7 in) for compensating different parapet thicknesses or obstructive elements on the facade of the building. It can Swivel round its own axis 180 degrees, allowing mounting/maintain the camera easily and safely from the rooftop. The mount is intended for outdoor fixed and PTZ dome cameras supporting 1.5" NPS thread. A retrofit mounting bracket (optional accessory) makes it possible to reuse holes drilled for Pelco's PTZ dome parapet mount.	725	1015	120
AXIS T91D62 ADAPTER MOUNTING BRACKET	Retrofit adapter mount bracket for re-using holes drilled from Pelco's PTZ dome parapet mount, or for increasing the attachment area towards the parapet.	290	400	45
AXIS T91B50 TELESCOPIC CEIL MNT	Indoor/outdoor telescopic ceiling mount. Expands between 1 m (39") and 2 m (79"). Features a swivel action to prevent breaking if hit by forklifts or high vehicles. Can be mounted on a sloped ceiling. Accessory extension pipes (Not included) for a maximum length of 5 m (197"). Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	170	1160	170
AXIS T91B51 CEILING MOUNT	The indoor/outdoor ceiling mount is ideal for low ceiling installations such as parking houses, with swivel action to prevent breaking if hit. Can be mounted in a sloped ceilings/soffits to compensate angles up to 45 degrees. Available accessory extension pipes (Not included) of 30 cm (12") or 1 meter (39") to enable correct camera height for the specific environment. Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	185	185	195
AXIS T91B52 EXTENSION PIPE 30 CM	Extension pipe for AXIS T91B50 and AXIS T91B51. Length 30 cm (12").	65	340	65
AXIS T91B52 EXTENSION PIPE 100 CM	Extension pipe for AXIS T91B50 and AXIS T91B51. Length 100 cm (39").	65	1035	65
AXIS T91B53 TELESCOPIC CEIL MNT 2P	Twin-pack (bulk). Includes 2x indoor telescopic ceiling mounts, extendable between 1m to 1.8m (3.2 to 6ft) at 10cm (4") intervals. Compatible with Axis pendant kits and camera holder with 3/4" conduit interface. Suitable for vertical and horizontal mounting.	185	1065	110
AXIS T91B63 CEILING MOUNT	Chromated and powder coated aluminum ceiling mount 75 cm / 29.5 inch compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	300	805	85

AXIS T91A64 BRACKET CORNER	Corner Bracket that is compatible with several wall mounts: AXIS T91B61 Wall Mount, AXIS T91D61 Wall Mount 1.5" NPS, AXIS T91G61 Wall Mount, AXIS T91H61 Wall Mount, AXIS T91L61 Wall-and-Pole Mount. These wall mounts in turn are compatible with AXIS P55-series, AXIS Q60/61/63-series, AXIS M32-series, AXIS Q37-series, AXIS M55-series, AXIS P56-series and their associated pendant kits.	200	355	205
AXIS T91F67 POLE MOUNT STAINLESS STEEL	Pole mount bracket for AXIS Q35-SLVE stainless steel cameras. Compatible with AXIS T91F61 Wall mount. Made of marine-grade stainless steel. Includes 1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Straps length 1450mm (57"), suitable for pole diameter range 100-410mm (4"-16").	220	260	80
AXIS T91A6 PIPE SEAL 1PCS	Pipe seal for AXIS T91A6, to protect from dust, water and bugs.	275	230	90
AXIS T93C WALL-POLE CONDUIT BACKBOX	Aluminum conduit back box for wall or pole mount. Space for outdoor power supply, and electrical connection boxes. Steel straps for pole mount are sold separately. Recommended to use with POWER SUPPLY PS24 240W (not included).	215	365	170
AXIS T94A01C ATTACHMENT KIT	For attaching AXIS Q61 PTZ network camera to AXIS Q6000-E MkII PTZ network camera.	265	265	160
AXIS T94A01D PENDANT KIT	Pendant kit for the AXIS Q60-series and AXIS P55-series PTZ Network Cameras, enables mount on standard '1,5" NPT threaded brackets. White.	165	240	80
AXIS T94A01F CEILING BRACKET	Bracket for mounting an AXIS P56 Series camera in a hard ceiling. For indoor and outdoor installations. 3/4" conduit hole, compatible with ACI adapters.	120	130	95
AXIS T94A02F CEILING BRACKET	Aluminum ceiling bracket for Axis PTZ cameras and AXIS Q37 Series for indoor or outdoor use. 3/4" conduit hole on the side.	120	130	95
AXIS T94A01L RECESSED MOUNT	Outdoor recessed mount for AXIS Q60-E cameras. Can be mounted in panels, wood or pre-made holes solid concrete. The mount is very sturdy and made of aluminum and stainless steel. It supports the IK10 impact rating of the camera and has two 3/4" conduit holes for a plenum rated and rodent safe installation.	320	320	260
AXIS T94A02L RECESSED MOUNT	Outdoor recessed mount for AXIS P56 cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a 3/4" hole for cable protection conduits.	320	320	215
AXIS T94B02D PENDANT KIT 10PCS	Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/-LVE, M30-V/-WV and Companion dome cameras. 10-pack.	210	195	110
AXIS T94B02D PENDANT KIT	Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/-LVE, M30-V/-WV and Companion dome cameras. Single pack.	50	125	10

AXIS T94B02D PENDANT KIT BLACK	Pendant kit for wall mount or ceiling mount in black. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/LVE, M30-VI-WV and Companion dome cameras. Single pack.	123	113	58
AXIS T94B05L RECESSED MOUNT	Indoor recessed mount for drop ceiling installation. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M3044-V/M3045-V/M3046-V/M3047-V/M3048-V.	155	155	140
AXIS T94B03L RECESSED MOUNT	Indoor recessed mount for drop ceiling installations. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M2025/26 and AXIS Companion Bullet.	155	160	160
AXIS T94B02M J-BOX/GANG BOX PLATE	Bracket for mounting a camera on a 4" square, 4" octagon, single or double-gang junction box. Compatible with AXIS M3044-V/M3045-V/M3046-V.	175	185	25
AXIS T94B01P CONDUIT BACK BOX	Conduit back box for 1/2" or M20 pipes. Features the 1/2" ACI interface to enable use of ACI adapters. There is an integrated female tripod thread for use of standard camera stands or holders. Compatible with AXIS M3044-V/M3045-V/M3046-V.	110	125	50
AXIS T94C01L RECESSED MOUNT	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS M42 series and AXIS Companion Dome mini LE.	75	285	160
AXIS T94C01M J-BOX/GANG BOX PLATE	Bracket for mounting camera on 4" square, 4" octagon, single or double-gang junction box. Compatible with AXIS M42 Series and AXIS Companion Dome mini LE.	195	30	175
AXIS T94C01U UNIVERSAL MOUNT	Versatile 4-in-1 mount accessory for use as either a pendant kit with 3/4" (M25) conduit interface, conduit back box with 1/2" (M20) conduit side entry, pole mount, or standard camera thread. Compatible with AXIS M42 series and AXIS Companion Dome mini LE. Pole mounting straps available separately.	45	150	130
AXIS T94D01S MT BRACKET FL WT 10PCS	White plastic adapter for mounting AXIS P3904-R and AXIS P3905-R on flat surfaces. Does not fit with AXIS P3915-R. Used when the cable must enter from the side. 10 pack.	120	220	115
AXIS T94D02S MT BRACKET CU WT 10PCS	White plastic adapter for mounting AXIS P3904-R, AXIS P3905-R and AXIS P3915-R on curved surfaces. 10 pack.	115	120	115
AXIS T94F01D PENDANT KIT	Indoor pendant kit for AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE. to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes. The camera network cable fits into the product and a RJ45 network cable coupler is included.	160	160	200
AXIS TM1902 Stand Mount 4 pcs	Mounting stand in plastic for wall and ceiling. Stand height 70 mm (2.7 in). Circular base with diameter 69 mm (2.7 in). White color.	160	240	80
AXIS T94F01M J-BOX/GANG BOX PLATE	Bracket for mounting on 4" square, 4" octagon, single or double-gang junction box. RJ45 network cable coupler included. Compatible with. Compatible with AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE, P14 Series.	175	175	25

AXIS T94F01P CONDUIT BACK BOX	Backbox for AXIS M3006-V, AXIS M3007-PI-PV, AXIS M3024-LVE/3025-VE/3026-VE/3027-PVE, P14 Series, which enables safe cabling through 1/2" (M20) conduits.	165	180	40
AXIS T94G01P CONDUIT BACK BOX	Back box for 3/4" (M25) conduits/cable protection pipes. Compatible with AXIS Q1765-LE and AXIS Q1931-E.	165	240	60
AXIS T94K01D PENDANT KIT	Indoor pendant kit for AXIS P32-V Series- AXIS P33/-V and AXIS Q3505-V, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	205	190	180
AXIS T94M01D PENDANT KIT	Outdoor pendant kit for AXIS P32 & Q35 series. Compatible with several Axis ceiling, wall, and pole mounts, As well 1.5" NPS threaded pipes.	220	240	105
AXIS T94M02L RECESSED MOUNT	Outdoor recessed mount for mid-size outdoor dome cameras such as: AXIS P32-VE/-LVE, P33-VE/-LVE and Q35-VE/-LVE series. Suitable for outdoor installations in roof overhangs and soffits. Also suitable for indoor installations in plenum spaces.	265	265	195
AXIS T94N01D PENDANT KIT	AXIS T94N01D Pendant Kit comprises a weathershield and a mounting adapter for AXIS P3717-PL Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3717-PL to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	275	280	55
AXIS T94N02D Pendant Kit	AXIS T94N02D Pendant Kit comprises a weathershield and a mounting adapter for AXIS P3715-PLVE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3715-PLVE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	170	260	70
AXIS T94N01G POLE MOUNT	Stainless steel pole mount designed for use with heavier Axis products such as positioning cameras and positioning units. IK10. Includes 3pcs stainless steel straps included for pole diameter 60-400mm (2.4-15.7in) and sealing gaskets for multiple cable entries with protection against insect infestation.	275	315	80
AXIS T94N01L RECESSED MOUNT	Indoor and outdoor recessed mount for discreet installations in drop ceilings, roof overhangs/soffits of AXIS P37 network camera series. Also suitable for installations in plenum space, as the back box is made of metal with a 3/4" hole for cable protection conduits.	330	315	110
AXIS T94P01B CORNER BRACKET	Corner mount for AXIS P5414-E/15-E, AXIS Q1765-LE, AXIS Q1931-E and AXIS P33-VE series.	255	290	135
AXIS T94P01L RECESSED MOUNT	Indoor and outdoor recessed mount for AXIS M55 Series. Suitable for air-handling spaces in indoor installations as the enclosure is made of metal and has a 3/4" (M25) conduit hole for protected cable-routing. UL-approved.	280	300	125
AXIS T94Q01A WALL MOUNT	Wall mount compatible with all Axis outdoor fixed box cameras and housings. Corrosion tested according to NEMA 4X, UL listed and IK10 rated.	165	240	80

AXIS T94Q01F CEILING AND COLUMN MNT	The powder-coated aluminum AXIS T94Q01F for AXIS fixed box outdoor ready cameras and housings, can be used for both ceiling/soffit and column/parapet installations. This allows Axis' fixed camera housings to be mounted under hard surfaces such as ceilings, beams, soffits and canopies. It can also be mounted on pole or column tops, parapets and other horizontal building structures. Re-direction and maintenance of the camera is easy thanks to the swivel arm feature. The cable is routed through the pipe, and is never exposed to weather or potential vandalism. Cable conduits and Axis' conduit adapters (3/4" dimension) are used for cable protection when routed from the side.	305	345	120
AXIS T94R01B CORNER BRACKET	The powder-coated aluminum AXIS T94R01B Corner Bracket is used for attaching the wall mount of Axis' camera housing to the outer corners of a building. AXIS T94R01B Corner Bracket is compatible with AXIS T91E61 Wall Mount for fixed dome cameras. Small-size fixed dome and bullet-style cameras can also be mounted, thanks to the included and commonly used hole pattern of a single gang junction box.	158	223	110
AXIS TQ1601-E CONDUIT BACK BOX	Back box to enable external cable entry or use of cable protection equipment. Holes on top and side for 3/4 inch conduits or M25 cable protection pipes. Compatible with AXIS T94Q01A Wall mount, all AXIS M11-E/P13-E/Q16-E/Q1755-E/Q1910-E/21-E/22-E outdoor fixed box camera wall mounts and AXIS T92E Series and AXIS T93E05 Fixed camera housings.	180	150	68
AXIS T94S01L RECESSED MOUNT	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS P32-V/-LV series.	180	285	85
AXIS T94S01L RECESSED MOUNT 10P	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS P32-V/-LV series. 10-pack.	405	480	195
AXIS T94S02L RECESSED MOUNT	Indoor recessed mount for ceiling/wall installations. Compatible with AXIS M3057/58-PLVE cameras. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	80	290	180
AXIS T94S01P CONDUIT BACK BOX	Outdoor-ready, impact resistant (IK10+) back box with sealed compartment (IP66/67) for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind a wide range of Axis network cameras. Includes a network cable and extra gaskets.	205	220	60
AXIS TQ1602-E CONDUIT BACK BOX	Outdoor-ready, impact resistant (IK10+) back box with sealed compartment (IP66/67) for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind a wide range of Axis network cameras. Includes a network cable and extra gaskets. Specifically designed for aesthetically pleasing installations with AXIS Q17/Q19 and P14 Camera Series	205	215	60

AXIS T94T02D PENDANT KIT	Outdoor pendant kit for AXIS M30-PLVE Series. Weathershield made from impact-, UV-, and heat-resistant polymer. Compatible with wide range of Axis mounts with 1.5" NPS threaded interface.	190	190	80
AXIS T94U01D PENDANT KIT	Pendant kit for AXIS Q3505-SVE, without weather shield, mainly for indoor use made of stainless steel.	245	260	60
AXIS T94U02D PENDANT KIT	Outdoor pendant kit with weather shield for AXIS Q3505-SVE, made of stainless steel.	270	245	115
AXIS T94V01C DUAL CAMERA MOUNT	AXIS T94V01C Dual Camera Mount allows back-to-back installation of two Axis cameras for panoramic coverage. Compatible with a wide range of Axis dome cameras, box cameras, and bullet cameras. Compatible with Axis mounting accessories with 1.5" NPS threaded interface, for mounting on walls, poles, and under ceilings. AXIS T94V01C is IK10 rated for impact resistance, which safeguards it against vandalism. Suitable for both indoor and outdoor use. Note: To ensure physical stability, do not use AXIS T94V01C for single camera installations.	215	305	105
AXIS T94V01D PENDANT KIT	Pendant kit for indoor and outdoor use for the AXIS Q36-VE Series compatible with Axis ceiling-/wall-/pole mounts with 1.5" NPS thread.	260	265	210
AXIS T94X01A WALL MOUNT 6PCS	Wall mount for AXIS T92F10 Outdoor Housing. 6-piece pack. Optional accessory: AXIS T94Y01G Pole Mount 6PCS (sold separately)	300	365	305
AXIS T94Y01G POLE MOUNT 6PCS	Pole mount for AXIS T92F10 Outdoor Housing, with 1 pair stainless steel straps included per piece. 6-piece pack. Required accessory: AXIS T94X01A Wall Mount 6PCS (sold separately)	310	265	270
AXIS T95A64 BRACKET CORNER	Corner bracket for AXIS T98A-VE Surveillance Cabinet and AXIS Positioning Cameras. When used with AXIS Positioning Cameras, AXIS T94J01A Wall Mount is required.	205	325	185
AXIS T95A67 BRACKET POLE	Pole bracket for AXIS T98A-VE Surveillance Cabinet. No straps required.	140	255	206
WALL MOUNT AXIS PS24	Metal box to mount AXIS PS24 to a wall.	205	285	245
AXIS PS-24 Pole bracket	Outdoor pole mount bracket for PS-24 and AXIS T97A10. Requires the Wall Mount AXIS PS-24 (5000-011) and a mounting tool for straps (21776 or similar).	240	390	225
AXIS T91A03 DIN RAIL CLIP 5PCS	The clip, made of steel, enables mounting on a standard 35mm DIN rail. It includes 2 cable ties. Compatible with AXIS T8120/T8133 midspans and AXIS T8604 / T8605 converters. Weight: 17 g (0.6 oz.). 5-pack.	165	180	40
AXIS MIDSPAN DIN CLIP A	Din clip for AXIS midspan T8123, T8124 and T8125	205	85	10
AXIS P33 MOUNTING BRACKET	Mounting bracket for AXIS P33-VI-LV indoor cameras. For mounting cameras on junction boxes (4" square, 4" octagon, single-gang, or double-gang), and other Axis mounting accessories. Also compatible with selected AXIS M30 and P32 cameras.	165	240	80
TF9905 Wall Mount 5P	Mounting kit for AXIS P1204/E. Kit contents: Flush mount wall bracket. 5 pack.	120	130	95
AXIS TQ1904 MOUNTING BRACKET	Mounting bracket compatible with AXIS Q1715. It includes bracket, pad, and TX20 screw.	90	125	35

AXIS RETROFIT KIT FOR T94S01L 4P	Cover ring and holder for installing selected AXIS P32 cameras with legacy AXIS T94S01L Recessed Mount. Bulk pack with 4 sets of rings and clips to retrofit 4 cameras.	195	205	77
AXIS RETROFIT KIT T94K01L/02L 4P	Retrofit into T94K01L or T94K02L. Mic hole for - LV cameras. Includes 4 sets of lid ring cover, gaskets, screws.	212	216	105
AXIS ACI COND ADAP 3/4" U-SHAPE 30MM 5PCS	Mechanical adapter that provides a U-shaped 30mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS P54-series, AXIS P32-VE Series (requires AXIS ACI Mounting Bracket A), AXIS Q3505-VE, AXIS T91B6X mounts and AXIS AXIS T94R01P Conduit Back Box. 5 pcs.	120	130	95
AXIS ACI CONDUIT ADAPTER 1/2"-3/4" A 2P	Step up ACI adapter for attaching 3/4" conduits or M25 pipes to AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 2 pcs	121	132	95
AXIS ACI COND ADAP 1/2 " U-SHAPE 20MM 5P	Mechanical adapter that provides a U-shaped 20mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 5 pcs	105	155	35
AXIS ACI COND ADAP 1/2"-3/4" NPS 2P	Threaded stainless steel step up ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 1/2" conduit interface such as AXIS Q35-V series. 2 pcs	85	130	42
AXIS ACI CONDUIT ADAPTER 3/4" NPS 2P	Threaded stainless steel ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 3/4" conduit interface such as AXIS Q35-VE series. 2 pcs	85	130	45
AXIS F7308 CABLE BLACK 8M 4PCS	AXIS F7308 comes in packs of four. 8-m (26 ft.) black cable with an RJ12 contact for connection to an AXIS F1004 Sensor Unit. Used as a spare part for the original cable that comes with AXIS F1004 Sensor Unit.	190	185	120
AXIS F8401 CLEAR LENS PROTECTOR 5PCS	Lens protection for AXIS F1005-E. The lens protector is screwed onto the threaded front part of the sensor unit to protect the lens. Comes in pack of 5 units.	105	155	35
AXIS F8202 STRAIGHT MT BRACKET 5PCS	Mounting bracket that allows the pinhole sensor unit of AXIS F1025 to be mounted onto a flat surface with the cone being flush with opposite surface. Comes in pack of 5 pcs.	165	180	40
AXIS F8203 FIXED MT BRACKET 5PCS	Metal bracket for stable mounting of AXIS F1005-E, F1015 and F1035-E. Variety of holes for screws for flexible mounting. Comes in pack of 5 units.	165	180	40
AXIS F8211 PINHOLE TRIM RING 10PCS	Trim ring for discreet mounting of AXIS F1025 Sensor Unit behind a thin surface. 10 PCS.	105	155	35
AXIS F8212 TRIM RING 10PCS	Trim ring for discreet mounting of AXIS F1005-E, F1035-E, P1214-E and P1224-E behind a surface. 10 PCS.	120	130	95
AXIS F8205 BULLET ACCESSORY	Bullet-style camera accessory for AXIS F1005-E. AXIS F1005-E provides 113° horizontal FOV. Comes with c-clamp and a stand.	165	180	45
AXIS F8225 PINHOLE ACCESSORY	Discreet accessory for ceiling mount of AXIS F1025 (pinhole). AXIS F1025 provides 92° horizontal FOV. Used to get overview of rooms or of a door. Can easily be repainted to fit ceiling color.	165	190	75

AXIS F8235 FISHEYE ACCESSORY	Discreet accessory to mount a AXIS F1035-E in a ceiling. Perfect for overview in small rooms or in parts of a larger room. Can easily be repainted to fit ceiling color.	165	190	75
AXIS F92A01 BLACK HEIGHT S. HOUSING	Height strip housing for discrete mounting of a pin hole sensor unit, for capturing eye-level images e.g. of people leaving a store. It is compatible with AXIS F1025, FA1125, F1004 Pin hole, AXIS P1264 and P1265. Comes with both a metric and an imperial height strip. Black aluminium housing.	220	900	75
AXIS F92A01 SILVER HEIGHT S. HOUSING	Height strip housing for discrete mounting of a pin hole sensor unit, for capturing eye-level images e.g. of people leaving a store. It is compatible with AXIS F1025, FA1125, F1004 Pin hole, AXIS P1264 and P1265. Comes with both a metric and an imperial height strip. Silver aluminium housing.	220	900	75
AXIS T91R61 WALL MOUNT	Tiltable wall-mount for AXIS D2110-VE Security Radar and AXIS D2050-VE Network Radar Detector. Includes arm, AXIS T94R01P CONDUIT BACK BOX and conduit 260 mm (10 inch) cable kit.	325	220	90
AXIS TD4601 ACI Conduit Bracket 5pcs	AXIS TD4601 is an ACI Conduit Bracket for AXIS D4100-E Network Strobe Siren. 5P	80	130	30
AXIS TM3001 TILT MOUNT	Tilt Mount Plastic, 15deg tilt, 1/2" (M20) conduit. BRACKET MOUNT ASSEMBLY M3067.	130	115	50
AXIS TM3101 PENDANT WALL MOUNT	Elegant mount for indoor mounting of Axis mini dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, AXIS T8643). Compatible with wide range of cameras, incl. AXIS M20/M30/M31/M42, etc. Made from strengthened eco-friendly plastic.	135	195	50
AXIS TM3101 PENDANT WALL MNT BLACK	Elegant mount in black for indoor mounting of Axis mini dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, AXIS T8643). Compatible with wide range of cameras, incl. AXIS M30, AXIS M31, AXIS M42, etc. Made from strengthened eco-friendly plastic.	135	195	50
AXIS TM3201 RECESSED MOUNT	Recessed mount for selected AXIS M30 cameras. Includes covers for fixed mini dome and panoramic cameras.	135	265	85
AXIS TM3204 RECESSED MOUNT	Indoor recessed mount for ceiling/wall installations. Compatible with AXIS M4308-PLVE. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	185	290	85
AXIS TM3205 RECESSED MOUNT	Designed for indoor drop ceiling installations for selected Axis cameras (M3057/8 and M3077). It's robust with an IK10-rating and is easily installed. The enclosure is made of metal alloy, making it suitable for installations in air-handling (plenum) spaces. Casing includes mic holes for M3077 and plugs in mic holes when used with M3057/8.	225	225	175
AXIS TM3208 RECESSED MOUNT	Indoor recessed mount for ceiling/wall installations. Compatible with AXIS M3057-PLVE, AXIS M3057-PLVE Mk II, AXIS M3058-PLVE, AXIS M3077-PLVE. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	185	290	85

AXIS TM3209 RECESSED MOUNT	Indoor recessed mount for drop ceiling installation. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M3064-V, AXIS M3065-V, AXIS M3066-V, AXIS M3067-P, AXIS M3068-P, AXIS M3075-V, AXIS M3085-V, AXIS M3086-V, AXIS M3088-V.	160	160	150
AXIS TM3210 RECESSED MOUNT	Indoor recessed mount for drop ceiling installation. The aluminum casing makes it suitable for use in air handling spaces. Compatible with selected AXIS M43 Series fisheye panoramic cameras.	160	160	155
AXIS TM3211 RECESSED MOUNT	Recessed mount for selected AXIS M43 cameras. Includes cover for fisheye panoramic cameras.	290	190	90
AXIS TP1601 ADAPTER PLATE	Adapter plate for mounting on conduit back box TP3603 or T94S01P. Plate is for P14 series and M42 series that allows for the cameras to look aesthetically pleasing when mounted onto a conduit back box.	160	175	30
AXIS TP3101 PENDANT WALL MOUNT	Elegant mount for indoor mounting of Axis dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, T8643) and AXIS I/O Indication LED. Compatible with AXIS M32-LVE and AXIS P32-VI-LV cameras. Made from strengthened eco-friendly plastic.	160	225	50
AXIS TP3103-E PENDANT KIT	Outdoor pendant kit for AXIS P3265-LVE, P3267-LVE, P3268-LVE. Compatible with Axis mounts: ceiling, wall, parapet, poll and 1.5" NPS threaded pipes.	244	255	82
AXIS TP3201 RECESSED MOUNT	Indoor recessed mount for drop ceiling installation. Supports the optional use of an internal microphone. Metal enclosure with conduit entries, suitable for installation in air handling / plenum spaces. Compatible with: AXIS M32-LVE, AXIS P32-VI-LV, AXIS P33-V and AXIS Q35-VI-LV series; and AXIS Device Microphone A and B.	225	230	175
AXIS TP3201-E RECESSED MOUNT	Outdoor recessed mount for drop ceiling plenum installations. Supports the optional use of an internal microphone. Metal enclosure with conduit entries, suitable for installation in air handling / plenum spaces. Compatible with: AXIS M32-LVE, AXIS P32-VE/-LVE. T94M02L used in the past for outdoor but size was too big not matching form factor.	225	225	170
AXIS TP3202 RECESSED MOUNT	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with selected AXIS M32 and AXIS P32 cameras.	295	185	80
AXIS TP3203 RECESSED MOUNT	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with selected AXIS M32 and AXIS P32 cameras.	290	185	85
AXIS TP3601 3/4" CONDUIT ADAPTER 4P	Adapters for protected cable routing in 3/4" conduit (M25 pipe). Compatible with selected AXIS M32 and P32 cameras. 4pcs bulk pack.	70	115	53

AXIS TP3603 CONDUIT BACK BOX	TP3603 indoor conduit back box a complement to T94S01P at a lower price point for large indoor installations (eg data centers). Compatible with P32/M32 indoor versions as well as indoor versions of Q17/19/29, P33, Q35, and P14/M42(plate needed TP1601). TP3603 has two separate conduit entries (1/2" & 3/4") and has space for connectors (e.g. T86 Media Converters & T6101 I/O interface).	160	180	60
AXIS TP3701 J-BOX & POLE ADAPTER	Optional accessory for mounting over junction boxes or on poles. Plastic straps (two) are included. Compatible with AXIS TM3101 and TP3101 Pendant Wall Mount.	130	180	35
AXIS TP3905 CONDUIT ADAPTER 1" 4P	Step down ACI adapter 1" to 3/4". IK8 and made of plastic. For attaching 1" conduits or M25 pipes to AXIS products with a 3/4" conduit interface such as P32 or conduit back boxes. Pack of 4.	160	180	37
AXIS TP8101 PENDANT KIT	An indoor metal pendant kit for mounting AXIS P8815-2 3D People Counter. Compatible AXIS ceiling mounts and 1.5" and 3/4" conduits.	100	208	78
AXIS TP8201 RECESSED MOUNT	A plenum rated recessed mount for P8815-2 3D People Counter	120	225	68
AXIS TP3602 1/2" CONDUIT ADAPTER 4P	Adapters for protected cable routing in 1/2" conduit (M20 pipe). Compatible with selected AXIS M32 and P32 cameras. 4pcs bulk pack.	70	115	53
AXIS TQ3101-E PENDANT KIT	An outdoor pendant kit for mounting AXIS Q38 Series.	340	355	150
AXIS TQ3102 PENDANT KIT	An indoor pendant kit for mounting AXIS Q38 Series.	200	240	67
AXIS TQ3201-E RECESSED MOUNT	Recessed mount for indoor and outdoor use of AXIS Q36, P38 and Q38 Series.	270	270	195
AXIS TQ6501-E PARAPET MOUNT	Parapet Mount is an outdoor-ready mount. The round base of the mount makes it easy to install as well as suitable for installations on poles. Cables can be routed through the bottom, or from the side by using a conduit connection. Chromated and powder coated aluminum parapet mount compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Includes mounting plate, pipe seal, conduit hole cover. Color: White	483	800	118
AXIS TQ9601 CONDUIT TOP BOX	CONDUIT TOP BOX for Q9216-SLV.	170	180	65
AXIS TQ6901-E ADAPTER BRACKET 4P	AXIS TQ6901-E is a useful adapter for retrofitting AXIS Q6215-LE in camera installations that have 3rd party competitor mounts. AXIS TQ6901-E is made of powder coated aluminum and is sold in packs of four.	160	180	85
AXIS TS3001 Recorder Mount	AXIS TS3001 Recorder Mount ensures that the AXIS S3008 Recorder is in a fixed position either if it is mounted on walls, shelves, or under tables. Its design and shape allows the recorder to be mounted in two opposite directions.	200	222	73
AXIS TQ6201-E RECESSED MOUNT	Indoor and outdoor plenum recessed mount for AXIS Q6315-LE PTZ. Suitable for outdoor installations in roof overhangs and soffits. Also suitable for indoor installations in plenum spaces.	320	320	212

AXIS TQ1501-E CRANE TRAFFIC MOUNT	A crane and traffic mount for more stability and less vibrations. Note: Pivot mount for more stability, Robust, IK10, Coating in corrosion resilient material, offers more stability to your camera installations in demanding situations, such as mounting on cranes or traffic lights. NEMA 4X-ratings and can be tilted up to 45 degrees. Compatible with P13-E/LE, T92E, T93F, Q16-LE, T92G20, T91B47.	200	180	110
AXIS TM3206 RECESSED MOUNT	Designed for indoor drop ceiling installations for M4308. It's robust with an IK10-rating and is easily installed. The enclosure is made of metal alloy, making it suitable for installations in air-handling (plenum) spaces. Casing includes mic holes.	225	225	175
AXIS TM3207 RECESSED MOUNT	Designed for indoor drop ceiling installations for selected Axis cameras (M3067/8, M4216). It's robust with an IK10-rating and is easily installed. The enclosure is made of metal alloy, making it suitable for installations in air-handling (plenum) spaces.	160	160	150
AXIS TF9902 SURFACE MOUNT	Bracket to mount and secure a F series main unit onto a surface. It withstands vibrations and secures all cables to/from the main unit.	160	175	35
AXIS TF9903 DIN RAIL CLIP	DIN clip + angled mounting bracket. Allows an AXIS F Series main unit to be mounted on a DIN rail with the short side against the rail to minimize used space. Main unit can be mounted with cables going in any of three directions (up, down or out from the rail).	160	175	35
AXIS TM5601 CONDUIT BACK BOX	Indoor conduit back box for AXIS M5000 & AXIS M5000-G. Has a conduit side entry with a conduit cover. Has 3 tx20 screws.	266	276	47
AXIS TD3901 Strain Relief 2P	Strain relief accessory for AXIS D3110 Connectivity Hub, preventing cables getting lose over time causing disconnection of the device or sensors. Easy to mount, comes with two screws. 2 pack	110	95	20
AXIS TD3902 Connector Kit	Spare kit of connectors for AXIS D3110 Connectivity Hub.	60	80	10
AXIS TP1602-E Conduit Back Box	A conduit back box that gives more space needed for installation. Deeper back box than what product comes with and existing conduit back boxes. Compatible with P1455-LE, P1467/8-LE. Comes in Axis white and is IP66 and IK10.	170	185	57
AXIS TF1902-RE MOUNTING BRACKET 4P	AXIS TF1902-RE Mounting Bracket 4P is a bulk pack of 4x Mounting brackets. The mounting bracket is an accessory for the AXIS F2105-RE and F2135-RE, F7225-RE, FA1105, FA1125 and FA1080-E sensors. Thanks to the different hole patters as well as the possibility to bend the bracket in numerous directions, AXIS TF1202-RE Mounting bracket gives extra flexibility and resilience of the sensor unit.	102	118	45

AXIS TF1202-RE RECESSED MOUNT 4P	TF1202-RE Recessed Mount 4P is a bulk pack of 4x Recessed Mounts for AXIS F2105-RE Standard sensor. AXIS TF1202-RE Recessed Mount is the perfect accessory when installing AXIS F2105-RE standard sensor in a wall, a glass, plastic or metal panel from 1 to 15mm. Beyond the aesthetics aspect giving a finishing look of the installation, it also guarantees that no water will leak into the wall or the panel. AXIS TF1202-RE Recessed Mount is made of plastic and comes with a built-in lens protection highly recommended when AXIS F2105-RE is used in harsh environment.	105	120	45
AXIS TF1203-RE RECESSED MOUNT 4P	AXIS TF1203-RE Recessed Mount 4P is a bulk pack of 4x Recessed Mount for AXIS F2135-RE Fisheye sensor. AXIS TF1203-RE Recessed Mount is the perfect accessory when installing AXIS F2135-RE standard sensor in a wall, a glass, plastic or metal panel from 1 to 15mm. Beyond the esthetics aspect giving a finishing look of the installation, it also guarantees that no water will leak into the wall or the panel. AXIS TF1203-RE Recessed Mount is made of plastic and comes with a built-in lens protection highly recommended when AXIS F2135-RE is used in harsh environments.	105	120	45
AXIS TF1901-RE SWIVEL MOUNT 4P	AXIS TF1901-RE Swivel Mount 4P is a bulk pack of 4x Swivel Mounts for AXIS F21 sensors. It allows the modular sensor unit to be fixed and angled to get the desired viewing direction.	102	118	45
AXIS TF1201-RE RECESSED MOUNT 4P	AXIS TF1201-RE Recessed Mount is a bulk pack of 4x Recessed Mount for AXIS F2105-RE standard sensor unit and AXIS F2135-RE fisheye sensor unit. AXIS TF1201-RE Recessed Mount is the perfect accessory when installing the selected sensor units in a wall, a glass, plastic or metal panel from 1mm to 15mm. Beyond the aesthetics aspect giving a finishing look of the installation, it also guarantees that no water will leak into the wall or the panel. AXIS TF1201-RE comes in silver and is made of aluminium.	105	120	45
AXIS TQ1003-E Wall Mount	Wall mount compatible with all Axis outdoor fixed box cameras and housings. Corrosion tested according to NEMA 4X, UL listed and IK10 rated. Highly robust, Rotatable, and Flexible cable routing.	150	235	95
AXIS TQ3103-E PENDANT KIT	Pendant kit for indoor and outdoor use for the AXIS Q36-VE Series compatible with Axis ceiling-/wall-/pole mounts with 1.5" NPS thread.	310	330	100
AXIS TQ3202-E RECESSED MOUNT	Recessed mount for indoor and outdoor use of AXIS Q3626/8 VE. It has a metal back box and is suitable for installation in plenum (air-handling) spaces.	270	270	190
AXIS TM4101 PENDANT KIT	Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. Compatible with the small form factor of AXIS M42 series of cameras.	129	146	56

AXIS TM4201 RECESSED MOUNT 4P	A recessed mount compatible with M42 series of cameras. Designed for soft ceilings that have thickness of 15+/-1 mm. Includes adapter mount top and mount bottom. Comes in 4p.	284	301	47
AXIS TP5201-E RECESSED MOUNT	Outdoor recessed mount for AXIS P56 cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a hole for cable protection conduits.	320	320	210
AXIS TP4601-E Conduit Back Box	Outdoor-ready, impact resistant (IK10) back box with sealed compartment (IP66/67) for secure storage of connectivity devices (T6101 MKII, T8645,8). 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind AXIS P4705-PLVE, and AXIS P4707-PLVE.	200	295	70
AXIS TQ3601-E CONDUIT BACK BOX	Outdoor-ready, impact resistant (IK11) back box with sealed compartment (IP66/67) for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind AXIS P3807-PVE, AXIS P3818-PVE, AXIS P3827-PVE, AXIS Q3536-LVE, AXIS Q3538-LVE, AXIS Q3626-VE, AXIS Q3628-VE, AXIS Q3819-PVE, AXIS Q3839-PVE. Includes a network cable and extra gaskets.	230	250	60
AXIS TP3004-E Wall Mount Black	A black version of T91D61 which is chromated and powder coated aluminum wall mount with 1.5" NPS thread for fixed dome pendant kits. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal and conduit hole cover. Color: Black	250	322	165
AXIS TP3105-E Pendant Kit Black	TP3105-E is a black version of T94N01D which is white. It has a weathershield and a mounting adapter for AXIS P37x-PLE Network Cameras. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P37x-PLE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	277	277	58
AXIS TP3106-E Pendant Kit Black	Black Indoor pendant kit similar to T94K01D white for AXIS P32-V Series- AXIS M43/-V, AXIS M32-V, AXIS M30-V compatible with Axis ceiling-/wall mounts, AXIS pole mount and 1.5" NPS threaded pipes.	188	200	74
AXIS TP3301-E Pole Mount Black	A black version of T91B67 white which is Outdoor-ready, powder-coated aluminum pole mount with 1.5" NPS thread for fixed dome pendant kits. Includes insect-proof cable gasket and 1 pair of stainless steel straps (with TX30 screw) for pole diameter between 65-165mm (2.5"-6.5"). White in color.	247	325	201
AXIS TP3204-E RECESSED MOUNT	Outdoor recessed mount for discreet installations in drop ceilings, roof overhangs/soffits of AXIS P3735-PLE, AXIS P3737-PLE, AXIS P3738-PLE. Suitable for installations in plenum space, as the back box is made of metal with a 3/4" hole for cable protection conduits.	115	320	340

AXIS TQ5001-E Wall/Pole Mount	Wall-and-Pole Mount for Axis PTZ and multi-sensor cameras. Built-in Ethernet cable with an IP66 RJ45 connector for quick installation with protection against dust and water. Connect PoE via either RJ45 or IDC (insulation-displacement contact) connectors. Suitable for both indoor and outdoor environments. Separate stainless steel straps required for pole installation.	165	300	195
AXIS TP1001-E Wall/Pole Mount	Wall-and-Pole Mount for Axis PTZ and multi-sensor cameras. Built-in Ethernet cable with an IP66 RJ45 connector for quick installation with protection against dust and water. Connect PoE via either RJ45 or IDC (insulation-displacement contact) connectors. Suitable for both indoor and outdoor environments. Separate stainless steel straps required for pole installation. The 1.5" NPS thread mount ensures compatibility with all pendant kits for Axis fixed dome cameras.	165	300	235
AXIS TW4100 Front Windshield Mount	Adhesive windshield mount compatible with selected F-series sensors for secure and easy mounting on the front windshield.	110	150	40
AXIS TW4101 Rear Windshield Mount	Adhesive windshield mount compatible with selected F-series sensors for secure and easy mounting on the rear windshield.	110	150	40
AXIS TQ4901 Cover Sleeve	A cover sleeve that fits around AXIS TP4601-E Conduit Back Box. Sleeve done for Q9307-LV used with AXIS TP4601-E Conduit Back Box. If sleeve not used with conduit back box there is a mushroom effect where Q9307 is too big for TP4601. Technically Q9307 can fit on TP4601 without sleeve but would not look good.	170	260	70
AXIS TP9601 Conduit Top Box	Conduit back box for corner camera P9117-PV. Has two conduit entries 3/4" (m25), made of steel and comes in white.	120	175	75
AXIS TM5602-E CONDUIT ADAPTER	Mechanical adapter that provides a U-shaped 30mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS M5525-E, AXIS M5526-E.	80	132	47
AXIS TQ9301 Corner Bracket	Corner indoor bracket compatible with: AXIS P3265-LV: AXIS P3265-V, AXIS P3267-LV, AXIS P3268-LV, AXIS Q9307-LV. Comes with 4 TX20 screws. Made of steel, and painted Axis white.	170	210	80
AXIS TM3213 Recessed Mount	Indoor recessed mount for drop ceiling installation. The aluminum (plenum) casing makes it suitable for use in air handling spaces. Compatible with AXIS M3125-LVE, AXIS M3126-LVE, AXIS M3128-LVE.	160	160	150
AXIS TQ9302 Pole Mount	A pole mount for Telesitting in Healthcare is main use case when a IV pole type needs a mount for a pole to attach a camera. The mount should be mountable on thin poles from 18mm to 25mm. Cable entry from top or bottom up. Mount compatible with Q9307-LV, several P32 cameras and I8116.	153	80	55

AXIS TF1201 RECESSED MOUNT 4P	AXIS TF1201 Recessed Mount is a bulk pack of 4x Recessed Mount for AXIS FA1105 sensor unit Beyond the aesthetics aspect giving a finishing look of the installation, AXIS TF1201 Recessed Mount is the perfect accessory when installing the selected sensor units in a wall, a glass, plastic or metal panel from 1mm to 15mm. AXIS TF1201 comes in silver and is made of aluminium.			
AXIS TF1202 RECESSED MOUNT 4P	TF1202 Recessed Mount 4P is a bulk pack of 4x Recessed Mounts for AXIS FA1105 sensor unit. Beyond the aesthetics aspect giving a finishing look of the installation, AXIS TF1202 Recessed Mount is the perfect accessory when installing AXIS FA1105 sensor unit in a wall, a glass, plastic or metal panel from 1 to 15mm. AXIS TF1202 Recessed Mount is made of plastic and comes with a built-in lens protection highly recommended to protect FA1105 lens from tempering or vandalism.			
AXIS TF1804 Bullet Housing 4 pcs	AXIS TF1804 Bullet Housing 4P is a bulk pack of 4 Bullet Housings for AXIS F21 sensor units. AXIS TF1804 Bullet Housing is an indoor Bullet housing which fits all F21 sensors. The bullet housing comes with a stand for an easy mounting on a wall or ceiling.	120	265	70
AXIS TM3212 Recessed Mount	Recessed mount for AXIS M3125-LVE, AXIS M3126-LVE, AXIS M3128-LVE. Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	185	285	80
AXIS TM5806-E Housing	A housing for AXIS M5000, AXIS M5000-G that makes the camera outdoor ready. Resistant to harsh weather conditions (IP66, IK10, NEMA 4x), PVC-free, made of aluminum material. Note a harting connector needs to be used as interface to secure IP-rating.			
AXIS T99A11 24V AC/DC	High accuracy outdoor positioning unit to be used with PT Mount models in AXIS Q19 and Q29 series. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Optional wall mount and pole mount accessories available separately. Powered by 24 V AC/DC.	375	375	730

AXIS T99A12 PT Unit 24 V	High accuracy outdoor positioning unit to be used with the outdoor models of AXIS P13 Series and AXIS Q1656-LE. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Optional wall mount and pole mount accessories available separately. Powered by 24 V AC/DC. T99A12 expand the possibilities for IR light, upcoming White light as well as wiper which is included in upcoming AXIS Q1656-LE .	280	280	520
AXIS TC1601 Universal Mount	Versatile accessory to be used with AXIS C1410 Network Mini Speaker. It can be used as either a pendant kit with 3/4" (M25) conduit interface, conduit back box with 1/2" (M20) conduit side entry, or with standard stands or holders using the integrated female (M6) tripod thread.	210	200	50
AXIS TC1701 Front Cover 5P	AXIS TC1701 Front Cover is sold as spare parts to the AXIS C1410 Network Mini Speaker. It enables easy on-site replacement in case the original front cover has been damaged. The cover is re-paintable. Solid in packs of five units.	210	185	115
AXIS TC1603 TILE BRIDGE 2P	AXIS TC1603 Tile Bridge is a mount plate used with AXIS C1210-E Network Ceiling Speaker and AXIS C1211-E Network Ceiling Speaker. The tile bridge is to be used in soft ceiling installations, as it prevents the ceiling tile to sink downward by distributing the speaker weight. Sold in 2pcs per pack.	385	690	40
AXIS TC1602 CONDUIT ADAPTER 5P	AXIS TC1602 Conduit Adapter is used for protected cable routing in 3/4" conduits and M20 pipes. Compatible with AXIS C12-series of network ceiling speakers. Sold in 5pcs per pack.	140	220	50
AXIS TC1901 WIRE KIT 5P	AXIS TC1901 is a kit for installing AXIS C15 pendant speakers hanging from the ceiling. It contains a 10m/32.8ft wire and a hook for easy adjustment of the mounting height. Sold in 5pcs per pack.	140	220	50
AXIS TC1902 Ceiling Speaker Gasket 5P	AXIS TC1902 is a gasket to use with AXIS C1210-E ceiling speakers to allow IP54 rating.	310	330	35
AXIS TC1903 Ceiling Speaker Gasket 5P	AXIS TC1903 is a gasket to use with AXIS C1211-E ceiling speakers to allow IP54 rating.	310	330	35
AXIS TC6901	AXIS C6110 Network Paging Console comes with a built in microphone and can be used stand-alone. For customers preferring a gooseneck microphone AXIS TC6901 Gooseneck Microphone can be bought as an optional accessory.	410	75	45

AXIS AUDIO MANAGER CENTER 1Y ELIC	AXIS Audio Manager Center is a subscription-based hybrid cloud service for remote management and monitoring of multisite audio systems. Cloud-based and on-premises components combine to provide a stable solution, even if internet access is temporarily down. The software significantly reduces user workloads, with a single sign-on to schedule announcements, background music, ads, and more for all selected sites using AXIS Audio Manager Edge. It's simple to set up and to adjust zones, content, and schedules, without downtime. Furthermore, health monitoring provides immediate notifications if any part of the system isn't working. AXIS Audio Manager is licensed annually by the number of speaker devices (or equivalent) in the system. A no-cost version with a limited feature set is also available. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
AXIS AUDIO MANAGER PRO - E-LICENSE	AXIS Audio Manager Pro provides easy, remote management of large IP audio installations. The AXIS AUDIO MANAGER PRO - E-LICENSE is used to when installing AXIS Audio Manager Pro on your own custom hardware or virtual machine (VMWare, Microsoft Hyper-V, Microsoft Windows Datacenter) Delivered as eLicense key. One license key per unit. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	0	0	0
AXIS C7050 MK III	AXIS Audio Manager Pro provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. Especially useful in retail or in schools, AXIS Audio Manager Pro helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or centrally to all devices. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager realizes the benefits of network audio.	260	550	145

AXIS SPEAKER FOR INFORMACAST ELIC	AXIS Speaker Functionality for Singlewire InformaCast® is a licensed add-on to compatible Axis network speakers, network bridge or network amplifier and with this you get InformaCast® compatibility. AXIS Speaker Functionality for Singlewire InformaCast® is applicable for One(1) Axis network device perpetually and it requires a separate subscription for the InformaCast® application acquired from Singlewire. Delivered as an eLicense key, One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
AXIS XC1311	AXIS XC1311 Explosion-protected Network Horn Speaker is certified for use in hazardous locations (ATEX: II 2G Ex d IIC T5 Gb, II 2D Ex tb IIIC T=91°C Db; IECEX: Ex db IIC T5 Gb, Ex tb IIIC T=91°C Db; cULus: Class I Div 1 ABCD T5, Class I Zone 1 AEx db IIC T5 Gb, Zone 21 AEx tb IIIC T=91°C Db). The speaker is a complete audio system in a single unit. It connects to the standard existing network without need for a separate audio network. Built-in memory supports pre-recorded messages, or operators can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP).	250	250	445
AXIS C6110	AXIS C6110 Network Paging Console complements your network speakers to create a complete public address system that enables live paging, prerecorded callouts, and two-way audio. Configure as many zones as needed in the web interface, using the expandable tree structure. Then, to page, navigate to the right zone using the console's color LCD and twelve physical buttons. You can also configure buttons to trigger actions on other IoT devices – for example, doors or lights. The console can be wall-mounted or placed on a desktop, where you can use it as-is, with an external headset, or with AXIS TC6901 Gooseneck Microphone	335	180	105

AXIS C1310-E NETWORK HORN SPEAKER	AXIS C1310-E Network Horn Speaker is perfect for outdoor environments in most climates. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1310-E allows users to remotely It allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). AXIS C1310-E is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost-effective approach to system design.	200	240	270
AXIS C1004-E NETW CAB SPEAKER BLACK	AXIS C1004-E Network Cabinet Speaker (black) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	295	350	260
AXIS C1004-E NETW CAB SPEAKER WHITE	AXIS C1004-E Network Cabinet Speaker (white) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	295	350	260

AXIS C1410 NETWORK MINI SPEAKER	AXIS C1410 Network Mini Speaker is a discreet and affordable speaker that fits into smaller spaces and provides wide-area audio coverage. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1410 allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general announcements. Built-in memory supports pre-recorded messages, or personnel can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound and with remote health testing you know that it is working. Open standards support easy integration with network video, access control, analytics, and VoIP. AXIS C1410 is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost-effective approach to system design. It also has a built-in PIR sensor for motion detection.	195	195	100
AXIS C1210-E NETWORK CEILING SPEAKER	AXIS C1210-E Network Ceiling Speaker is an all-in-one speaker system that makes voice announcements and background music smart and easy. It connects to standard network using one cable for both power (PoE) and connectivity. AXIS C1210-E offers flexible, discrete recessed ceiling installation, ideal for indoor environments but can also be used for protected outdoor areas like under the eaves. Additionally, it features a backbox that meets plenum requirements. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processor (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing and 2-way audio talk-back. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management. The outer diameter is 283 mm (11.1 in) and the dimension for fixing hole is 261 mm (10.3 in).	365	365	265

AXIS C1211-E NETWORK CEILING SPEAKER	AXIS C1211-E Network Ceiling Speaker is an all-in-one speaker system that makes voice announcements smart and easy. It connects to standard network using one cable for both power (PoE) and connectivity. AXIS C1211-E offers flexible, discrete recessed ceiling installation, ideal for indoor environments but can also be used for protected outdoor areas like under the eaves. Additionally, it features a backbox that meets plenum requirements. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processor (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing and 2-way audio talk-back. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management. The outer diameter is 216 mm (8,5 in) and the dimension for fixing hole is 194 mm (7.6 in)	235	245	200
AXIS C1510 NETWORK PENDANT SPEAKER	AXIS C1510 Network Pendant Speaker is an all-in-one speaker system that makes voice announcements smart and easy. It connects to standard network using one cable for both power (PoE) and connectivity. AXIS C1510 is ideal for high ceiling installations of any height, thanks to easy adjustable wire length [wire not included]. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processor (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing and 2-way audio talk-back. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management. Axis pendant speakers comes in two sizes, whereas AXIS C1510 is the larger more powerful model.	412	387	306
AXIS C1511 NETWORK PENDANT SPEAKER	AXIS C1511 Network Pendant Speaker is an all-in-one speaker system that makes voice announcements smart and easy. It connects to standard network using one cable for both power (PoE) and connectivity. AXIS C1511 is ideal for high ceiling installations of any height, thanks to easy adjustable wire length [wire not included]. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processor (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing and 2-way audio talk-back. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management. Axis pendant speakers comes in two sizes, whereas AXIS C1511 is the smaller model.	290	290	270

AXIS C1610-VE	AXIS C1610-VE Network Sound Projector is perfect for outdoor environments in most climates. It has a nice design and is very robust (IK11 rating) making it the perfect choice for environments in need for a less intrusive design and when the placement means a risk for vandalism from people. AXIS C1610-VE allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. The speaker is a complete audio system in a single unit including audio management software. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound and the speakers sound quality enables high quality speech. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). AXIS C1610-VE is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost-effective approach to custom design.	258	266	187
AXIS C1110-E White	AXIS C1110-E is a combination of great performance and design. It is a very flexible speaker that can be used for voice messages and background music, can be installed indoors or protected outdoors, its easy-click mounting bracket supports installations on walls, ceilings, and poles, and it can be mounted horizontally or vertically. AXIS C1110-E supports full duplex 2-way communication with echo cancellation, and the built-in microphone enables remote health testing as well. AXIS C1010-E offers digital signal processing for clear voice messages and background music, and its rich bass makes it the perfect choice if background music is a primary use case. It's built on an open platform, supporting integration with VMS, access control, analytics and VoIP with SIP support. AXIS Audio Manager Edge software comes preinstalled for easy management of users, content, zones, and scheduling. This all-in-one speaker system connects to the standard network using a single cable for power (PoE) and connectivity.	237	342	203

AXIS C1110-E Black	AXIS C1110-E is a combination of great performance and design. It is a very flexible speaker that can be used for voice messages and background music, can be installed indoors or protected outdoors, its easy-click mounting bracket supports installations on walls, ceilings, and poles, and it can be mounted horizontally or vertically. AXIS C1110-E supports full duplex 2-way communication with echo cancellation, and the built-in microphone enables remote health testing as well. AXIS C1010-E offers digital signal processing for clear voice messages and background music, and its rich bass makes it the perfect choice if background music is a primary use case. It's built on an open platform, supporting integration with VMS, access control, analytics and VoIP with SIP support. AXIS Audio Manager Edge software comes preinstalled for easy management of users, content, zones, and scheduling. This all-in-one speaker system connects to the standard network using a single cable for power (PoE) and connectivity.	237	342	203
AXIS C1111-E White	AXIS C1111-E is a combination of great performance and design. It is a very flexible speaker that can be used for voice messages and background music, can be installed indoors or protected outdoors, its easy-click mounting bracket supports installations on walls, ceilings, and poles, and it can be mounted horizontally or vertically. AXIS C1111-E supports full duplex 2-way communication with echo cancellation, and the built-in microphone enables remote health testing as well. AXIS C1011-E offers digital signal processing for clear voice messages and background music. It's built on an open platform, supporting integration with VMS, access control, analytics and VoIP with SIP support. AXIS Audio Manager Edge software comes preinstalled for easy management of users, content, zones, and scheduling. This all-in-one speaker system connects to the standard network using a single cable for power (PoE) and connectivity.	190	285	165
AXIS C1111-E Black	AXIS C1111-E is a combination of great performance and design. It is a very flexible speaker that can be used for voice messages and background music, can be installed indoors or protected outdoors, its easy-click mounting bracket supports installations on walls, ceilings, and poles, and it can be mounted horizontally or vertically. AXIS C1111-E supports full duplex 2-way communication with echo cancellation, and the built-in microphone enables remote health testing as well. AXIS C1011-E offers digital signal processing for clear voice messages and background music. It's built on an open platform, supporting integration with VMS, access control, analytics and VoIP with SIP support. AXIS Audio Manager Edge software comes preinstalled for easy management of users, content, zones, and scheduling. This all-in-one speaker system connects to the standard network using a single cable for power (PoE) and connectivity.	190	285	165

AXIS C1310-E Mk II	AXIS C1310-E Mk II Network Horn Speaker is perfect for outdoor environments in most climates. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1310-E Mk II allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP).	280	245	200
AXIS C1410 Mk II	AXIS C1410 Mk II Network Mini Speaker is a discreet and affordable speaker that fits into smaller spaces and provides widearea audio coverage. It allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general announcements. Built-in memory supports pre-recorded messages, or personnel can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP. It also has a built-in PIR sensor for motion detection.	185	200	100
AXIS TC1703 Mesh Cover 5p	AXIS TC1703 Front mesh cover is sold as spare parts to the AXIS C1210-E Ceiling Speaker and AXIS C1510 Pendant Speaker. It enables easy on-site replacement in case the original front mesh cover has been damaged. The cover is re-paintable. Solid in packs of five units.	310	330	35
AXIS TC1704 Mesh Cover 5p	AXIS TC1704 Front mesh cover is sold as spare parts to the AXIS C1211-E Ceiling Speaker and AXIS C1511 Pendant Speaker. It enables easy on-site replacement in case the original front mesh cover has been damaged. The cover is re-paintable. Solid in packs of five units.	260	263	65
AXIS TC1705 Mesh Cover White 5 pcs	AXIS TC1705 White Front mesh cover is sold as spare parts to the White AXIS C1110-E Network Cabinet Speaker. It enables easy on-site replacement in case the original front mesh cover has been damaged. The cover is re-paintable. Sold in packs of five units.	317	240	65
AXIS TC1705 Mesh Cover Black 5 pcs	AXIS TC1705 Black Front mesh cover is sold as spare parts to the Black AXIS C1110-E Network Cabinet Speaker. It enables easy on-site replacement in case the original front mesh cover has been damaged. The cover is re-paintable. Sold in packs of five units.	317	240	65
AXIS TC1706 Mesh Cover White 5 pcs	AXIS TC1706 White Front mesh cover is sold as spare parts to the AXIS C1111-E Network Cabinet Speaker. It enables easy on-site replacement in case the original front mesh cover has been damaged. The cover is re-paintable. Sold in packs of five units.	257	165	65

AXIS TC1706 Mesh Cover Black 5 pcs	AXIS TC1706 Black Front mesh cover is sold as spare parts to the AXIS C1111-E Network Cabinet Speaker. It enables easy on-site replacement in case the original front mesh cover has been damaged. The cover is repaintable. Sold in packs of five units.	257	165	65
AXIS C8310 Volume Controller	AXIS C8310 is a control panel for adjusting music volume in a zone and selecting between multiple scheduled audio sources. The panel has six buttons with volume up, volume down, mute and three numbered program selectors. It connects as an accessory to the I/O port of a host network audio device. It supports recessed wall mount (US single gang box and EU connection box). The product is easy to install and a frame for optional wall mount is included. The product is available in white.	100	135	45
AXIS C8110 NETWORK AUDIO BRIDGE	AXIS C8110 Network Audio Bridge is a smart solution based on open standards for connecting and combining analog and digital audio systems. Thanks to the built-in AXIS Audio Manager Edge application you can get functionalities like zone management and content scheduling in existing analog systems. With SIP support it is possible to connect an IP telephony system for callouts in analog speakers. With analog audio input you can easily integrate your intercom system or music streaming box with network speakers from Axis.	116	180	31
AXIS C8210 NETWORK AUDIO AMP	AXIS C8210 Network Audio Amplifier is a smart migration tool for transforming any passive speaker, independent of brand or formfactor, into a network speaker. This gives you all the benefits of network audio including less components. AXIS C8210 enables scalable and cost-effective solutions and can power up to eight speakers with a total power output of 15 W. Based on open standards, the amplifier is easily integrated with other systems. It is small, easy to place, and easy to connect using Power over Ethernet.	117	175	37
AXIS XPQ1785	Explosion-protected stainless steel (316L) PTZ network camera certified for use in hazardous areas according to ATEX, IECEx, cMETus. Ex db IIC T5 Gb, Ex tb IIIC T100°C Db, Class I/II/III Div 1 Groups B, C, D, E, F, G, Class I Zone 1 AEx db IIC T5 Gb, Zone 21 AEx tb IIIC T100°C Db. IP 66/67/68, Type 4X. Certificate: 20ATEX0651X (ATEX), EXV 20.0017X (IECEx), E115198 (cMETus), part code: P21. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan and tilt and 256 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and built-in smoke and fire detection. Operating temp -60°C to +60°C. 110-230VAC, RJ45 and SFP for fiber or coax connection. Integrated wiper, sunshield and AXIS Surveillance microSDXC card 128Gb included.	400	600	250

AXIS XFQ1656	1/1.8" sensor, 4 MP, Day/night, explosion-protected fixed camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 3.9-10 mm F1.5 i-CS lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics with PPE monitoring (missing hard hat detection), Video motion detection, shock detection and active tampering alarm. Smoke alert smoke and fire detection analytic. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Optional analog or digital microphone, two-way audio. Supervised I/O for alarm/event handling, 128GB SD card included. Serial port for RS485 communication. PoE or 110-230VAC power input, SFP + RJ45 for network connectivity. Electropolished stainless steel (316L) enclosure, certified for use in hazardous areas according to ATEX, IECEx, cMETus. Ex db IIC T5 Gb, Ex tb IIIC T100°C Db, Class I/II/III Div 1 Groups B, C, D, E, F, G, Class I Zone 1 AEx db IIC T5 Gb, Zone 21 AEx tb IIIC T100°C Db. IP 66/67/68, Type 4X. Certificate: 20ATEX0651X (ATEX), EXV 20.0017X (IECEX), E115198 (cMETus), part code: F31. Swivel joint included.	285	390	215
AXIS P1468-XLE	Explosion-protected (ATEX: II 3 G Ex ec IIC T4 Gc, II 2 D Ex tb IIIC 135C Db; IECEx: Ex ec IIC T4 Gc, Ex tb IIIC T135C Db; cULus: Class I Div 2 Group ABCD T4, Class II Div 2 Group FG T135C; Class III Div 2, Class I Zone 2 AEx ec IIC T4 Gc, Zone 21 AEx IIIC T135C Db) fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR. Varifocal 6-13 mm P-iris lens with remote zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 8MP stream up to 60 fps, 30fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, Smoke alert analytic. Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, defogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. AXIS Edge Vault for added cyber security. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Powered by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield.	140	260	180

AXIS Q1961-XTE 7 mm 8.3 fps	AXIS Q1961-XTE is an ARTPEC 8 based explosion-protected (ATEX: II 3 G Ex ec IIC T4 Gc, II 2 D Ex tb IIIC T135C Db; IECEX: Ex ec IIC T4 Gc, Ex tb IIIC T135C Db; cULus: Class I Div 2 Group ABCD T4, Class II Div 2 Group FG T135C; Class III Div 2, Class I Zone 2 AEx ec IIC T4 Gc, Zone 21 AEx IIIC T135C Db) thermometric camera that lets you remotely monitor temperatures from -40 °C to 350 °C (-40 °F to 660 °F). It supports up to 10 configurable polygonal detection areas allowing you to monitor for specific temperature levels and change rates. With early fire detection analytics (included), it's possible to set triggers and preventively act on early signs of fire. Robust and impact-resistant (IK10 (excluding front glass) and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free and light weight. Edge-to-edge functionality lets you connect network speakers and other Axis network devices	140	260	180
EXCAM XF M3016	Explosion-protected, PoE powered, 3 MP fixed network camera, ATEX/IECEX/EAC-Ex/IA/PESO certified for hazardous locations. Ex II 2 G Ex d IIC T6 Gb, Ex II 2 D Ex t IIIC T80°C Db IP68, -5°C <= Ta <= +50°C (intermittent). Model key:T08-VA1.2.K1.BOR-N.N-005.N-P-090. Stainless steel 316L housing. 2.8mm F2.0 lens. Zipstream, WDR. AXIS Surveillance SD Card 128GB, 5m network cable preinstalled. Built to order, 6 weeks lead time.	265	570	190
EXCAM XF P1377	Explosion-protected, PoE powered, 5 MP fixed network camera, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T5 Gb, Ex II 2 D Ex t IIIC T100°C Db IP68, -60°C <= Ta <= +60°C. Model key:T08-VA2.3.K3.BOR2-C-005-K-LL. Stainless Steel 316L housing. i-CS mount lens, 3.9-10 mm, F1.2. Lightfinder 2.0, Zipstream, Forensic WDR. AXIS Surveillance SD Card 64GB, 5m network and power cable preinstalled. Built to order. 6 weeks lead time.	450	550	290
ExCam XF P3807	ExCam XF P3807 is an explosion-protected multi-sensor camera, providing an easy, reliable and cost-efficient one-camera installation – reducing installation time, cabling and VMS license costs. Thanks to its excellent image sensors, along with Forensic WDR and Lightfinder technology, it provides great video quality in any light conditions. Its four sensors give a seamless 180° panoramic overview, at up to 30 fps in 8 MP resolution. Enclosed in a stainless steel enclosure (1.4404), it is ATEX, IECEX and INMETRO certified II 2G Ex db IIC, T6 GB, II 2 D Ex tb IIIC T85°C Db IP68. Operating temp -50C to +60C.	285	320	490

EXCAM XF Q1785	Explosion-protected, PoE powered, HDTV 1080p 32x optical zoom, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T5 Gb, Ex II 2 D Ex t IIIC T95°C Db IP68, -60°C ≤ Ta ≤ +60°C. Model key:T08-VA2.3.K3.BOR5-C-005-K-LL. Stainless Steel 316L housing with wiper and sunshield. Lightfinder, Zipstream, forensic WDR, electronic image stabilization. AXIS Surveillance SD Card 64GB, 5m network and power cable preinstalled, Ex e connection box. <u>Built to order. 6 weeks lead time.</u>	450	550	290
EXCAM XPT Q6075	Explosion-protected, top performance, PoE powered HDTV 1080p PTZ dome network camera with 40x zoom, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T6 Gb, Ex II 2 D Ex t IIIC T80°C Db IP68, -50°C ≤ Ta ≤ +60°C. Model key:T08-TNXCD-C-005-K-LL. Stainless Steel 316L housing. Auto day/night functionality, Zipstream, wide dynamic range, electronic image stabilization, highlight compensation. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p@60 fps, Lightfinder 2.0. AXIS T8154 PoE midspan with fiber slot is included (for installation in safe area or Ex d enclosure), AXIS Surveillance SD Card 128GB, EXTB-3 connection box, 5m armored network and power cable preinstalled. <u>Built to order, 6 weeks lead time</u>	665	320	290
AXIS M1055-L BOX CAMERA	Day/night, small indoor box style 2 MP / HDTV camera with a Deep Learning Processing Unit (DPLU). Built-in IR illumination and WDR. Fixed lens with 103° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Built-in I/O. MQTT support. Axis Object Analytics, video motion detection and active tampering alarm. MicroSD memory card slot for local storage. AXIS Edge Vault for increased Cyber Security. Tally LED to indicate video streaming or recording. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes bracket for easy mounting on wall and corner. Midspan not included	105	140	90
AXIS M1075-L BOX CAMERA	Day/night, small fully featured indoor box style 2 MP / HDTV camera with a Deep Learning Processing Unit (DPLU). Built-in IR illumination and WDR. Fixed lens with 103° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Built-in microphones and speaker for two-way audio, I/O and integrated PIR motion sensor. Micro-HDMI output. MQTT support. Axis Object Analytics, video motion detection and active tampering alarm. MicroSD memory card slot for local storage. AXIS Edge Vault for increased Cyber Security. Tally LED to indicate video streaming or recording. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Optional wireless kit available. Includes bracket for easy mounting on wall and corner. Midspan not included	105	140	90

AXIS M1135 MK II	HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Camera also supports i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with either built-in microphone or optional microphone. I/O for alarm/event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	150	200	85
AXIS M1135 MK II i-CS	HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal i-CS lens 3.5-10 mm F1.8 with remote installation zoom and focus. Camera also supports DC-iris lenses. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with either built-in microphone or optional microphone. I/O for alarm/event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	150	195	85
AXIS M1135-E MK II	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Camera also supports i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with optional microphone. I/O for alarm/event handling, MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Operation in -25°C to +50°C. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included.	255	360	145

AXIS M1135-E MK II i-CS	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal i-CS lens 3.5-10 mm F1.8 with remote installation zoom and focus. Camera also supports DC-iris lenses. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with optional microphone. I/O for alarm/event handling, MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Operation in -25°C to +50°C. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included	255	350	140
AXIS M1137 MK II	5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Camera also supports i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with either built-in microphone or optional microphone. I/O for alarm/event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	150	200	85
AXIS M1137 MK II i-CS	5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal i-CS lens 3.5-10 mm F1.8 with remote installation zoom and focus. Camera also supports DC-iris lenses. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with either built-in microphone or optional microphone. I/O for alarm/event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	150	195	85

AXIS M1137-E MK II	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight 5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Camera also supports i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with optional microphone. I/O for alarm/event handling, MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Operation in -25°C to +50°C. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included	255	360	145
AXIS M1137-E MK II i-CS	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight 5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal i-CS lens 3.5-10 mm F1.8 with remote installation zoom and focus. Camera also supports DC-iris lenses. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with optional microphone. I/O for alarm/event handling, MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Operation in -25°C to +50°C. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included	255	360	140
AXIS M2035-LE	Day/night, compact and outdoor-ready bullet style HDTV camera, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 101° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included	112	162	132

AXIS M2035-LE Black	Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 101° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	112	162	132
AXIS M2035-LE 8 MM	Day/night, compact and outdoor-ready bullet style HDTV camera, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed tele lens with 39° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). <u>Midspan not included</u>	112	162	132
AXIS M2035-LE 8 MM BLACK	Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed tele lens with 39° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	112	162	132

AXIS M2036-LE	Day/night, compact and outdoor-ready bullet style 4 MP camera, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included	112	162	132
AXIS M2036-LE Black	Day/night, compact and outdoor-ready bullet style 4 MP camera in black color, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	112	162	132
AXIS P1375	HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0 technology. Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	202	272	92
AXIS P1375-E BAREBONE	AXIS P1375-E Barebone. No lens. Midspan not included	200	535	220

AXIS P1377	5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. PoE class 3 or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included	200	260	100
AXIS P1377 BAREBONE	AXIS P1377 Barebone in single pack. No lens. No power supply.	200	260	100
AXIS P1377-LE	Outdoor, NEMA 4X, IP66/67 and IK10-rated, 5MP resolution, day/night, fixed box camera providing providing Forensic WDR and Lightfinder technology. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (130 feet).Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included	200	540	220
AXIS P1377-LE BAREBONE	AXIS P1377-LE Barebone. No lens. Midspan not included	200	540	220

AXIS P1378-LE	Outdoor, NEMA 4X, IP66/67 and IK10-rated, 4K resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Features a 1/1.8" image sensor. Optimized IR, a power-efficient 850nm IR LED technology covering 50 meters (164 feet). Includes an IR corrected varifocal 3.9-10 mm F1.5 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4K at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included.	200	540	220
AXIS P1378-LE BAREBONE	AXIS P1378-LE Barebone. No lens. Midspan not included	200	540	220
AXIS P1385	1/2.8" image sensor, 2 MP / 1080p resolution, day/night box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. Varifocal IR corrected CS-mount 2.8-13 mm P-iris lens with remote focus. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 2 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Includes black stand for wall and ceiling. Midspan or power supply not included.	220	265	105

AXIS P1385-B	1/2.8" image sensor, 2 MP / 1080p resolution, day/night, box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. Camera supports CS-mount P-Iris, DC-iris and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 2 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Lens and stand are not included but available as optional accessories. Midspan and power supply not included.	220	265	105
AXIS P1385-E	1/2.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact resistant, 2MP / 1080p resolution, day/night box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. Varifocal IR corrected 2.8-13 mm F1.4 P-iris lens and remote focus. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 2 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield, wall bracket and cable glands. Midspan or power supply not included.	205	545	235

AXIS P1385-BE	AXIS P1385-BE 1/2.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact resistant, 2MP / 1080p resolution, day/night box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 2 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield and cable glands. Lens, mounts, illuminator are not included but available as optional accessories. Midspan or power supply not included.	205	545	235
AXIS P1387	1/2.7" image sensor, 5 MP resolution, day/night, box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. Varifocal IR corrected CS-mount 2.8-13 mm P-iris lens with remote focus. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 5 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Includes black stand for wall and ceiling. Midspan or power supply not included.	220	265	105

AXIS P1387-B	1/2.7" image sensor, 5 MP resolution, day/night, box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 5 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Lens and stand are not included but available as optional accessories. Midspan and power supply not included.	220	265	105
AXIS P1387-LE	1/2.7" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact resistant, 5 MP resolution, day/night box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (164 feet). Varifocal IR corrected 2.8-13 mm F1.4 P-iris lens and remote focus. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 5 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield, wall bracket and cable glands. Midspan or power supply not included.	205	545	235

AXIS P1387-BE	1/2.7" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact resistant, 5 MP resolution, day/night box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (164 feet). Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 5 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield and cable glands. Lens, mounts, illuminator are not included but available as optional accessories. Midspan or power supply not included.	205	545	235
AXIS P1388	1/1.8" image sensor, 4K / 8 MP resolution, day/night, box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. Varifocal IR corrected CS-mount 3.9-10 mm P-iris lens with remote focus. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 8 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Includes black stand for wall and ceiling. Midspan or power supply not included.	220	265	105

AXIS P1388-B	1/1.8" image sensor, 4K / 8 MP resolution, day/night, box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 8 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Lens and stand are not included but available as optional accessories. Midspan and power supply not included.	220	265	105
AXIS P1388-LE	1/1.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact resistant, 4K / 8MP resolution, day/night box camera with Deep Learning Processing Unit (DLPU). WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (164 feet). Varifocal IR corrected 3.9-10 mm F1.5 P-iris lens and remote focus. Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield, wall bracket and cable glands. Midspan or power supply not included.	205	545	235

AXIS P1388-BE	1/1.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact resistant, 4K / 8MP resolution, day/night box camera with Deep Learning Processing Unit (DLPU). Forensic WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (164 feet). Camera supports CS-mount P-Iris, DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8 MP stream up to 50/60 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio with speaker pairing, audio detection with either optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield and cable glands. Lens, mounts, illuminator are not included but available as optional accessories. Midspan or power supply not included.	205	545	235
AXIS P1465-LE-3 L.P-Verifier Kit	Please check the supported countries Visit www.axis.com for supported products and application download. Compact outdoor, HDTV / 1080p, day/night, fixed bullet camera with built-in AXIS License Plate Verifier application. Detect and verify vehicles in single lanes with speed up to 70 km/h (45 mph) in 7 to 20 meter distance (23-65 feet). License plate reading time less than 1 second. OptimizedIR, Forensic WDR, Lightfinder, shock detection, IK10, IP66/67, NEMA TS-2-2003 v02.06. Operation temperature -40°C to +60°C (-40°F to 140°F). Integrated bracket for easy mounting on wall and ceiling. License plate verification day and night. Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE) or or 12-28 VDC input. Midspan not included	140	260	160

AXIS P1455-LE	Compact and outdoor-ready HDTV camera for day and night surveillance. NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution fixed bullet camera providing Forensic WDR and Lightfinder 2.0. Varifocal 3-9 mm F1.6 lens with remote 3 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection and active tampering alarm, defogging and corridor format. Audio in and I/O port, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 40 meters (131 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-key, and IP66/67-rated cable glands. Midspan not included.	146	317	142
AXIS P1465-LE 9 mm	Compact outdoor, NEMA 4X, IP66, IP67 and IK10-rated 2MP /1080p resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR. Varifocal 3-9 mm P-iris lens with remote zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 2MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, defogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. AXIS Edge Vault for added cyber security. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Powered by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable weather shield, mounting bracket, Torx L-keys, and IP66/67-rated cable glands. Midspan not included.	260	140	158

AXIS P1465-LE 29 mm	Compact outdoor, NEMA 4X, IP66, IP67 and IK10-rated 2MP /1080p resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR. Varifocal 10.9-29 mm P-iris tele lens with remote zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 2MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Electronic image stabilization, Barrel distortion correction, defogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. AXIS Edge Vault for added cyber security. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Powered by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable weather shield, mounting bracket, Torx L-keys, and IP66/67-rated cable glands. Midspan not included.	260	140	158
AXIS P1467-LE	Compact outdoor, NEMA 4X, IP66, IP67 and IK10-rated 5MP resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR. Varifocal 2.8-8 mm P-iris lens with remote zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 5MP at 25/30. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Barrell distortion correction, defogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. AXIS Edge Vault for added cyber security. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Powered by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-keys, and IP66/67-rated cable glands. Midspan not included.	260	145	160

AXIS P1448-LE	Compact outdoor, 4K Ultra HD (8MP) resolution, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-9.8 mm F1.6 P-iris lens with remote 3.5x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 25 meters (82 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C (-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	145	315	140
AXIS P1468-LE	Compact outdoor, NEMA 4X, IP66, IP67 and IK10-rated 8MP resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR. Varifocal 6-13 mm P-iris lens with remote zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 8MP stream up to 60 fps, 30fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Barrell distortion correction, defogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. AXIS Edge Vault for added cyber security. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Powered by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-keys, and IP66/67-rated cable glands. Midspan not included.	260	145	160

AXIS Q1615-LE Mk III	Outdoor, NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution, day/night, fixed box camera providing OptimizedIR, Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with remote zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Axis Zipstream technology for reduced bandwidth and storage needs. Deep learning processing unit, shock detection, intrusion alarm. Barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start-up in -40°C to 60°C (-40 °F to 140 °F).I includes removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.	300	710	280
AXIS Q1656	1/1.8" sensor, 4 MP, Day/night fixed box camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 3.9-10 mm F1.5 i-CS lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Includes black stand for wall and ceiling. Midspan or power supply not included.	210	270	100

AXIS Q1656-B	1/1.8" sensor, 4 MP, Day/night fixed box camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Lens and stand are not included but available as optional accessories. Midspan and power supply not included.	210	270	100
AXIS Q1656-LE	1/1.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact resistant, 4 MP, Day/night fixed box camera with Deep Learning Processing Unit (DLPU). Built in wiper. Support for Forensic WDR and Lightfinder 2.0. Optimized IR, a power-efficient 850nm IR and White IR LED technology. Includes an IR corrected varifocal 3.9-10 mm F1.5 i-CS lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 (PoE+) or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield, wall bracket, Torx T20 screwdriver and cable glands. Midspan or power supply not included.	200	535	220

AXIS Q1656-BLE	1/1.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact resistant, 4 MP, Day/night fixed box camera with Deep Learning Processing Unit (DLPU). Built in wiper. Support for Forensic WDR and Lightfinder 2.0. Optimized IR, a power-efficient 850nm IR and White LED technology. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 (PoE+) or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield and cable glands. Lens and mounts are not included but available as optional accessories. Midspan or power supply not included.	200	535	220
AXIS Q1656-BE	1/1.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and IK10 impact resistant, 4 MP, Day/night fixed box camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 (PoE+) or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C to +60°C (-40 °F to 140 °F). Includes removable sunshield and cable glands. Lens, mounts, wiper, illuminator are not included but available as optional accessories. Midspan or power supply not included.	200	535	220

AXIS Q1656-DLE	AXIS Q1656-DLE Radar-Video Fusion Camera. Enhanced situational awareness based on the fusion of visual- and radar sensor information in one device. 1/1.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact-resistant, 4 MP, Day/night radar-video fusion camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR and White IR LED technology. Includes an IR corrected varifocal 3.9-10 mm F1.5 i-CS lens with remote zoom and focus. Integrated radar unit, 60.0 GHz-61.5 GHz and 95 degree horizontal field of detection. In addition to radar-video fusion, radar functionality such as built-in analytics including classification of humans and vehicles, is available and enables filtering on distance, customized detection zones, and autotracking for PTZ cameras. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, Radar motion detection, AXIS Speed Monitor, shock detection and active tampering alarm. Axis Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type2 Class 4 (PoE+) or 10-28 V DC power with redundancy. Built-in heater, Arctic Temperature Control for start-up in -40°C	565	210	300
AXIS Q1715 BLOCK CAMERA	HDTV 1080p camera with 21x motorized zoom, day/night, fixed block camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. Built-in varifocal lens, 4-84.6 mm F1.6 with fixed focus and auto focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Micro-HDMI and HD-SDI output. AXIS Edge Vault with FIPS certified TPM for added cyber security. Defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 or IEEE 802.3at Type2 Class 4 (PoE) or 10-28 V DC power with redundancy. Includes black stand for wall and ceiling mount. Midspan or power supply not included.	235	235	100

AXIS Q1700-LE	Robust outdoor, color 2 MP/1080p HDTV license plate camera for sharp license plate images day and night. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p / 2MP resolution at up to 50/60 fps. Varifocal 18–137 mm, 8x optical zoom lens, 16°-2.3° HFOV, F2.9 with remote zoom and installation focus. License plate capture range 20-50 meter at night with built-in OptimizedIR at speeds up to 130 km/h (81 mph) Includes license plate capture assistant for easy setup, pixel counter, shock detection, active tampering alarm, defogging and electronic image stabilization. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. Integrated bracket for easy mounting on wall and ceiling. Dark grey (NCS S5502-B) casing, black fixed metal weather shield with anti-glare coating. NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), RJ45 or IDC punchdown connector, 20-28 V DC or 20-24 V AC. License plate recognition software, power supply or midspan not included.	165	454	235
AXIS Q1798-LE	Robust outdoor, NEMA 4X, IP66/67 and IK10-rated 10 MP/ 4K, day/night, fixed bullet camera providing Forensic WDR and Lightfinder 2.0 technology. Features a 4/3" type image sensor, built-in varifocal 12–48 mm, 4 x optical Canon zoom lens, 90°-21° HFOV, F1.7 with remote zoom and autofocus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4K at 30 fps /10MP resolution at 20 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Includes analytics AXIS Guard Suite, Video motion detection, shock detection and active tampering alarm. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Audio mic/line in, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable sunshield, Torx T20 allen key, IP66/67- rated cable glands and optional IDC punch connector. Power supply or midspan not included.	175	395	240

AXIS Q1800-LE	LPR camera for 3rd party software. Robust, outdoor, NEMA 4X, IP66 and IK10-rated, 2 MP/1080p resolution license plate camera, purpose-tuned for sharp license plate images, day/night, fixed bullet camera. OptimizedIR, a power-efficient 850 nm IR LED technology. Varifocal 7-137 mm, 20x optical zoom lens, 38°–2.3° HFOV with remote zoom and focus. License plate capture range 20-100 meter at speeds up to 250 km/h (155 mph) with optional server based LPR software. Includes Traffic Camera Installation Assistance for easy setup Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 2MP up to 90 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Corridor format, barrel distortion correction, defogging, electronic imaging stabilization and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 10-28 V DC or 20-24 V AC. IP66- rated cable glands and optional IDC punch connectors. 30W PoE out to power an additional device, requires Axis Midspan 60 W, IEEE 802.3bt Type 3 Class 6 Power supply or midspan not included.			
AXIS Q1805-LE	Robust, outdoor, NEMA 4X, IP66, IP67 and IK10-rated, 2 MP/1080p resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR, a power-efficient 850 nm IR LED technology. Varifocal 4.3-137 mm, 32x optical zoom lens, 60°–2.3° HFOV with remote zoom and autofocus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 2MP up to 90 fps, 25/30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Corridor format, barrel distortion correction, defogging, electronic imaging stabilization and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 10-28 V DC or 20-24 V AC. Includes a removable sunshield, IP66/67- rated cable glands and optional IDC punch connectors. 30W PoE out to power an additional device, requires Axis Midspan 60 W, IEEE 802.3bt Type 3 Class 6 Power supply or midspan not included.	200	395	210

AXIS Q1806-LE	1/1.8" image sensor, robust, outdoor, NEMA 4X, IP66, IP67 and IK10-rated, 4 MP resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR, a power-efficient 850 nm IR LED technology. Varifocal 4.3-137 mm, 32x optical zoom lens, 60°–2.3° HFOV with remote zoom and autofocus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 4MP up to 90 fps, 25/30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Corridor format, barrel distortion correction, defogging, optical imaging stabilization and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 10-28 V DC or 20-24 V AC. Includes a removable sunshield, IP66/67- rated cable glands and optional IDC punch connectors. 30W PoE out to power an additional device, requires Axis Midspan 60 W, IEEE 802.3bt Type 3 Class 6 Power supply or midspan not included	200	395	210
AXIS Q1808-LE	4/3" image sensor, robust outdoor, NEMA 4X, IP66, IP67 and IK10-rated 10 MP/ 4K resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support Forensic WDR and Lightfinder 2.0 and OptimizedIR, a power-efficient 850 nm IR LED and White LED technology. Varifocal 12–48 mm, 4 x optical Canon zoom lens, 90°-21° HFOV with remote zoom and autofocus. Multiple, individually configurable H.264, H.265 with Zipstream and Motion JPEG. 4K up to 60 fps and 10MP at 30 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Corridor format, barrel distortion correction, defogging, electronic imaging stabilization and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable sunshield, , IP66, IP67- rated cable glands and optional IDC punch connectors. 30W PoE out to power an additional device, requires Axis Midspan 60 W, IEEE 802.3bt Type 3 Class 6 Power supply or midspan not included	200	400	220

AXIS Q1808-LE 150MM	4/3" image sensor, robust outdoor, NEMA 4X, IP66, IP67 and IK10-rated 10 MP/ 4K resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support Forensic WDR and Lightfinder 2.0 and OptimizedIR, a power-efficient 850 nm technology. Varifocal 50–150 mm, 3 x optical Canon zoom lens, 21°-7° HFOV with remote zoom and autofocus. Multiple, individually configurable H.264, H.265 with Zipstream and Motion JPEG. 4K up to 60 fps and 10MP at 30 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Corridor format, barrel distortion correction, defogging, electronic imaging stabilization and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable sunshield, , IP66, IP67- rated cable glands and optional IDC punch connectors. 30W PoE out to power an additional device, requires Axis Midspan 60 W, IEEE 802.3bt Type 3 Class 6 Power supply or midspan not included	200	400	220
AXIS Q1809-LE 150 mm	4/3" image sensor, robust outdoor, NEMA 4X, IP66, IP67 and IK10-rated 41 MP/ 8K resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support WDR, Lightfinder 2.0 and OptimizedIR, a power-efficient 850 nm technology. Varifocal 50–150 mm, 3 x optical Canon zoom lens, 21°-7° HFOV with remote zoom and autofocus. Multiple, individually configurable H.264, H.265 with Zipstream and Motion JPEG. 8K up to 30 fps and 41MP at 15 fps. Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS 140-3 Level 3 for added cyber security. Defogging, electronic imaging stabilization and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +55°C (-40 °F to 131 °F). Powered by PoE class 4/6 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable sunshield, , IP66, IP67- rated cable glands and optional IDC punch connectors. 30W PoE out to power an additional device, requires 60 W midspan, IEEE 802.3bt Type 3 Class 6 Power supply or midspan not included	395	200	210
AXIS FA1105 SENSOR UNIT	AXIS FA1105 is a discreet indoor sensor unit with 111° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a small hole visible for the lens. AXIS FA1105 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	165	170	70

AXIS FA1125 SENSOR UNIT	AXIS FA1125 is an extremely discreet indoor, pin hole lens, Sensor Unit with a 91° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a pinhole visible for the lens. AXIS FA1125 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	165	160	70
AXIS FA3105-L EYEBALL SENSOR UNIT	AXIS FA3105-L is a compact eyeball sensor unit with built in IR illumination (15 m / 49 ft range of reach) for use with AXIS FA Main Unit. It has 103° horizontal field of view and 1080p HDTV resolution with Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to the main unit.	165	190	75
AXIS FA4115 SENSOR UNIT	AXIS FA4115 is a compact varifocal dome sensor unit with 53° to 99° horizontal field of view for use with an AXIS FA Main Unit. AXIS FA4115 provides a 1080p resolution a Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8-m (26 ft.) cable for connection to a main unit.	165	200	60
AXIS FA51 MAIN UNIT	AXIS FA51 is a single-channel modular camera Main Unit. It is equipped with HDMI out for connection to a public view monitor or a surveillance monitor, I/O ports and a SD card slot. It features Axis Forensic WDR (wide dynamic range) for clarity when there are both dark and light areas in the scene and Axis Zipstream for lowered bandwidth and storage requirements, without compromising image quality. It is compatible with all Sensor Units in the FA Series including IR and thermal units. The AXIS Face Detector application for loss prevention comes pre-loaded.	85	185	40
AXIS FA51 MAIN UNIT 10PCS	AXIS FA51 is a single-channel modular camera Main Unit in bulk 10-pack. It is equipped with HDMI out for connection to a public view monitor or a surveillance monitor, I/O ports and a SD card slot. It features Axis Forensic WDR (wide dynamic range) for clarity when there are both dark and light areas in the scene and Axis Zipstream for lowered bandwidth and storage requirements, without compromising image quality. It is compatible with all Sensor Units in the FA Series including IR and thermal units. The AXIS Face Detector application for loss prevention comes pre-loaded.	175	175	295

AXIS FA51-B MAIN UNIT 10PCS	AXIS FA51-B is a single-channel barebone modular camera Main Unit in bulk 10-pack. The PCBAs are individually packed in ESD bags inside the bulk box. They are UR-certified and designed for integration into machines, devices and enclosures. The product is equipped with HDMI out for connection to a public view monitor or a surveillance monitor, I/O ports and a SD card slot. It features Axis Forensic WDR (wide dynamic range) for clarity when there are both dark and light areas in the scene and Axis Zipstream for lowered bandwidth and storage requirements, without compromising image quality. It is compatible with all Sensor Units in the FA Series including IR and thermal units. The AXIS Face Detector application for loss prevention comes pre-loaded. Important notice: This product must be integrated into a final product or solution and is not intended for stand-alone use. Consequently, this product must be properly integrated into a suitable casing before it is made available to the end user. The entity or person who integrates this product into a final product or solution is also responsible for ensuring that the final product fulfills safety, EMC and other regulatory standards required by law and that the final product is certified accordingly.	197	255	60
AXIS FA54 MAIN UNIT	AXIS FA54 is a modular camera Main Unit and can stream full frame rate HDTV 1080p videos from four sensor units simultaneously using one IP address. It has an HDMI port for connection to a surveillance or public view monitor, Forensic WDR (wide dynamic range) that is optimized for low light and motion, Axis Zipstream, two microphone inputs and one audio out, I/O port and two micro SD card slots for local storage.	125	250	150
AXIS P8815-2 3D Ppl Counter BK	AXIS P8815-2 3D People Counter is a custom-designed stereo camera designed for people counting. The people counter functionality is included; no need to purchase and install a separately licensed product. Main features include: Accurate and reliable 3D people counting. All-in-one solution with reliable hardware. Optimized for challenging conditions. Flexible counting zones. Easy integration in AXIS Store Reporter or 3rd party reporting system. This version comes with a black casing.	188	83	45
AXIS P8815-2 3D Ppl Counter WH	AXIS P8815-2 3D People Counter is a custom-designed stereo camera designed for people counting. The people counter functionality is included; no need to purchase and install a separately licensed product. Main features include: Accurate and reliable 3D people counting. All-in-one solution with reliable hardware. Optimized for challenging conditions. Flexible counting zones. Easy integration in AXIS Store Reporter or 3rd party reporting system. This version comes with a white casing.	188	83	45

AXIS F9114 MAIN UNIT	AXIS F9114 is a 4-channel main unit part of the 2nd generation F-series. Up to 4x F21, F7225-RE or F4105-LRE video sensors can be connected to it. It also has 2 Audio IN, 1 Audio Out, 4x configuration I/O, 1 RS 232/485, 1x 10-48V DC. It has an Ethernet port and PoE Class 4. Max 25,5W AXIS TU6009 Connector 6-pin (for the I/O port), AXIS TU6008 Connector 5-pin (for RS port) and AXIS TU6001 Connector 3-in (for DC power) have to be purchased separately. AXIS F9114 main unit is NOT compatible with the 1st generation of F-series sensors (F1005-E, F1015-E, F1025-E, F1025 F4005, F4005-E).	165	175	80
AXIS F9114-B MAIN UNIT	AXIS F9114-B is a 4-channel Barebone main unit part of the 2nd generation F-series. AXIS F9114-B has no casing. It is UL recognised and meant to be integrated into a something else (ex: machine...). The final product has to be UL certified. Up to 4x F21, F7225-RE or F4105-LRE video sensors can be connected to it. It also has 2 Audio IN, 1 Audio Out, 4x configuration I/O, 1 RS 232/485, 1x 10-48V DC. It has an Ethernet port and PoE Class 4. Max 25,5W. AXIS TU6009 Connector 6-pin (for the I/O port), AXIS TU6008 Connector 5-pin (for RS port) and AXIS TU6001 Connector 3-in (for DC power) have to be purchased separately. AXIS F9114-B main unit is NOT compatible with the 1st generation of F-series sensors (F1005-E, F1015-E, F1025-E, F1025 F4005, F4005-E).	144	180	70
AXIS F9104-B MAIN UNIT	AXIS F9104-B is a 4-channel Barebone main unit part of the 2nd generation F-series. AXIS F9104-B has no casing. It is UL recognised and is meant to be integrated into a something else (ex: machine...). The final product has to be UL certified. Up to 4x F21, F7225-RE or F4105-LRE video sensors can be connected to it. it has a 10-48V DC and an Ethernet port. AXIS F9104-B is PoE Class 4. Max 25,5W. AXIS TU6001 Connector 3-in (for DC power) has to be purchased separately. AXIS F9104-B main unit is NOT compatible with the 1st generation of F-series sensors (F1005-E, F1015-E, F1025-E, F1025 F4005, F4005-E).	110	110	80

AXIS F9111 MAIN UNIT	AXIS F9111 is a one channel main unit part of the 2nd generation F-series. One F21, F7225-RE or F4105-LRE video sensor can be connected to it. It also has 2 Audio IN, 1 Audio Out, 4x configuration I/O, 1 RS 232/485, 1x 10-48V DC. It has an Ethernet port and PoE Class 4. Max 25,5W. AXIS TU6009 Connector 6-pin (for the I/O port), AXIS TU6008 Connector 5-pin (for RS port) and AXIS TU6001 Connector 3-in (for DC power) have to be purchased separately. AXIS F9111 main unit is NOT compatible with the 1st generation of F-series sensors (F1005-E, F1015-E, F1025-E, F1025-F, F4005, F4005-E).	165	175	80
AXIS F2115-R Varifocal Sensor	AXIS F2115-R is a 1080p Varifocal sensor part for the 2nd generation F-series. The focus as well as the focal length has to be manually adjusted on the lens. The Horizontal Field of View varies from 107° to 56°. The focal length varies from 3.2mm to 5.7mm. AXIS F2115-R is a rugged indoor sensor. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2115-R Varifocal sensor. An AXIS TU600X cable has to be purchased separately. There is no mounting accessory included with AXIS F2115-R Varifocal sensor. Mounting accessories can be purchased separately. AXIS F2115-R Varifocal sensor is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44).	80	121	40
AXIS F2135-RE Fisheye Sensor	AXIS F2135-RE is a 1080p Fisheye sensor part of the 2nd generation F-series. It has 185° Horizontal Field of View and 1.98mm focal length. AXIS F2135-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2135-RE fisheye sensor. An AXIS TU600X cable has to be purchased separately. There is no mounting accessory included with AXIS F2135-RE fisheye sensor. Mounting accessories can be purchased separately. AXIS F2135-RE fisheye sensor is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44).		121	40

AXIS F2105-RE Standard Sensor	AXIS F2105-RE is a 1080p Standard sensor part for the F-series. It has 108° Horizontal Field of View and 3.1mm focal length. AXIS F2105-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2105-RE standard sensor. An AXIS TU600X cable has to be purchased separately. There is no mounting accessory included in AXIS F2105-RE standard sensor. Mounting accessories can be purchased separately. AXIS F2105-RE is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44)	80	120	40
AXIS F2105-RE Standard Sensor 8P	AXIS F2105-RE Standard Bulk 8P is a bulk pack of 8x 1080p Standard sensor part for the F-series. It has 180° Horizontal Field of View and 3.1mm focal length. AXIS F2105-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2105-RE standard bulk 8p. AXIS TU600X cables have to be purchased separately. There is no mounting bracket included with AXIS F2105-RE bulk 8 p. Mounting accessories can be purchased separately. AXIS F2105-RE standard sensor is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44)	140	190	50
AXIS F2115-R Varifocal Sensor 8P	AXIS F2115-R Varifocal Bulk 8P is bulk pack of 8x 1080p Varifocal sensor part for the F-series. The focus as well as the focal length has to be manually adjusted on the lens. The Horizontal Field of View varies from 107° to 56°. The focal length varies from 3.2mm to 5.7mm. AXIS F2115-R is a rugged indoor sensor. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2115-R standard Bulk 8p. AXIS TU600X cables have to be purchased separately. There is no cable included with AXIS F2115-R standard Bulk 8P. Mounting accessories can be purchased separately. AXIS F2115-R is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44)	140	190	50

AXIS F2135-RE Fisheye Sensor 8P	AXIS F2135-RE Fisheye Bulk 8P is a bulk pack of 8x 1080p Fisheye sensor part for the F-series. It has 185° Horizontal Field of View and 1.98mm focal length. AXIS F2135-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2135-RE fisheye bulk 8p. AXIS TU600X cables have to be purchased separately. There is no mounting accessory included with AXIS F2135-RE. Mounting accessories can be purchased separately. AXIS F2135-R is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44).	140	190	50
AXIS F7225-RE Pinhole Sensor	AXIS F7225-RE is a 1080p Angled pinhole sensor part for the F-series. It has 92° Horizontal Field of View and 3.7mm focal length. AXIS F7225-RE is a rugged outdoor angled pinhole sensor. It is IP66 certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). AXIS F7225-RE does not come with a cable. An AXIS TU600X cable has to be purchased separately. AXIS F7225-RE comes with 1x AXIS F8202 Straight Mounting bracket	80	120	33
AXIS F7225-RE Pinhole Sensor 8P	AXIS F7225-RE pinhole bulk 8p is bulk pack of 8x 1080p angled pinhole sensor part for the F-series. AXIS F7225-RE has 92° Horizontal Field of View and 3.7mm focal length. AXIS F7225-RE is a rugged outdoor sensor. It is both IP66 certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). AXIS F7225-RE standard bulk 8P does not come with any cables. AXIS TU600X cables have to be purchased separately. AXIS F7225-RE standard bulk 8P comes with 8x AXIS F8202 Straight Mounting brackets.	160	240	78
AXIS F4105-LRE Dome Sensor	AXIS F4105-LRE is a 1080p mini-dome sensor with IR light part for the F-series. It has 110° Horizontal Field of View and 2.8mm focal length. AXIS F4105-LRE uses detachable M12 lenses. Several M12 lenses can be purchased separately offering different types of Horizontal Field of View and Focal Length. AXIS F4105-LRE is a rugged outdoor mini-dome sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). AXIS F4105-LRE does not come with a cable. An AXIS TU600X cable has to be purchased separately. AXIS F4105-LRE does not come with any mounting accessory. Mounting accessories can be purchased separately.	115	130	73

AXIS F4105-LRE Dome Sensor 8P	AXIS F4105-LRE bulk 8p is bulk pack of 8x 1080p mini-dome sensors with IR part for the F-series. AXIS F4105-LRE-RE has 110° Horizontal Field of View and 2.8 mm focal length. AXIS F4105-LRE uses detachable M12 lenses. Several M12 lenses can be purchased separately offering different types of Horizontal Field of View and Focal Length. AXIS F4105-LRE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). AXIS F4105-LRE standard bulk 8P do not come with any cables. AXIS TU600X cables have to be purchased separately. AXIS F4105-LRE standard bulk 8P do not come with any mounting accessories. Mounting accessories can be purchased separately.	285	395	205
AXIS P1245 Mk II Modular Standard Camera	AXIS P1245 Mk II is a Modular Standard Camera with Deep Learning capabilities. It has on a small-sized main unit and AXIS FA1105 Sensor Unit. The camera provides HDTV 1080p resolution, 111° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264, H265 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance. <u>It comes with metal nuts for the intallation</u>	166	166	70
AXIS P1265 Mk II Modular Pinhole Camera	AXIS P1265 Mk II is a Modular Pinhole Camera with Deep Learning capabilities. It has on a small-sized main unit and an AXIS FA1125 Pinhole Sensor Unit which are designed for extremely discreet indoor installations. The camera provides HDTV 1080p resolution, 91° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264, H265 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector with a detachable cable (8 m/26 ft.) for easy installation and maintenance. <u>It comes with metal nuts for the installation</u>	166	166	70

AXIS P1245 Mk II Modular Standard Camera 10 pcs	This is a bulk pack of 10x P1245 Mk II cameras. AXIS P1245 Mk II Camera with Deep Learning capabilities. It has on a small-sized main unit and AXIS FA1105 Sensor Unit. The camera provides HDTV 1080p resolution, 111° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264, H265 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance. it comes with metal nuts for the installation.	180	265	225
AXIS P1265 Mk II Modular Pinhole Camera 10 pcs	This is a bulk pack of 10x P1265 Mk II pinhole cameras. AXIS P1265 Mk II is a modular pinhole camera with Deep Learning modular capabilities. It has on a small-sized main unit and an AXIS FA1125 Pinhole Sensor Unit which are designed for extremely discreet indoor installations. The camera provides HDTV 1080p resolution, 91° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264, H265 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector with a detachable cable (8 m/26 ft.) for easy installation and maintenance. It comes with metal nuts for the installation.	180	265	225
AXIS P1275 Mk II Modular Varifocal Dome Camera	AXIS P1275 Mk II is Modular Varifocal Dome Camera with Deep Learning capabilities. It has a small-sized main unit and an AXIS FA4115 Dome Sensor Unit with a varifocal lens that enables easy mounting on walls or ceilings. It can be manually directed with pan, tilt and rotate movements. The camera provides HDTV 1080p resolution, 53-99° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264, H265 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance.	196	166	64

AXIS Q1686-DLE	AXIS Q1686-DLE Radar-Video Fusion Camera. Speed and license plate pairing camera by utilizing fusion of visual- and radar sensor information in one device and on edge. Powerful device for wrong way applications and directional alerts by radar technology. 1/1.8" image sensor, outdoor, NEMA 4X, IP66, IP67 and impact-resistant, 4 MP, Day/night radar-video fusion camera with Deep Learning Processing Unit (DLPU). Image optimization for license plate capture profile, traffic capture profile and Lightfinder 2.0. Optimized IR, a purpose built and powerful 850nm IR-illuminator kit. Includes an varifocal 9-50 mm F1.5 i-CS lens with remote zoom and focus. Integrated radar unit, 60.0 GHz-61.5 GHz and 95 degree horizontal field of detection. In addition to radar-video fusion, radar functionality such as built-in analytics including classification of vehicles, is available and enables filtering on distance, customized detection zones, and multiple line crossing Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. Radar motion detection, AXIS Speed Monitor, shock detection and active tampering alarm. Axis Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization, electronic radar stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port	215	565	300
AXIS F2137-RE FISHEYE SENSOR	AXIS F2137-RE is a 5Mp Fisheye sensor. It has 185° Horizontal Field of View and 1.98mm focal length. AXIS F2137-RE is a rugged outdoor sensor unit. It is both IP66 and IP6K9K certified. AXIS F2137-RE is compatible with all AXIS F91 main units. All the accessories available for AXIS F2135-RE are also compatible with AXIS F2137-RE. No cable is included with AXIS F2137-RE fisheye sensor. AXIS TU600X cables shall be purchased separately. No mounting accessory is included with AXIS F2137-RE fisheye sensor. Mounting accessories shall be purchased separately.	80	122	40

AXIS F2137-RE FISHEYE SENSOR 8P	AXIS F2137-RE Fisheye sensor 8P is bulk pack of 8x 5Mp Fisheye sensor. AXIS F2137-RE has 185° Horizontal Field of View and 1.98mm focal length. AXIS F2137-RE is a rugged outdoor sensor unit. It is both IP66 and IP6K9K certified. AXIS F2137-RE is compatible with all AXIS F91 main units. All the accessories available for AXIS F2135-RE are also compatible with AXIS F2137-RE. No cable is included with AXIS F2137-RE fisheye sensor. AXIS TU600X cables shall be purchased separately. No mounting accessory is included with AXIS F2137-RE fisheye sensor. Mounting accessories shall be purchased separately.	110	200	90
AXIS F2107-RE STANDARD SENSOR	AXIS F2107-RE is a 5Mp Standard sensor. It has 110° Horizontal Field of View and 2.8mm focal length. AXIS F2107-RE is a rugged outdoor sensor unit. It is both IP66 and IP6K9K certified. AXIS F2107-RE is compatible with all AXIS F91 main units. All the accessories available for AXIS F2105-RE are also compatible with AXIS F2107-RE. No cable is included with AXIS F2107-RE fisheye sensor. AXIS TU600X cables shall be purchased separately. No mounting accessory is included with AXIS F2107-RE fisheye sensor. Mounting accessories shall be purchased separately.	80	122	40
AXIS F2107-RE STANDARD SENSOR 8P	AXIS F2107-RE Standard sensor 8P is a bulk pack of 8x 5Mp Standard sensor. AXIS F2137-RE has a 110° Horizontal Field of View and 2.8mm focal length. AXIS F2107-RE is a rugged outdoor sensor unit. It is both IP66 and IP6K9K certified. AXIS F2107-RE is compatible with all AXIS F91 main units. All the accessories available for AXIS F2105-RE are also compatible with AXIS F2107-RE. No cable is included with AXIS F2107-RE fisheye sensor. AXIS TU600X cables shall be purchased separately. No mounting accessory is included with AXIS F2107-RE fisheye sensor. Mounting accessories shall be purchased separately.	110	200	90

AXIS Q1800-LE-3 L.P.Verifier Kit	Please check the supported countries at www.axis.com. AXIS License Plate Verifier preinstalled, Robust, outdoor, NEMA 4X, IP66 and IK10-rated, 2 MP/1080p resolution license plate camera, purpose-tuned for sharp license plate images, day/night, fixed bullet camera. OptimizedIR, a power-efficient 850 nm IR LED technology. Varifocal 7-137 mm, 20x optical zoom lens, 38°–2.3° HFOV with remote zoom and focus. License plate capture range 20-100 meter at speeds up to 200 km/h (124 mph) with built-in AXIS License Plate Verifier application. Includes Traffic Camera Installation Assistance for easy setup. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 2MP up to 90 fps. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Corridor format, barrel distortion correction, defogging, electronic imaging stabilization and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 10-28 V DC or 20-24 V AC. IP66- rated cable glands and optional IDC punch connectors. 30W PoE out to			
AXIS M3046-V 2.4mm	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max 4 MP at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. <u>Midspan not included.</u>	135	115	75
AXIS M3047-P	Ultra-compact, indoor fixed mini dome with 6 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 30 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet. <u>Midspan not included.</u>	115	125	75

AXIS M3085-V	AXIS M3085-V is an ultra-compact, indoor fixed mini dome with Deep Learning Processing Unit (DLPU). Dust - and IK08 vandal-resistant casing, fixed lens, horizontal/vertical field of view 102°/55°. D/N functionality with automatically removable IR-cut filter. Lightfinder. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 2MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Audio and I/O with optional accessories. MicroSD memory card slot for local storage. Axis Object Analytics, video motion detection and active tampering alarm. Axis Edge Vault for increased cybersecurity. Powered by IEEE 802.3af/802.3at Type 1 Class 2	120	110	90
AXIS M3086-V	AXIS M3086-V is an ultra-compact, indoor fixed mini dome with Deep Learning Processing Unit (DLPU). Dust - and IK08 vandal-resistant casing, fixed lens, horizontal/vertical field of view 130°/93°. D/N functionality with automatically removable IR-cut filter. Lightfinder. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. MicroSD memory card slot for local storage. Audio and I/O with optional accessories. Axis Object Analytics, video motion detection and active tampering alarm. Axis Edge Vault for increased cybersecurity Powered by IEEE 802.3af/802.3at Type 1 Class 2	120	110	90
AXIS M3086-V Mic	AXIS M3086-V is an ultra-compact, indoor fixed mini dome with with advanced video and audio analytics. Built-in microphone for audio analytics and streaming. Dust - and IK08 vandal-resistant casing, fixed lens, horizontal/vertical field of view 130°/93°. D/N functionality with automatically removable IR-cut filter. Lightfinder. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. MicroSD memory card slot for local storage. Two-way audio and I/O with optional accessories. Axis Object Analytics, Axis Audio Analytics, video motion detection and active tampering alarm. Axis Edge Vault for increased cybersecurity Powered by IEEE 802.3af/802.3at Type 1 Class 2	110	120	90
AXIS M3088-V	AXIS M3088-V is an ultra-compact, indoor fixed mini dome with Deep Learning Processing Unit (DLPU). Dust - and IK08 vandal-resistant casing, fixed lens, horizontal/vertical field of view 109°/56°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 8MP at 15 fps with WDR. Zipstream for reduced bandwidth and storage. MicroSD memory card slot for local storage. Audio and I/O with optional accessories. Axis Object Analytics, video motion detection and active tampering alarm. AXIS Edge Vault for increased cybersecurity. Powered by IEEE 802.3af/802.3at Type 1 Class 2	120	110	90

AXIS M3026-VE	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed, 106° lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps or 3 MP resolution at 20 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	150	195	130
AXIS M3077-PLVE	With its 6 MP sensor, AXIS M3077-PLVE offers excellent image quality and a complete 180° or 360° overview, indoors or out, around the clock. It features two built-in microphones allowing for audio surveillance and detection. This compact mini dome offers dewarped views such as panorama, quad, corner, and corridor views directly from the camera. It includes Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging light or near darkness. And, Axis OptimizedIR for surveillance in pitch darkness. Furthermore, enhanced security functionality prevents unauthorized access and safeguards your system.	160	160	90
AXIS M3104-LVE	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	120	140	120
AXIS M3105-L	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	120	140	120
AXIS M3115-LVE	AXIS M3115-LVE is a compact mini dome in a flat-faced, outdoor-ready, IK08 impact-resistant design with built-in IR illumination. Fixed lens, 105° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 1080p at up to 30 fps with Forensic WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet.	124	110	118

AXIS M3125-LVE White	AXIS M3125-LVE is a compact, turret style outdoor-ready dome camera. IP66 and IK08 impact-resistant design with built-in IR illumination. Fixed lens, 110° horizontal field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 2MP at up to 30 fps with WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced AI-based analytics. Axis Object Analytics, video motion detection and active tampering alarm. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault with FIPS 140-3 level 3 for increased <u>cyber security. White color.</u>	123	112	114
AXIS M3125-LVE Black	AXIS M3125-LVE is a compact, turret style outdoor-ready dome camera. IP66 and IK08 impact-resistant design with built-in IR illumination. Fixed lens, 110° horizontal field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 2MP at up to 30 fps with WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced AI-based analytics. Axis Object Analytics, video motion detection and active tampering alarm. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault with FIPS 140-3 level 3 for increased <u>cyber security. Black color.</u>	123	112	114
AXIS M3116-LVE	AXIS M3116-LVE is a compact mini dome in a flat-faced, outdoor-ready, IK08 impact-resistant design with built-in IR illumination. Fixed lens, 130° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4 MP at up to 30 fps with Forensic WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video <u>storage. Power over Ethernet.</u>	124	110	118
AXIS M3126-LVE White	AXIS M3126-LVE is a compact, turret style outdoor-ready dome camera. IP66 and IK08 impact-resistant design with built-in IR illumination. Fixed lens, 130° horizontal field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4MP at up to 30 fps with WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced AI-based analytics. Axis Object Analytics, video motion detection and active tampering alarm. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault with FIPS 140-3 level 3 for increased <u>cyber security. White color.</u>	123	112	114

AXIS M3126-LVE Black	AXIS M3126-LVE is a compact, turret style outdoor-ready dome camera. IP66 and IK08 impact-resistant design with built-in IR illumination. Fixed lens, 130° horizontal field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4MP at up to 30 fps with WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced AI-based analytics. Axis Object Analytics, video motion detection and active tampering alarm. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault with FIPS 140-3 level 3 for increased cyber security. Black color.	123	112	114
AXIS M3128-LVE White	AXIS M3128-LVE is a compact, turret style outdoor-ready dome camera. IP66 and IK08 impact-resistant design with built-in IR illumination. Fixed lens, 110° horizontal field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 8MP at up to 15 fps with WDR. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced AI-based analytics. Axis Object Analytics, video motion detection and active tampering alarm. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault with FIPS 140-3 level 3 for increased cyber security. White color.	123	112	114
AXIS M3128-LVE Black	AXIS M3128-LVE is a compact, turret style outdoor-ready dome camera. IP66 and IK08 impact-resistant design with built-in IR illumination. Fixed lens, 110° horizontal field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 8MP at up to 15 fps with WDR. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced AI-based analytics. Axis Object Analytics, video motion detection and active tampering alarm. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault with FIPS 140-3 level 3 for increased cyber security. Black color.	123	112	114
AXIS M3215-LVE	Fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Fixed lens, 101°/ 55° horizontal/vertical field of view . Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. Max 2MP at 30 fps with WDR up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket and weather shield	210	200	145

AXIS M3216-LVE	Fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Fixed lens, 102°/ 73° horizontal/vertical field of view . Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. Max 4MP at 30 fps with WDR up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket and weather shield	210	200	145
AXIS M4215-V	Compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting. 3.6-6.6 mm with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 2MP for wide 16:9 view with up to 30 fps. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault for increased Cyber Security	125	135	90
AXIS M4215-LV	Compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting. 3.6-6.6 mm with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 2MP for wide 16:9 view with up to 30 fps. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault for increased Cyber Security	125	135	90
AXIS M4216-V	Compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4MP in 4:3, 3MP in 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output (micro). MicroSD memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security	135	125	80

AXIS M4216-LV	Compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4MP in 4:3, 3MP in 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output (micro). MicroSD memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security	135	125	80
AXIS M4218-V	Compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting. 3.6-6.6 mm with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 8MP for wide 16:9 view with up to 15 fps. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault for increased Cyber Security	125	135	90
AXIS M4218-LV	Compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting. 3.6-6.6 mm with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 8MP for wide 16:9 view with up to 15 fps. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault for increased Cyber Security	125	135	90
AXIS M4308-PLE	AXIS M4308-PLE is a discreet, outdoor-ready mini dome designed to blend seamlessly into any environment. With 12 MP sensor and stereographic lens it offers outstanding images and complete 360° panoramic overview. Thanks to Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. AXIS Object Analytics is included and a deep learning processing unit (DPLU) enables unique opportunities to take advantage of analytics based on deep learning on the edge. It includes Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging light or near darkness. Plus, Axis OptimizedIR for surveillance in pitch darkness. Four built-in microphones and Voice Enhancer offers audio capture with great noise suppression.	160	160	90

AXIS M4317-PLVE	AXIS M4317-PLVE is a discreet, IK10 and IP66 outdoor-ready mini dome designed with 6 MP sensor and stereographic lens, that can deliver multiple 360° or 180° panoramic views at up to 30 fps with no blind spots. Thanks to Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. AXIS M4317-PLVE comes with build-in configurable IR, making it perfect for low light situations. Signed firmware and secure boot ensure firmware authenticity. Power over Ethernet	165	175	95
AXIS M4318-PLVE	AXIS M4318-PLVE is a discreet, IK10 and IP66 outdoor-ready mini dome designed with 12 MP sensor and stereographic lens, that can deliver 360° or 180° panoramic views at up to 30 fps with no blind spots. Thanks to Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. AXIS M4318-PLVE comes with build-in configurable IR, making it perfect for low light situations. Signed firmware and secure boot ensure firmware authenticity. Power over Ethernet	165	175	95
AXIS M4327-P	AXIS M4327-P is an ultra-compact, indoor fixed mini dome with 6 MP sensor and stereographic lens, that can deliver multiple 360° or 180° panoramic views at up to 30 fps with no blind spots. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. AXIS M4327-P is delivered factory-focused and features digital roll functionality for easy installation. Signed firmware and secure boot ensure firmware authenticity. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet	110	125	95

AXIS M4328-P	AXIS M4328-P is an ultra-compact, indoor fixed mini dome with 12 MP sensor and stereographic lens, that can deliver 360° or 180° panoramic views at up to 30 fps with no blind spots. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. AXIS M4328-P is delivered factory-focused and features digital roll functionality for easy installation. Signed firmware and secure boot ensure firmware authenticity. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet.	110	125	95
AXIS P3245-LV	Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	175	161	132
AXIS P3245-LVE 22 MM	Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes	200	265	135

AXIS P3247-LV	AXIS P3247-LV is a day/night fixed dome with discreet, dust- and IK10 vandal-resistant indoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 3-8mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 5 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	175	161	132
AXIS P3247-LVE	AXIS P3247-LVE is a day/night fixed dome with IK10 vandal-resistant outdoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 3-8 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 5 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	270	200	135
AXIS P3248-LV	AXIS P3248-LV is a day/night fixed dome with discreet, dust- and IK10 vandal-resistant indoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes.	175	161	132

AXIS P3265-V	High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 2. Includes mounting bracket	160	160	130
AXIS P3265-LV	High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket	160	160	130
AXIS P3265-LVE	High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield	200	270	140

AXIS P3245-V	Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	175	161	132
AXIS P3265-LVE 22 mm	High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield.	200	210	150
AXIS P3267-LV	High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 5MP stream in 4:3 up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket.	145	162	162

AXIS P3267-LVE	High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 5MP stream in 4:3 up to 30fps.. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield	200	210	150
AXIS P3267-LVE Mic	High-performance fixed dome camera with advanced video and audio analytics. Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Built-in microphone for audio analytics and streaming. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 5MP stream in 4:3 up to 30fps. AXIS Object Analytics, AXIS Audio Analytics, Video motion detection and tampering alarm. Two-way audio. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield	210	200	140
AXIS P3245-VE	Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes	265	200	135

AXIS P3268-LV	High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP 4K stream in 16:9 up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket.	145	163	164
AXIS P3245-LVE	Fixed dome with support for Forensic WDR, Lightfinder 2.0 and Optimized IR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	265	200	135
AXIS P3268-LVE	High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP 4K stream in 16:9 up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield.	200	210	150

AXIS P4705-PLVE Panoramic Camera	AXIS P4705-PLVE offers two channels with 2MP per channel, at a frame rate of up to 60 fps. With its unique design, this multidirectional camera offers cost-effective installation and flexible positioning of both varifocal camera heads. Each head can be controlled individually, so you can capture scenes in two directions in wide angle or zoomed-in views, with up to 2.5x zoom. It features Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging or poor light. The camera comes with a Deep Learning Processing Unit and can run analytics on both channels simultaneously. Furthermore, Zipstream with support for H.264 and H.265 significantly lowers bandwidth and storage requirements.	190	240	120
AXIS P4707-PLVE Panoramic Camera	AXIS P4707-PLVE offers two channels with 5MP per channel, at a frame rate of 30 fps. With its unique design, this multidirectional camera offers cost-effective installation and flexible positioning of both varifocal camera heads. Each head can be controlled individually, so you can capture scenes in two directions in wide angle or zoomed-in views, with up to 2.5x zoom. It features Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging or poor light. The camera comes with a Deep Learning Processing Unit and can run analytics on both channels simultaneously. Furthermore, Zipstream with support for H.264 and H.265 significantly lowers bandwidth and storage requirements.	180	230	110
AXIS P4708-PLVE Panoramic Camera	AXIS P4708-PLVE offers two channels with 8MP (4K) per channel, at a frame rate of 25/30 fps. With its unique design, this multidirectional camera offers cost-effective installation and flexible positioning of both varifocal camera heads. Each head can be controlled individually, so you can capture scenes in two directions in wide angle or zoomed-in views, with up to 2.5x zoom. It features Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging or poor light. The AI powered camera comes with a Deep Learning Processing Unit and can run multiple analytics on both channels simultaneously. Furthermore, Zipstream with support for H.264 and H.265 significantly lowers bandwidth and storage requirements.	190	240	120
AXIS P3735-PLE	AXIS P3735-PLE Panoramic Camera offers 4x2 MP sensors and is perfect for 360° and 270° coverage. You'll be able to count on both high-quality overviews and detailed coverage thanks to the brilliant design of this cost-effective solution. With 360° IR illumination, the product provides excellent image quality around the clock, even in challenging lighting. With ARTPEC-8 and its deep learning processing unit, the product supports analytics and metadata on all sensors.	320	345	120

AXIS P3737-PLE	AXIS P3737-PLE Panoramic Camera offers 4x5 MP sensors and is perfect for 360° and 270° surveillance. You'll be able to count on both high-quality overviews and detailed coverage thanks to the brilliant design of this cost-effective solution. With 360° IR illumination, the product provides excellent image quality around the clock, even in challenging lighting. With ARTPEC-8 and its deep learning processing unit, the product supports analytics and metadata on all sensors.	320	345	120
AXIS P3738-PLE	AXIS P3738-PLE Panoramic Camera offers 4x4K (4x8 MP) sensors and is perfect for 360° and 270° surveillance. You'll be able to count on both high-quality overviews and detailed coverage thanks to the brilliant design of this cost-effective solution. With 360° IR illumination, the product provides excellent image quality around the clock, even in challenging lighting. With ARTPEC-8 and its deep learning processing unit, the product supports analytics and metadata on all sensors.	320	345	120
AXIS P3818-PVE	AXIS P3818-PVE delivers a 180° panoramic overview of extensive areas with ultra-high resolution images and incredible details up to 30 fps. With 13 MP resolution and seamless stitching of all three images, it offers 180° horizontal and 90° vertical coverage with no blind spots. Including a variety of mounting options, it's also possible to mount two cameras back-to-back for a complete 360° overview using AXIS T94V01C Dual Camera Mount. Featuring edge-to-edge technology, it's easy to add support for audio. Additionally, built-in cybersecurity features prevent unauthorized access and safeguard your system.	230	230	270
AXIS P3827-PVE	AXIS P3827-PVE delivers a 180° panoramic overview of extensive areas with high resolution images and incredible details up to 30 fps. With 7 MP resolution and seamless stitching of all four images, it offers 180° horizontal and 90° vertical coverage with no blind spots. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. With AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. Including horizon straightening, this product will give an excellent viewing experience, enabling to set the horizon in the image. Additionally, built-in cybersecurity features prevent unauthorized access and safeguard your system. Power over Ethernet	230	230	270

AXIS P3925-R RJ45 2.8mm	AXIS P3925-R RJ45 2.8mm is a Full HDTV 1080p fixed dome onboard camera with male RJ45 network connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. <u>Includes lens tool, I-key, and drill template.</u>	165	120	85
AXIS P3925-R RJ45 2.8mm 10P	AXIS P3925-R RJ45 2.8mm 10P is a bulk pack 10x AXIS P3925-R. Full HDTV 1080p fixed dome onboard camera with male RJ45 network connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	555	365	280
AXIS P3925-R M12 2.8mm	AXIS P3925-R M12 2.8mm is full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 connector. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. <u>Includes lens tool, I-key, and drill template.</u>	165	120	85
AXIS P3925-R M12 2.8mm 10P	AXIS P3925-R M12 2.8mm 10P is a bulk pack 10x AXIS P3925-R. Full HDTV 1080p fixed dome onboard camera with female M12 connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	555	365	280

AXIS P3925-LRE RJ45 6mm	AXIS P3925-LRE RJ45 6mm is a compact streamlined exterior onboard camera for rolling stock and vehicles with male RJ45 network connector. The HDTV 1080p camera is equipped with two 850 nm IR LEDs, removable IR-cut filter for day/night functionality and a 6 mm F1.9 lens in a rugged IP6K9K and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology, Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	168	140	95
AXIS P3925-LRE M12 6mm	AXIS P3925-LRE M12 6mm is a compact streamlined exterior onboard camera for rolling stock and vehicles with female M12 connector. The HDTV 1080p camera is equipped with two 850 nm IR LEDs, removable IR-cut filter for day/night functionality and a 6 mm F1.9 lens in a rugged IP6K9K and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology, Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	168	140	95
AXIS P3935-LR RJ45 2.8mm	AXIS P3935-LR RJ45 2.8mm is a Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with male RJ45 network connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	165	120	85
AXIS P3248-LVE	AXIS P3248-LVE is a day/night fixed dome with IK10 vandal-resistant outdoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet	270	200	135

AXIS P3935-LR RJ45 2.8mm 10P	AXIS P3935-LR RJ45 2.8mm 10P is a bulk pack of 10x AXIS P3935-LR. Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with male RJ45 network connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	555	365	280
AXIS P3935-LR M12 2.8mm	AXIS P3935-LR M12 2.8mm is a Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	165	120	85
AXIS P3935-LR M12 2.8m 10P	AXIS P3935-LR M12 2.8m 10P is a bulk pack of 10x AXIS P3935-LR. Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	555	365	280
AXIS P9106-V BRUSHED STEEL	3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Elegant brushed steel design with no visible screws. Dust- and waterproof (IP66) casing. WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. Color: Brushed stainless steel.	153	180	117
AXIS P9106-V WHITE	3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Ligature-resistant design with dust- and waterproof (IP66) casing. WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. White in color.	160	180	110

AXIS Q3536-LVE 9MM DOME CAMERA	Advanced fixed dome camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR. IR shielded dome for reduced reflections. Robust, dust- and IK10+ vandal-resistant outdoor-ready metal casing. Varifocal 4-9 mm P-Iris lens with remote zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.	210	240	271
AXIS Q3536-LVE 29MM DOME CAMERA	Advanced fixed dome camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR. IR shielded dome for reduced reflections. Robust, dust- and IK10+ vandal-resistant outdoor-ready metal casing. Varifocal 11-29 mm P-Iris lens with remote zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.	205	235	266
AXIS Q3538-LVE DOME CAMERA	Advanced fixed dome camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR. IR shielded dome for reduced reflections. Robust, dust- and IK10+ vandal-resistant outdoor-ready metal casing. Varifocal 6-13 mm P-Iris lens with remote zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.	210	240	271

AXIS Q3538-SLVE DOME CAMERA	Advanced fixed dome camera in a DNV marine certified, electropolished stainless steel (SS 316L) outdoor casing, offering high corrosion resistance and IK10+ (50 joules) vandal resistance, with Deep Learning Processing Unit (DLPU). Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR. IR shielded dome for reduced reflections. Varifocal 6-13 mm P-Iris lens with remote zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F), powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket for wall/ceiling or junction boxes.	220	220	275
AXIS Q3626-VE	Advanced dome camera with remote adjustment by Pan, Tilt, Roll and Zoom (PTRZ). Includes a Deep Learning Processing Unit (DLPU) for advanced edge analytics. Support for Forensic WDR, Lightfinder 2.0. Robust, dust- and IK10 vandal-resistant outdoor-ready metal casing. Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.	220	265	190

AXIS Q3628-VE	Advanced dome camera with remote adjustment by Pan, Tilt, Roll and Zoom (PTRZ). Includes a Deep Learning Processing Unit (DLPU) for advanced edge analytics. Support for Forensic WDR, Lightfinder 2.0. Robust, dust- and IK10 vandal-resistant outdoor-ready metal casing. Varifocal 6-13 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.	220	265	190
AXIS Q3819-PVE	AXIS Q3819-PVE delivers a 180° panoramic overview of extensive areas. With 14 MP resolution and seamless stitching of all four images, it offers 180° horizontal and 38° vertical coverage. It's possible to mount two cameras back-to-back for a complete 360° overview using AXIS T94V01C Dual Camera Mount. It features AXIS Object Analytics for nuanced and remarkably granular object classification. Furthermore, it includes built-in motors allowing for remote pan/tilt/roll functionality and it offers smart pairing with Axis network speakers using edge-to-edge technology. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of <u>Axis devices on your network</u>.	230	230	335
AXIS Q9216-SLV STEEL	Robust stainless steel corner-mount camera replacing AXIS Q8414 (Trinity). Key features: • Anti-ligature, stainless steel, IK10+, IP66, • 4MP, >90° VFoV, >120° HFoV, • 940nm LEDs for invisible IR • H.264 + H.265 with Zipstream, • Built-in microphone, • I/O and optional line-in/out, • Option to further prevent screw-tampering	232	245	115
AXIS Q9216-SLV WHITE	Robust stainless steel corner-mount camera replacing AXIS Q8414 (Trinity). Key features: • Anti-ligature, stainless steel, IK10+, IP66, • 4MP, >90° VFoV, >120° HFoV, • 940nm LEDs for invisible IR • H.264 + H.265 with Zipstream, • Built-in microphone, • I/O and optional line-in/out, • Option to further prevent screw-tampering	232	245	115

AXIS Q8414-LVS METAL	AXIS Q8414-LVS Network Camera Metal is a brushed stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	340	260	205
AXIS Q8414-LVS WHITE	AXIS Q8414-LVS Network Camera White is a powder coated stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	340	260	205
AXIS P3265-LVE-3 L.P- Verifier Kit	Please check the supported countries Visit www.axis.com for supported products and application download. Discreet outdoor, HDTV / 1080p, day/night, dust- and IK10 vandal-resistant fixed dome camera with built-in AXIS License Plate Verifier application. Detect and verify vehicles in single lanes with speed up to 30 km/h (19 mph) in 2 to 7 meter distance (7 to 23 feet) to allow vehicle entry/exit into a controlled area. I/O port for direct control, built-in block and allow lists of up to 1000 license plates. License plate reading time less than 1 second. Optimized IR, Forensic WDR, Lightfinder, shock detection, IK10, IP66/67. Operation temperature -40°C to +50°C (-40°F to 122°F). Includes mounting bracket for wall/ceiling or junction boxes. License plate verification day and night. Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	200	260	135
AXIS M3057-PLR Mk II DOME CAMERA	AXIS M3057-PLR MkII is a 6Mp resolution fisheye rollingstock compliant camera offering excellent image quality and a complete 180° or 360° overview. It is intended to be used inside trains or buses. It comes with a M12 connector pigtail. This dome also offers dewarped views such as panorama, quad, corner, and corridor views directly from the camera. It includes Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging light or near darkness. The IR allows for surveillance in pitch darkness. Furthermore, enhanced security functionality prevents unauthorized access and safeguards your system.	170	170	100

AXIS P3905-R MK III RJ45 3.6mm	AXIS P3905-R Mk III RJ45 3.6mm is a 1080p fixed dome onboard camera with a male RJ45 network connector on the pigtail. Equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R Mk III is rollingstock compliant.	111	160	81
AXIS P3905-R MK III M12 3.6mm	AXIS P3905-R Mk III M12 3.6mm is a 1080p fixed dome onboard camera with a M12 network connector on the pigtail. Equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R Mk III is rollingstock compliant.	111	160	81
AXIS P3905-R MK III RJ45 3.6mm 10P	AXIS P3905-R Mk III RJ45 3.6mm 10P is a bulk pack of 10x AXIS P3905-R Mk III cameras. It is a 1080p fixed dome onboard cameras with a male RJ45 network connector on the pigtail. AXIS P3905-R Mk III is equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R Mk III is rollingstock compliant.	394	285	198
AXIS P3905-R MK III M12 3.6mm 10P	AXIS P3905-R Mk III M12 3.6mm 10P is a bulk pack of 10x AXIS P3905-R Mk III cameras. It is a 1080p fixed dome onboard cameras with a M12 network connector on the pigtail. AXIS P3905-R Mk III is equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R Mk III is rollingstock compliant.	394	285	198
AXIS M3905-R RJ45 3.6mm	AXIS M3905-R is a 1080p fixed dome onboard camera with a male RJ45 network connector on the pigtail. Equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R is not rollingstock compliant.	111	160	81
AXIS M3905-R M12 3.6mm	AXIS M3905-R M12 is a 1080p fixed dome onboard camera with a M12 network connector on the pigtail. Equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R M12 is not rollingstock compliant.	111	160	81
AXIS M3905-R RJ45 3.6mm 10P	AXIS M3905-R 10P is a bulk pack of 10x AXIS M3905-R cameras. It is a 1080p fixed dome onboard cameras with a male RJ45 network connector on the pigtail. AXIS M3905-R is equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R is not rollingstock compliant.	394	285	198
AXIS M3905-R M12 3.6mm 10P	AXIS M3905-R M12 10P is a bulk pack of 10x AXIS M3905-R cameras. It is a 1080p fixed dome onboard cameras with a M12 network connector on the pigtail. AXIS M3905-R is equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R M12 is not rollingstock compliant.	394	285	198

AXIS M4317-PLR	AXIS M4317-PLR is Onboard panoramic camera for buses. AXIS M4317-PLR is a discreet, IK10 and IP66 ready dome designed with 6 MP resolution and a stereographic lens. It can deliver multiple 360° or 180° panoramic views at up to 30 fps with no blind spots. Thanks to Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. AXIS M4317-PLVE comes with build-in configurable IR, making it perfect for low light situations. Signed firmware and secure boot ensure firmware authenticity. AXIS M4317-PLR as a built-in RJ45 connector	165	180	100
AXIS M4318-PLR	AXIS M4318-PLR is a discreet, IK10 and IP66 ready dome designed with 12 MP resolution and a stereographic lens. It can deliver multiple 360° or 180° panoramic views at up to 30 fps with no blind spots. Thanks to Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. AXIS M4318-PLVE comes with build-in configurable IR, making it perfect for low light situations. Signed firmware and secure boot ensure firmware authenticity. AXIS M4318-PLR as a built-in RJ45 connector	165	180	100
AXIS P3268-SLVE	Advanced fixed dome camera in a DNV marine certified, NSF/ANSI Standard 169 Special Purpose Food Equipment and Devices electropolished stainless steel (SS 316L) outdoor casing, offering high corrosion resistance and IK11/ IP 66/67/68/ Nema 4X. With Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP 4K stream in 16:9 up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket	185	190	130

AXIS Q9307-LV	This all-in-one device combines sharp video, audio, actionable analytics, and indication LEDs. Camera part is from P3267-LV, 4 mics from M4308, and similar speaker as C1410. With four built-in microphones and a built-in speaker, it supports two-way communication. It comes with coughing fit and stressed voice analytics adding an extra audible dimension to active incident management. AXIS Live Privacy Shield lets you remotely monitor activities while safeguarding privacy. And the indication LEDs clearly show when the camera is recording or when audio is being used. This vandal-resistant, IK08-rated camera withstands daily wipe-downs with chemical detergents. Plus, with just one device to install, it offers cost-efficient one-dron installation	208	278	132
AXIS F4105-SLRE Dome Sensor	AXIS F4105-SLRE is 1080p mini-dome sensor with a Stainless Steel casing (SS 316L). It is NFS/ANSI standard 169 certified for food and beverage processing industry along with catering. AXIS F4105-SLRE has built-in IR lights. It has a default 110° Horizontal Field of View and 2.8mm focal length. AXIS F4105-SLRE uses detachable M12 lenses. Several M12 lenses can be purchased separately offering different types of Horizontal Field of View and Focal Length. AXIS F4105-SLRE is a rugged outdoor mini-dome sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 30fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only)	135	120	80
AXIS P9117-PV	AXIS P9117-PV indoor corner mounted camera with 6 MP sensor and stereographic lens, that can deliver multiple 360° or 180° panoramic views at up to 30 fps with no blind spots. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. The product as well has a in built mic supporting audio analytics out of the box. Has an elevator door state detector ACAP pre-installed. Vandal-resistant (IK10) and IP66-rated dust protection. Product comes in white while steel variant cover purchased in a 4 pack separately	180	160	110

AXIS F4105-SLRE Dome Sensor 8P	AXIS F4105-SLRE is a bulk pack of 8x F4105-R SLRE Stainless Steel Dome Sensors. It is 1080p mini-dome sensor with a Stainless Steel casing (SS 316L). It is NFS/ANSI standard 169 certified for food and beverage processing industry along with catering. AXIS F4105-SLRE has built-in IR lights. It has a default 110° Horizontal Field of View and 2.8mm focal length. AXIS F4105-SLRE uses detachable M12 lenses. Several M12 lenses can be purchased separately offering different types of Horizontal Field of View and Focal Length. AXIS F4105-SLRE is a rugged outdoor mini-dome sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 30fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only).	290	395	200
AXIS M3905-R M12 2.8 mm	AXIS M3905-R is a 1080p fixed dome onboard camera with a M12 network connector on the pigtail. Equipped with 2.8mm, F1.2 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R is not rollingstock compliant.	118	165	85
AXIS M3905-R RJ45 2.8 mm	AXIS M3905-R is a 1080p fixed dome onboard camera with a RJ45 network connector on the pigtail. Equipped with 2.8mm, F1.2 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R is not rollingstock compliant.	118	165	85
AXIS M3905-R M12 2.8mm 10P	AXIS M3905-R M12 2.8mm 10P is a bulk pack of 10x AXIS M3905-R cameras. AXIS M3905-R M12 2.8mm camera is a 1080p fixed dome onboard camera with a M12 network connector on the pigtail. AXIS M3905-R M12 2.8mm camera is equipped with 2.8mm, F1.2 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R M12 2.8mm camera is not rollingstock compliant.	398	290	200
AXIS M3905-R RJ45 2.8 mm 10P	AXIS M3905-R RJ45 2.8mm 10P is a bulk pack of 10x AXIS M3905-R cameras. AXIS M3905-R RJ45 2.8mm camera is a 1080p fixed dome onboard camera with a RJ45 network connector on the pigtail. AXIS M3905-R RJ45 2.8mm camera is equipped with 2.8mm, F1.2 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R RJ45 2.8mm camera is not rollingstock compliant.	398	290	200
AXIS P3905-R Mk III M12 2.8 mm	AXIS P3905-R Mk III is a 1080p fixed dome onboard camera with a M12 network connector on the pigtail. Equipped with 2.8mm, F1.2 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R Mk III is rollingstock compliant.	118	165	85
AXIS P3905-R Mk III M12 2.8 mm 10P	AXIS P3905-R Mk III M12 10P is a bulk pack of 10x AXIS P3905-R Mk III cameras. It is a 1080p fixed dome onboard cameras with a M12 network connector on the pigtail. AXIS P3905-R Mk III is equipped with a 2.8mm, F1.2 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R Mk III M12 2.8mm is rollingstock compliant.	398	290	200

AXIS M5000 50 Hz	15MP indoor panoramic camera with PTZ and 10x optical zoom. Panoramic part; 3x5MP sensors for 360degrees surveillance PTZ part; HDTV 1080 (1920x1080) automatic day/night and autofocus. WDR- Forensic Capture H.264/265 with Zipstream, MJPEG Two-way audio, Deterrence LED, 30W PoE 802.3at or 24V, IP52, White body as standard. Surface mount or Axis PTZ standard mount. Midspan <u>not included.</u>	300	300	210
AXIS M5074	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 720p (1280x720) 30fps in H.264/H.265 with Zipstream and Motion JPEG. IP51 protection against dust and water. Featuring a built-in microphone, includes built-in analytics such as scream detection. Only PoE, midspan not included. Surface <u>ceiling mounting brackets included</u>	160	140	160
AXIS M5075	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 1080p (1920x1080) 30fps in H.264/H.265 with Zipstream and Motion JPEG. IP51 protection against dust and water. Featuring a built-in microphone, includes built-in analytics such as scream detection. Only PoE, midspan not included. Surface <u>ceiling mounting brackets included</u>	160	140	160
AXIS M5526-E 50 Hz	Discreet PTZ with 4MP resolution (2688x1512), 10x optical zoom, automatic day/night and autofocus. Continues 360° pan. WDR, Forensic Capture, IP66, PoE and 24V. 50fps in H.264, H.265 and Motion JPEG, Zipstream, Axis deep learning analytics, Scene profiles, two-way audio, 4 I/O. Surface mount or Axis PTZ <u>standard mount. Midspan not included.</u>	200	200	215
AXIS M5526-E 50 Hz 4 pcs	Industrial four pack of AXIS M5526-E 50Hz. Not <u>including bayonet adapter</u>	400	400	175
AXIS P5655-E 50HZ	PTZ camera with continues 360° pan for both indoor and outdoor with 32x optical zoom, Lightfinder 2, Autofocus and Focus Recall. HDTV 1080p @ 25/50fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are <u>not included.</u>	225	225	390
AXIS P5654-E Mk II 50 Hz	PTZ camera with 77° field of view, continues 360° pan for both indoor and outdoor with 21x optical zoom. HDTV 1080p and 720p @ 50fps in H.264/265, Motion JPEG, Axis Zipstream, Lightfinder 2 and Focus Recall, WDR, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are <u>not included.</u>	225	225	442

AXIS P5676-LE 50 Hz	PTZ camera with QHD 2560x1440 @50fps (4MP), 30x optical zoom with autofocus. IP66, IK10 and NEMA 4X. Zipstream with H.264/ H.265. Auto day/night, IR illumination 200M. Continuous 360° rotation. Shock detection, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Build in analytics, Fence Guard, Loitering Guard, Audio detection, Advanced Gatekeeper, Autotracker 2. Clear transparent dome cover. No mounting bracket or midspan included (several different accessories available).	240	240	320
AXIS Q6010-E 50HZ	Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N, Autopilot for tracking. Designed to be integrated with AXIS Q605x-E and AXIS Q607x-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	434	434	288
AXIS Q6074 50HZ	Top performance PTZ camera with HDTV 720p @50fps 30x optical zoom for indoor use. IP52 rated. Zipstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	265	265	425
AXIS Q6074-E 50HZ	Top performance PTZ camera with HDTV 720p @50fps, 30x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	300	300	440

AXIS Q6074-E 50 Hz NM	Top performance PTZ camera with HDTV 720p @50fps, 30x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover. No Midspan or mounting bracket included (several different accessories available)	300	300	440
AXIS Q6074-E 60 Hz NM	Top performance PTZ camera with HDTV 720p @60fps, 30x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover. No Midspan or mounting bracket included (several different accessories available)	300	300	440
AXIS Q6075 50HZ	Top performance PTZ camera with HDTV 1080p @50fps 40x optical zoom for indoor use. IP52 rated. Zipstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	265	265	425

AXIS Q6075-E 50HZ	Top performance PTZ camera with HDTV 1080p @50fps, 40x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	300	300	440
AXIS Q6075-E 50 Hz NM	Top performance PTZ camera with HDTV 1080p @50fps, 40x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover. No Midspan or mounting bracket included (several different accessories available).	300	300	440
AXIS Q6078-E 50HZ	Top performance UHD 4K PTZ camera, 20x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	295	295	445

AXIS Q6078-E 50 Hz NM	Top performance UHD 4K PTZ camera, 20x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover. No Midspan or mounting bracket included (several different accessories available).	295	295	445
AXIS Q6100-E 50HZ	Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N. Directional Audio Detection. Designed to be integrated with any AXIS Q61-series camera for large area coverage and simultaneous zoom-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q61.	400	400	290
AXIS Q6135-LE 50HZ	PTZ camera with continues 360° pan and build in IR illumination (200M) with 32x optical zoom, Autofocus and Focus Recall. HDTV 1080p @ 50fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Day & Night, IP66, NEMA 4X and NEMA TS2 classification. Full-size SD-card slot. Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper and analytics. Repaintable surface. Midspan with fiber slot and RJ45 input included.	250	250	390
AXIS Q6135-LE 50 Hz NM	PTZ camera with continues 360° pan and build in IR illumination (200M) with 32x optical zoom, Autofocus and Focus Recall. HDTV 1080p @ 50fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Day & Night, IP66, NEMA 4X and NEMA TS2 classification. Full-size SD-card slot. Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper and analytics. Repaintable surface. Midspan is NOT included.	220	220	365

AXIS Q6225-LE 50 Hz	PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300t), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521, NEMA TS2 for temperature up to 74C (165F), Arctic temperature control. Camera part; 1/2" sensor with HDTV 1080p, 30x optical zoom, 50fps, H264/H.265 with Zipstream and Motion JPEG, WDR, improved EIS. Perfect image quality in all directions without distortion, window wiper. Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Build in analytics. 90W Midspan included. Color; Urban grey. No mounting bracket included (several different accessories available).	275	380	380
AXIS Q6225-LE 50 Hz NM	PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300t), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521, NEMA TS2 for temperature up to 74C (165F), Arctic temperature control. Camera part; 1/2" sensor with HDTV 1080p, 30x optical zoom, 50fps, H264/H.265 with Zipstream and Motion JPEG, WDR, improved EIS. Perfect image quality in all directions without distortion, window wiper. Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Color; Urban grey. No Midspan or mounting bracket included (several different accessories available).	275	380	380
AXIS Q6315-LE 50 Hz	High-end PTZ camera with HDTV 1080p @50fps, 1/2" RGB sensor, 31x optical Quick zoom 1sec from width to tele and Laser Focus. Outdoor-ready, IP66, IK10 and NEMA 4x-rated NEMA TS2 for temperature up to 74C (165F). Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C. Auto day/night functionality, IR illumination up to 300M (980Feet). Continuous 360° rotation. Shock detection, Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Build in analytics. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	292	292	362

AXIS Q6315-LE 50 Hz NM	High-end PTZ camera with HDTV 1080p @50fps, 1/2" RGB sensor, 31x optical Quick zoom 1sec from width to tele and Laser Focus. Outdoor-ready, IP66, IK10 and NEMA 4x-rated NEMA TS2 for temperature up to 74C (165F). Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C. Auto day/night functionality, IR illumination up to 300M (980Feet). Continuous 360° rotation. Shock detection, Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Build in analytics. Clear transparent dome cover. No Midspan or mounting bracket included.	293	293	367
AXIS Q6318-LE 50 Hz	High-end PTZ camera with UHD 4K @25fps (8MP), 1/2" RGB sensor, 31x optical Quick zoom 1sec from width to tele and Laser Focus. Outdoor-ready, IP66, IK10 and NEMA 4x-rated NEMA TS2 for temperature up to 74C (165F). Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C. Auto day/night functionality, IR illumination up to 200M (656Ft). Continuous 360° rotation. Shock detection, Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Build in analytics. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	295	295	367
AXIS Q6318-LE 50 Hz NM	High-end PTZ camera with UHD 4K @25fps (8MP), 1/2" RGB sensor, 31x optical Quick zoom 1sec from width to tele and Laser Focus. Outdoor-ready, IP66, IK10 and NEMA 4x-rated NEMA TS2 for temperature up to 74C (165F). Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C. Auto day/night functionality, IR illumination up to 200M (656Ft). Continuous 360° rotation. Shock detection, Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Build in analytics. Clear transparent dome cover. No Midspan or mounting bracket included (several different accessories available).	293	293	367
AXIS V5925 50 Hz	Generic PTZ camera with 30x zoom, autofocus and HDTV 1080p resolution at 50fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. Studio quality in stereo. Power supply and wall mount bracket are included.	200	222	374
AXIS V5938 50 Hz	Generic PTZ camera with 20x zoom, autofocus and UHD 4K resolution at 50fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, WDR, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. Studio audio quality in stereo. Power supply, wall mount bracket and s/w for streaming are included.	200	220	370

AXIS Q8752-E 35 MM 8.3 FPS	High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM-module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	400	520	660
AXIS Q8752-E ZOOM 8.3 FPS	High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM-module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	400	520	660

AXIS Q8641-E 35MM 8.3 FPS 24V	High accuracy outdoor PT positioning thermal camera. 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	375	375	730
AXIS Q8642-E 60MM 8.3 FPS 24V	High accuracy outdoor PT positioning thermal camera. 640x480 resolution, 8.3 fps and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	375	375	730
AXIS Q8741-E 35MM 8.3 FPS 24V	High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	395	520	670

AXIS Q8741-LE 35MM 8.3 FPS 24V	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	395	520	670
AXIS Q8742-E ZOOM 8.3 FPS 24V	High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	395	520	670

AXIS Q8742-E 35MM 8.3 FPS 24V	High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	395	520	670
AXIS Q8742-LE 35MM 8.3 FPS 24V	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera only need one IP address and supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	395	520	670

AXIS Q8742-LE ZOOM 8.3 FPS 24V	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	395	520	670
AXIS P1280-E 2.2 MM 8.3 FPS	AXIS P1280-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable. The camera provides 208x156 resolution, a 2.2 mm lens with 63° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The flexible form factor allows it to be placed in locations with limited space and a wide range of mounting accessories enables wall, ceiling and recessed installations. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	150	300	80

AXIS P1280-E 4MM 8.3 FPS	AXIS P1280-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable. The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The flexible form factor allows it to be placed in locations with limited space and a wide range of mounting accessories enables wall, ceiling and recessed installations. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	150	300	85
AXIS P1290-E 4 MM 8.3 FPS	AXIS P1290-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing. The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	200	225	130
AXIS Q1941-E 7MM 8.3 FPS	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	190	410	240

AXIS Q1951-E 7mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <40 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities	140	261	160
AXIS Q1941-E 13MM 8.3 FPS	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	190	410	240
AXIS Q1951-E 13mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <40 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities	140	261	160

AXIS Q1941-E 19MM 8.3 FPS	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	190	410	240
AXIS Q1951-E 19mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <40 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	261	160
AXIS Q1951-E 35mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <40 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	261	160

AXIS Q1941-E 60MM 8.3 FPS	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	190	410	240
AXIS Q1941-E PT MOUNT 7MM 8.3 FPS	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185
AXIS Q1941-E PT MOUNT 13MM 8.3 FPS	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185
AXIS Q1941-E PT MOUNT 19MM 8.3 FPS	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185

AXIS Q1941-E PT MOUNT 35MM 8.3 FPS	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185
AXIS Q1941-E PT MOUNT 60MM 8.3 FPS	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185
AXIS Q1942-E 10MM 8.3 FPS	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	190	410	240
AXIS Q1952-E 10mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 10 mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <30 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	261	160

AXIS Q1942-E 19MM 8.3 FPS	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 19 mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	190	410	240
AXIS Q1952-E 19mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 19 mm lens with 31° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <30 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	261	160
AXIS Q1942-E 35MM 8.3 FPS	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 35 mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	190	410	240

AXIS Q1952-E 35mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 35 mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <30 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	261	160
AXIS Q1942-E 60MM 8.3 FPS	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	190	410	240
AXIS Q1942-E PT MOUNT 10MM 8.3 FPS	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185
AXIS Q1942-E PT MOUNT 19MM 8.3 FPS	Q1942-E PT mount 19mm Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 19mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185

AXIS Q1942-E PT MOUNT 35MM 8.3 FPS	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 35mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185
AXIS Q1942-E PT MOUNT 60MM 8.3 FPS	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	195	390	185
AXIS Q1971-E 7 mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount. The camera is based on ARTPEC 8 and it supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <20 mK @25C, F1.0 Image sensor resolution QVGA (384x288 pixels) The thermal image sensor of this product is manufactured within the European Union and is subject to EU export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	260	156

AXIS Q1971-E 13 mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount. The camera is based on ARTPEC 8 and it supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <20 mK @25C, F1.0 Image sensor resolution QVGA (384x288 pixels) The thermal image sensor of this product is manufactured within the European Union and is subject to EU export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	260	156
AXIS Q1971-E 19 mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount. The camera is based on ARTPEC 8 and it supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <20 mK @25C, F1.0 Image sensor resolution QVGA (384x288 pixels) The thermal image sensor of this product is manufactured within the European Union and is subject to EU export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	260	156

AXIS Q1971-E 25 mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount. The camera is based on ARTPEC 8 and it supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <20 mK @25C, F1.0 Image sensor resolution QVGA (384x288 pixels) The thermal image sensor of this product is manufactured within the European Union and is subject to EU export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	260	156
AXIS Q1971-E 35 mm 8.3 fps	Outdoor thermal network camera for wall and ceiling mount. The camera is based on ARTPEC 8 and it supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with AI-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <20 mK @25C, F1.0 Image sensor resolution QVGA (384x288 pixels) The thermal image sensor of this product is manufactured within the European Union and is subject to EU export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	140	260	156
AXIS Q1961-TE 7mm 8.3 fps	Q1961-TE is an ARTPEC 8 based thermometric camera that lets you remotely monitor temperatures from -40 °C to 350 °C (-40 °F to 660 °F). It supports up to 10 configurable polygonal detection areas allowing you to monitor for specific temperature levels and change rates. With early fire detection analytics (included), it's possible to set triggers and preventively act on early signs of fire. Robust and impact-resistant (IK10 and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free and light weight. Edge-to-edge functionality lets you connect network speakers and other Axis network devices.	260	140	165

AXIS Q1961-TE 13mm 8.3 fps	Q1961-TE is an ARTPEC 8 based thermometric camera that lets you remotely monitor temperatures from -40 °C to 350 °C (-40 °F to 660 °F). It supports up to 10 configurable polygonal detection areas allowing you to monitor for specific temperature levels and change rates. With early fire detection analytics (included), it's possible to set triggers and preventively act on early signs of fire. Robust and impact-resistant (IK10 and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free and light weight. Edge-to-edge functionality lets you connect network speakers and other Axis network devices.	260	140	165
AXIS Q2101-TE 7 mm 8.3 fps	Q2101-TE is an ARTPEC 8 based thermometric camera that lets you remotely monitor temperatures from -40 °C to 350 °C (-40 °F to 660 °F). Robust and impact-resistant (IK10 and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free. Edge-to-edge functionality lets you connect network speakers and other Axis network devices. Q2101-TE can be PT-mounted (PT head sold separately). When PT-mounted, Q2101-TE supports the Axis unique feature of Thermometric guard tour, giving you the possibility to configure 10 polygonal detection areas per preset. With up to 256 presets you can monitor very large and complex scenes for specific temperature levels and temperature change rates. With early fire detection analytics (included), it's possible to set triggers and preventively act on early signs of fire. The Early Fire Detection ACAP comes with a smart filtering function eliminating many false alarms, commonly originating from work vehicles such as truck, excavators and cars.	210	560	230
AXIS Q2101-TE 13 mm 8.3 fps	Q2101-TE is an ARTPEC 8 based thermometric camera that lets you remotely monitor temperatures from -40 °C to 350 °C (-40 °F to 660 °F). Robust and impact-resistant (IK10 and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free. Edge-to-edge functionality lets you connect network speakers and other Axis network devices. Q2101-TE can be PT-mounted (PT head sold separately). When PT-mounted, Q2101-TE supports the Axis unique feature of Thermometric guard tour, giving you the possibility to configure 10 polygonal detection areas per preset. With up to 256 presets you can monitor very large and complex scenes for specific temperature levels and temperature change rates. With early fire detection analytics (included), it's possible to set triggers and preventively act on early signs of fire. The Early Fire Detection ACAP comes with a smart filtering function eliminating many false alarms, commonly originating from work vehicles such as truck, excavators and cars.	210	560	230

AXIS Q2101-TE 19 mm 8.3 fps	Q2101-TE is an ARTPEC 8 based thermometric camera that lets you remotely monitor temperatures from -40 °C to 350 °C (-40 °F to 660 °F). Robust and impact-resistant (IK10 and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free. Edge-to-edge functionality lets you connect network speakers and other Axis network devices. Q2101-TE can be PT-mounted (PT head sold separately). When PT-mounted, Q2101-TE supports the Axis unique feature of Thermometric guard tour, giving you the possibility to configure 10 polygonal detection areas per preset. With up to 256 presets you can monitor very large and complex scenes for specific temperature levels and temperature change rates. With early fire detection analytics (included), it's possible to set triggers and preventively act on early signs of fire. The Early Fire Detection ACAP comes with a smart filtering function eliminating many false alarms, commonly originating from work vehicles such as truck, excavators and cars.	210	560	230
AXIS Q2901-E 9MM 8.3 FPS	AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	190	410	240
AXIS Q2901-E PTMOUNT 9MM 8.3 FPS	AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	195	390	185

AXIS Q2901-E 19MM 8.3 FPS	AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	190	410	240
AXIS Q2901-E PTMOUNT 19MM 8.3 FPS	AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	195	390	185
AXIS FA1080-E 2.2MM 8.3 FPS	AXIS FA1080-E 2.2M 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 2.2 mm lens with 63° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable. This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	150	300	80
AXIS FA1080-E 4MM 8.3 FPS	AXIS FA1080-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable. This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	150	300	80

AXIS FA4090-E 4MM 8.3 FPS	AXIS FA4090-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The dome housing makes it easy to install and direct the sensor unit to cover your area of interests. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable. This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	227	197	130
AXIS P7701	1 channel network video decoder. Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. Includes power supply.	190	250	105
AXIS P7701 VIDEO DEC BB BULK 20PCS	AXIS P7701 BARE BOARD in 20-pack. Cannot be sold separately as single packs. No power supplies.	360	550	280
AXIS P7701 VIDEO DECODER BARE BONE	Bare bone 1 channel video decoder (PCB without any mechanics). Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. No power supply.	165	240	80
AXIS D1110 VIDEO DECODER 4K	4K Video Decoder with 8 streams in multiview, local playback of media, DC or PoE powered, with audio through audio in or HDMI plus many more features	175	160	70
AXIS M7104 VIDEO ENCODER	Four channel video encoder supporting PAL/NTSC cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Serial port for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage.	210	170	75
AXIS P7216 VIDEO ENCODER	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. SFP slot for optional fiber connection and/or network redundancy. Unit includes 4 x micro SD card slots for edge storage. PTZ support. Unit has 4 x ARTPEC chips and 4 x IP addresses. Includes power supply.	570	190	75

AXIS P7304 VIDEO ENCODER	Four channel video encoder supporting PAL/NTSC and HD analog cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions up to 1080p. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm and audio detection. I/O for alarm/event handling, serial port for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage. Two-way audio with analog or digital microphone.	210	170	75
AXIS M7116	Sixteen-channel video encoder support PAL/NTSC cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. 4 serial ports for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage. PTZ cameras control over the serial ports.	285	520	85
AXIS P7316 Video Encoder	16-channel video encoder. Max 4K resolution at 15fp on 4x channels. The video encoder has 4x ARTPEC-7 chips and 4x IP addresses H.264, H265 and Motion JPEG on all channels. Video motion detection. Active tampering alarm. Two-way audio with audio detection. SFP slot for optional fiber connection and/or network redundancy. Unit includes 4x micro SD card slots for edge storage. PTZ support. Signed firmware and secure boot to enhance cybersecurity. It includes a power supply.	290	520	90
AXIS 291 1U VIDEO SERV RACK	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output.	420	550	140
AXIS S3008 Mk II 2 TB	AXIS S3008 Mk II 2 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. With its powerful PoE switch, eight PoE class 3 devices can be connected to the recorder and the recordings are done on the internal hard drive. It is compatible with AXIS Companion, AXIS Camera Station, their mobile app, and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 2 TB surveillance class hard drive and includes 5-year limited hardware warranty. This product is not a System Controller for Body Worn Solutions.	200	230	115

AXIS S3008 Mk II 4 TB	AXIS S3008 Mk II 4 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. With its powerful PoE switch, eight PoE class 3 devices can be connected to the recorder and the recordings are done on the internal hard drive. It is compatible with AXIS Companion, AXIS Camera Station, their mobile app, and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 4 TB surveillance class hard drive and includes 5-year limited hardware warranty. This product is not a System Controller for Body Worn Solutions.	200	230	115
AXIS S3008 Mk II 8 TB	AXIS S3008 Mk II 8 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. With its powerful PoE switch, eight PoE class 3 devices can be connected to the recorder and the recordings are done on the internal hard drive. It is compatible with AXIS Companion, AXIS Camera Station, their mobile app, and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 8 TB surveillance class hard drive and includes 5-year limited hardware warranty. This product is not a System Controller for Body Worn Solutions.	200	230	115
AXIS S3016 8 TB	AXIS S3016 8 TB Recorder is a 1U rack recorder with an integrated PoE switch and high power budget for up to 16 devices and a maximum of PoE class 4 per port. It provides reliable recording thanks to the four surveillance-grade hard drives and different RAID levels. This high-performance recorder offers a gigabit switch for connecting network devices and a 2.5 gigabit uplink for video recordings in ultra-high definition and includes a 5-year warranty. The recorder can be used in single-site, multi-site systems and for expanding storage and network in existing systems. It is compatible with both AXIS Companion as well as AXIS Camera Station video management software and mobile app. AXIS S3016 can be installed in server racks with a post-to-post distance between 376mm (14.8in) and 499mm (19.6in). For deeper server racks, AXIS TS3901 Rail Extensions can be used when the post-to-post distance is between 499mm (19.6in) and 689mm (27.1in).	525	525	190

AXIS S3016 16 TB	AXIS S3016 16 TB Recorder is a 1U rack recorder with an integrated PoE switch and high power budget for up to 16 devices and a maximum of PoE class 4 per port. It provides reliable recording thanks to the four surveillance-grade hard drives and different RAID levels. This high-performance recorder offers a gigabit switch for connecting network devices and a 2.5 gigabit uplink for video recordings in ultra-high definition and includes a 5-year warranty. The recorder can be used in single-site, multi-site systems and for expanding storage and network in existing systems. It is compatible with both AXIS Companion as well as AXIS Camera Station video management software and mobile app. AXIS S3016 can be installed in server racks with a post-to-post distance between 376mm (14.8in) and 499mm (19.6in). For deeper server racks, AXIS TS3901 Rail Extensions can be used when the post-to-post distance is between 499mm (19.6in) and 689mm (27.1in).	525	525	190
AXIS S3016 32 TB	AXIS S3016 32 TB Recorder is a 1U rack recorder with an integrated PoE switch and high power budget for up to 16 devices and a maximum of PoE class 4 per port. It provides reliable recording thanks to the four surveillance-grade hard drives and different RAID levels. This high-performance recorder offers a gigabit switch for connecting network devices and a 2.5 gigabit uplink for video recordings in ultra-high definition and includes a 5-year warranty. The recorder can be used in single-site, multi-site systems and for expanding storage and network in existing systems. It is compatible with both AXIS Companion as well as AXIS Camera Station video management software and mobile app. AXIS S3016 can be installed in server racks with a post-to-post distance between 376mm (14.8in) and 499mm (19.6in). For deeper server racks, AXIS TS3901 Rail Extensions can be used when the post-to-post distance is between 499mm (19.6in) and 689mm (27.1in).	525	525	190
AXIS S3008 4 TB	AXIS S3008 4 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. It is compatible with AXIS Companion VMS, AXIS Camera Station and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 4 TB surveillance class hard drive and includes 5-year limited hardware warranty. Calculate your PoE requirements with AXIS Site Designer. This product is not a System Controller for Body Worn Solutions.	120	190	220

AXIS S3008 8 TB	AXIS S3008 8 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. It is compatible with AXIS Companion VMS, AXIS Camera Station and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 8 TB surveillance class hard drive and includes 5-year limited hardware warranty. Calculate your PoE requirements with AXIS Site Designer. This product is not a System Controller for Body Worn Solutions.	120	190	220
AXIS S2108	AXIS Camera Station S2108 Appliance is an affordable, all-in-one appliance including a VMS client/server, storage, and an integrated PoE switch - all validated to meet the demands for reliable, basic surveillance up to 1080p. It is preloaded with AXIS Camera Station VMS and all other necessary software such as Windows 10 IoT Enterprise and AXIS Recorder Toolbox. It includes a Trusted Platform module (TPM 2.0), 2 TB storage, Core licenses for 8 devices and 5-year limited hardware warranty.	295	375	175
AXIS S2208 Mk II 4 TB	AXIS Camera Station S2208 Mk II 4 TB Appliance is ideal in coffee shops and offices, this all-in-one standalone appliance is silent and won't disturb local operations. It includes 8 AXIS Camera Station Pro licenses, a PoE switch with up to eight channels, and 4 TB storage. It also offers flexible storage options and supports powerful AI applications such as Smart Search 2. The system can easily be expanded using AXIS S30 Recorder Series for additional channels, PoE and storage. It's preloaded with software and tools to help you set up and maintain your system. For instance, AXIS Recorder Toolbox includes an intuitive setup wizard. Furthermore, it offers high-security features and standards such as FIPS 140-2 Level 2 certified TPM, Secure Boot, Signed firmware, SBOM and much more. The product includes 5-year limited hardware warranty.	465	370	270
AXIS S2212 Mk II 6 TB	AXIS Camera Station S2212 Mk II 6 TB Appliance is ideal in coffee shops and offices, this all-in-one standalone appliance is silent and won't disturb local operations. It includes 12 AXIS Camera Station Pro licenses, a PoE switch with up to 12 channels, and 6 TB storage. It also offers flexible storage options and supports powerful AI applications such as Smart Search 2. The system can easily be expanded using AXIS S30 Recorder Series for additional channels, PoE and storage. It's preloaded with software and tools to help you set up and maintain your system. For instance, AXIS Recorder Toolbox includes an intuitive setup wizard. Furthermore, it offers high-security features and standards such as FIPS 140-2 Level 2 certified TPM, Secure Boot, Signed firmware, SBOM and much more. The product includes 5-year limited hardware warranty.	465	370	270

AXIS S2216 Mk II 8 TB	AXIS Camera Station S2216 Mk II 8 TB Appliance is ideal for manufacturing sites and commercial buildings, this all-in-one rack appliance is perfect for installation in a server rack. It includes 16 AXIS Camera Station Pro licenses, a PoE switch with up to 16 channels, and 8 TB storage. It also offers flexible storage options and supports powerful AI applications such as Smart Search 2. The system can easily be expanded using AXIS S30 Recorder Series for additional channels, PoE and storage. It's preloaded with software and tools to help you set up and maintain your system. For instance, AXIS Recorder Toolbox includes an intuitive setup wizard. Furthermore, it offers high-security features and standards such as FIPS 140-2 Level 2 certified TPM, Secure Boot, Signed firmware, SBOM and much more. The product includes 5-year limited hardware warranty.	780	575	200
AXIS S2224 Mk II 12 TB	AXIS Camera Station S2224 Mk II 12 TB Appliance is ideal for manufacturing sites and commercial buildings, this all-in-one rack appliance is perfect for installation in a server rack. It includes 24 AXIS Camera Station Pro licenses, a PoE switch with up to 24 channels, and 12 TB storage. It also offers flexible storage options and supports powerful AI applications such as Smart Search 2. The system can easily be expanded using AXIS S30 Recorder Series for additional channels, PoE and storage. It's preloaded with software and tools to help you set up and maintain your system. For instance, AXIS Recorder Toolbox includes an intuitive setup wizard. Furthermore, it offers high-security features and standards such as FIPS 140-2 Level 2 certified TPM, Secure Boot, Signed firmware, SBOM and much more. The product includes 5-year limited hardware warranty.	780	575	260
AXIS S2208	AXIS Camera Station S2208 Appliance is an eight channel compact desktop Client/Server including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 4 TB storage, Core licenses for 8 devices, 5-year limited hardware warranty on the appliance and hard drive. Supports up to 4k ultra HD.	470	365	265
AXIS S2212	AXIS Camera Station S2212 Appliance is a twelve channel compact desktop Client/Server including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 6 TB storage, Core licenses for 12 devices, 5-year limited hardware warranty on the appliance and hard drive. Supports up to 4k ultra HD.	470	365	265

AXIS S2216	AXIS Camera Station S2216 Appliance is a sixteen channel Client/Server for rack-mounting including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 8 TB storage, Core licenses for 16 devices, 5-year limited hardware warranty on the appliance and hard drives. <u>Supports up to 4k ultra HD.</u>	575	775	205
AXIS S2224	AXIS Camera Station S2224 Appliance is a twenty four channel Client/Server for rack-mounting including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 12 TB storage, Core licenses for 24 devices, 5-year limited hardware warranty on the appliance and hard drives. <u>Supports up to 4k ultra HD.</u>	575	775	205
AXIS S1216 TOWER 8 TB	AXIS Camera Station S1216 Tower is an out-of-the-box ready workstation tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	445	530	380
AXIS S1216 RACK 8 TB	AXIS Camera Station S1216 Rack 8 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1216 Rack 8 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With an enterprise-grade hard drive, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1216 Rack 8 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	610	940	260

AXIS S1232 RACK 16 TB	AXIS Camera Station S1232 Rack 16 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1232 Rack 16 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1232 Rack 16 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	630	910	280
AXIS S1232 RACK 32 TB	AXIS Camera Station S1232 Rack 32 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1232 Rack 32 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1232 Rack 32 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	610	930	280

AXIS S1232 TOWER 32 TB	AXIS Camera Station S1232 Tower 32 TB is an out-of-the-box ready recording server and client validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1232 Tower 32 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1232 Tower 32 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	570	810	420
AXIS S1264 RACK 24 TB	AXIS Camera Station S1264 Rack 24 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1264 Rack 24 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 64 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1264 Rack 24 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	685	940	350

AXIS S1264 RACK 64 TB	AXIS Camera Station S1264 Rack 64 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1264 Rack 64 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 64 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1264 Rack 64 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	690	940	350
AXIS S1264 RACK 144 TB	AXIS Camera Station S1264 Rack 144 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1264 Rack 144 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 64 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1264 Rack 144 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	690	940	350

AXIS S1296 RACK 96 TB	AXIS Camera Station S1296 Rack 96 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	685	940	350
AXIS S1296 RACK 192 TB	AXIS Camera Station S1296 Rack 192 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 192 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 192 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	690	940	360
AXIS S9301	AXIS Camera Station S9301 Workstation is a complement to Axis recorders to enable quick set-up of a workstation meeting the demands for a reliable surveillance. The workstation is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9301 has validated hardware and software components for optimal surveillance experience and includes 5-year limited hardware warranty.	260	550	145

AXIS S9302	AXIS Camera Station S9302 Workstation is a complement to Axis recorders to enable quick set-up of a workstation meeting the demands for a reliable Ultra HD surveillance. The workstation is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9302 has validated hardware and software components for optimal surveillance experience and includes 5-year <u>limited hardware warranty</u> .	500	410	290
Axis Professional Services Token	Payment for Axis Professional Services. Only valid when applied to a signed Statement of Work (SOW) with an assigned Professional Services ID (PSID). Note: Order must contain PSID to be valid. Axis Professional Services tokens are non-cancellable, non-changeable, and non-returnable.	0	0	0
AXIS DEVICE MANAGER EXTEND	Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable. AXIS Device Manager Extend (ADM Extend) offers a unified, user-friendly interface that helps you proactively manage your customers' Axis devices and sites from anywhere. Featuring an intuitive dashboard and remote site access, you can manage thousands of Axis devices and it allows you to perform firmware updates and other tasks at scale. Additionally, it's an invaluable tool for troubleshooting and proactive planning, helping you save time and money. ADM Extend delivers product warranty, end-of-life, and hardening compliance information. For instance, you'll receive recommendations for firmware upgrades to help mitigate your customers device vulnerabilities. ADM Extend is based on annual subscription The renewal date is time-based (12 months) One license per device Activation through a license key redeemed by SI in AXIS License Manager. Free 90-day trial period End Customers and Authorized partners = world market price/device and year MRP (NSI), Gold and Silver Solution Partners = requires no license for full access			
ACAP AXIS PERIMETER DEFENDER 1 LICENSE	Single unit license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download.	230	320	2
ACAP AXIS PERIMETER DEFENDER 1 E-LICENSE	Single unit e-license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download. Delivered as eLicense key. One license key per unit. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	0	0	0

ACAP AXIS PERIMETER DEFENDER 10 LICENSE	Ten (10) unit license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download.	230	320	2
ACAP AXIS PERIMETER DEFENDER 10 E-LICENSE	Ten (10) unit e-license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download. Delivered as eLicense key. One license key per unit. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	0	0	0
AXIS H. 264 50-user decoder license pack	A license document that grants installation of AXIS AVC/H.264 decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 but does not have support for audio.	320	230	2
AXIS H.264 +AAC decoder 50-user decoder license pack	A license document that grants installation of AXIS AVC/H.264 and ACC decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 that also have support for audio.	320	230	2
AXIS PEOPLE COUNTER E-LICENSE	AXIS People Counter is a cost-efficient and scalable video analytics application for people counting. This business-improving application, installed on a network camera, enables accurate monitoring and analysis of customer flows. It is ideal for e.g. quick evaluation of marketing efforts, improving staff and store planning, or evaluating conversion rate if combined with point-of-sale data. In addition to people counting, this version can also estimate occupancy levels and detect and notify if more than one person enters within a set time interval or if people move in the wrong direction. Delivered as eLicense key. One license key per unit. Note: eLicenses are non-cancellable, non-changeable and non-returnable	0	0	0
AXIS LICENSE PLATE VERIFIER 1P E-LICENSE	Please check the supported countries (https://www.axis.com/products/axis-license-plate-verifier/where-to-buy) before ordering. Single unit e-license for AXIS License Plate Verifier. AXIS License Plate Verifier is an AXIS Camera Application Platform software that can be used in selected Axis cameras. It supports license plate recognition for slow-speed traffic and vehicle access control. This edge-based analytics allows for smart license plate reading at speeds of up to 70 km/h (45 mph). Visit www.axis.com for supported products and application download. Delivered as eLicense key. One license key per unit. Note: eLicenses are non-cancellable, non-changeable and non-returnable	0	0	0

AXIS STORE REPORTER 1Y ELICENSE	AXIS Store Reporter is a web-based tool that is used for graphical representation and reporting of statistical data gathered from Axis retail analytics applications. It is sold on a per channel basis as e-license. A license is valid for 12 months. After this period the license will have to be renewed. AXIS Store Reporter is based on Axis annual subscription. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
ACS CORE DEVICE E-LICENSE	One (1) AXIS Camera Station version 5.0 and up, Core Device license. Applicable for AXIS devices. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Delivered as eLicense key, One license key per order. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	0	0	0
ACS UNIVERSAL DEVICE E-LICENSE	One (1) Universal Device license applicable for AXIS Camera Station version 5.0 and up. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Delivered as eLicense key, One license key per order. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	0	0	0
ACS 4 TO UNIVERSAL UPG E-LICENSE	One (1) upgrade license applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. Delivered as eLicense key, One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	0	0	0
ACS CORE TO UNIVERSAL UPG E-LICENSE	This license is primarily used for replacing AXIS devices with ONVIF devices. One (1) Upgrade license and one AXIS Camera Station version 5 Core Device license upgrades to one (1) Universal Device license. Delivered as eLicense key, One license key per order. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	0	0	0

ACS 1 CORE DEVICE LICENSE	One (1) AXIS Camera Station version 5.0 and up, Core Device license. Applicable for AXIS devices. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 4 CORE DEVICE LICENSE	Four (4) AXIS Camera Station version 5.0 and up, Core Device licenses. Applicable for AXIS devices. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 16 CORE DEVICE LICENSE	Sixteen (16) AXIS Camera Station version 5.0 and up, Core Device licenses. Applicable for AXIS devices. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 32 CORE DEVICE LICENSE	Thirtytwo (32) AXIS Camera Station version 5.0 and up, Core Device licenses. Applicable for AXIS devices. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 1 UNIVERSAL DEVICE LICENSE	One (1) Universal Device license applicable for AXIS Camera Station version 5.0 and up. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. <u>Delivered as printed license code in envelope.</u>	230	320	2

ACS 4 UNIVERSAL DEVICE LICENSE	Four (4) Universal Device licenses applicable for AXIS Camera Station version 5.0 and up. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 10 UNIVERSAL DEVICE LICENSE	Ten (10) Universal Device licenses applicable for AXIS Camera Station version 5.0 and up. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 20 UNIVERSAL DEVICE LICENSE	Twenty (20) Universal Device licenses applicable for AXIS Camera Station version 5.0 and up. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 4 TO UNIVERSAL 1 UPG.LIC	One (1) upgrade license applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 4 TO UNIVERSAL 5 UPG.LIC	Five (5) upgrade licenses applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. <u>Delivered as printed license code in envelope.</u>	230	320	2
ACS 4 TO UNIVERSAL 10 UPG.LIC	Ten (10) upgrade licenses applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. <u>Delivered as printed license code in envelope.</u>	230	320	2

ACS 4 TO UNIVERSAL 20 UPG.LIC	Twenty (20) upgrade licenses applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. Delivered as printed license code in envelope.	230	320	2
ACS CORE TO UNIVERSAL 1 UPG.LIC	This license is primarily used for replacing AXIS devices with ONVIF devices. One (1) Upgrade license applicable for AXIS Camera Station version 5 Core Device license upgrade to Universal Device license. Delivered as printed license code in envelope.	230	320	2
ACS CORE TO UNIVERSAL 5 UPG.LIC	This license is primarily used for replacing AXIS devices with ONVIF devices. Five (5) Upgrade license applicable for AXIS Camera Station version 5 Core Device license upgrade to Universal Device license. Delivered as printed license code in envelope.	230	320	2
ACS CORE TO UNIVERSAL 10 UPG.LIC	This license is primarily used for replacing AXIS devices with ONVIF devices. Ten (10) Upgrade license applicable for AXIS Camera Station version 5 Core Device license upgrade to Universal Device license. Delivered as printed license code in envelope.	230	320	2
ACS CORE TO UNIVERSAL 20 UPG.LIC	This license is primarily used for replacing AXIS devices with ONVIF devices. Twenty (20) Upgrade license applicable for AXIS Camera Station version 5 Core Device license upgrade to Universal Device license. Delivered as printed license code in envelope.	230	320	2
ACS PRO CORE DEVICE 1y Lic	AXIS Camera Station Pro v6 Core Device subscription license. Applicable for One(1) Axis device during One(1) year. AXIS Camera Station Pro is a monitoring and recording system optimized to take full advantage of Axis leading network cameras, video encoders, access control and other devices. It combines easy setup with an intuitive user interface for efficient operation and quick investigation. This license is NOT intended for use with AXIS S12, S11, S21 or S22 Series NVRs which have licenses included. To add more licenses to an AXIS S-Series NVR, please see NVR licenses. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			

ACS PRO CORE DEVICE 5y Lic	AXIS Camera Station Pro v6 Core Device subscription license. Applicable for One(1) Axis device during Five(5) years. AXIS Camera Station Pro is a monitoring and recording system optimized to take full advantage of Axis leading network cameras, video encoders, access control and other devices. It combines easy setup with an intuitive user interface for efficient operation and quick investigation. This license is NOT intended for use with AXIS S12, S11, S21 or S22 Series NVRs which have licenses included. To add more licenses to an AXIS S-Series NVR, please see NVR licenses. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
ACS PRO UNIVERSAL DEVICE 1y Lic	AXIS Camera Station Pro v6 Universal Device subscription license. Applicable for One(1) device of any supported type during One(1) year. AXIS Camera Station Pro is a monitoring and recording system optimized to take full advantage of Axis leading network cameras, video encoders, access control and other devices. It combines easy setup with an intuitive user interface for efficient operation and quick investigation. This license is NOT intended for use with AXIS S12, S11, S21 or S22 Series NVRs which have licenses included. To add more licenses to an AXIS S-Series NVR, please see NVR licenses. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
ACS PRO UNIVERSAL DEVICE 5y Lic	AXIS Camera Station Pro v6 Universal Device subscription license. Applicable for One(1) device of any supported type during Five(5) years. AXIS Camera Station Pro is a monitoring and recording system optimized to take full advantage of Axis leading network cameras, video encoders, access control and other devices. It combines easy setup with an intuitive user interface for efficient operation and quick investigation. This license is NOT intended for use with AXIS S12, S11, S21 or S22 Series NVRs which have licenses included. To add more licenses to an AXIS S-Series NVR, please see NVR licenses. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			

ACS PRO CORE DEVICE NVR Lic	AXIS Camera Station Pro v6 Core Device NVR tied to hardware, lifetime expansion license. To be used in combination with AXIS S12, S11, S21 or S22 Series recorders as expansion licenses when more licenses than the preloaded are needed. Applicable for One(1) Axis device. The license will be tied to the NVR hardware for the lifetime of the NVR hardware. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
ACS PRO UNIVERSAL DEVICE NVR Lic	AXIS Camera Station Pro v6 Universal Device NVR tied to hardware, lifetime expansion license. To be used in combination with AXIS S11, S12, S21 or S22 Series recorders as expansion licenses when more licenses than the preloaded are needed. Applicable for One(1) device of any supported type. The license will be tied to the NVR hardware for the lifetime of the NVR hardware. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
ACS PRO Core to Universal NVR Lic	ACS PRO Core to Universal NVR Lic. This license is used for converting an existing ACS PRO CORE DEVICE NVR Lic into an ACS PRO UNIVERSAL DEVICE NVR Lic. The resulting license is tied to the same hardware for the lifetime of the NVR hardware. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
ACS CLOUD STORAGE 30D 720P 1Y ELIC	AXIS Camera Station Cloud Storage subscription license. Applicable for One(1) video sensor of any supported type during One(1) year. This license gives you access to 30 days retention time in 720p resolution. AXIS Camera Station Cloud Storage complements your AXIS Camera Station Edge installations offering secure video storage in the cloud, so your recordings are always available when you need them. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
AXIS TM3813-E Dome Clear 4P	AXIS TM3813 Dome Clear 4-Pack, are standard clear domes with anti-scratch hard coating. Compatible with AXIS M4317/M4318-PLVE. 4-pack.	75	250	30
AXIS M3006 CLEAR DOME 5PCS	Original white top cover with clear dome for AXIS M3006, 5pcs.	160	160	200
AXIS M3007 CLEAR DOME 5PCS	Original white top cover with clear dome for AXIS M3007, 5pcs.	155	155	140
AXIS M3024 CLEAR DOME 5PCS	Standard clear domes for AXIS M3024, 5 pcs	280	255	135
AXIS M3044-V/45-V/46-V CL DOME 5P	Standard clear dome for AXIS M3044-V/45-V/46-V, 5 pcs	80	370	40

AXIS M30-PLVE CLEAR DOME A 4P	Standard clear dome with anti-scratch hard coating. Rubber gaskets included. Compatible with AXISM3057/58-PLVE. 4-piece bulk pack.	120	130	95
AXIS M30 CASING B WHITE 5P	Original white casing for AXIS M3047/48-P. 5 pcs.	280	260	55
AXIS TM3803 WHITE CASING 4P	Spare part white casing. Cover top replacement part for M3067/68.	130	105	110
AXIS M42 CASING A WHITE 4P	Original white casings for AXIS M42 series. Easy to repaint. 4-piece bulk pack.	135	130	135
AXIS M42 CLEAR DOME A 4P	Clear dome with anti-scratch hard coating. Compatible with AXIS M42 series. 4x domes per pack.	55	365	100
AXIS M50 CLEAR DOME COVER A	Spare part AXIS M50 dome casing cover in white. Included in AXIS M5054/55/65 cameras.	165	190	75
AXIS M501X DOME	Spare part AXIS M501X dome, pre-mounted in the white top casing. Opening tool and gasket are included.	165	240	80
AXIS M55 CLEAR DOME A	Spare part clear dome in polycarbonate. IK09 vandal resistant. Compatible with AXIS M5525-E. Single pack.	170	175	50
SPR AXIS P3346-V DOME KIT	Dome kit for AXIS P3346-V, P3367-V and AXIS P3384-V as spare part. Includes a clear bubble, mounted on a zinc alloy dome cover and a separate smoked bubble.	190	250	105
SPR AXIS P3346-VE DOME KIT	Dome Kit for AXIS P3346-VE, P3367-VE, AXIS P3384-VE as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	190	250	105
AXIS P33 SEMI-SMOKED DOME A 4PCS	Semi-smoked dome with anti-scratch hard coating for indoor and outdoor AXIS P337X-LV/-LVE cameras. 4x domes per pack.	130	140	90
AXIS P33 CLEAR DOME A 4PCS	Clear dome with anti-scratch hard coating for indoor and outdoor AXIS P337X-V/-VE cameras. 4x domes per pack.	130	140	90
SPR TOP COVER AXIS P39-R 10 PCS	Original top cover including dome and screws for AXIS P39-R Series. 10 pieces.	280	255	135
AXIS P54 CLEAR DOME	Clear dome for AXIS P54-series.	190	190	110
AXIS P5512-E DOME KIT	Dome kit for AXIS P5512-E, 5514-E, 5515-E. Clear-/smoked dome and dome cover included.	280	255	135
AXIS TP3809 DOME COVER WHITE 4P	4 pack white dome cover for AXIS P3925-R. Replaces the standard white dome cover.	282	192	199
AXIS TQ6803 HARD-COATED CLEAR DOME	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS Q61-LE cameras. Weather-resistant and chemical-resistant. Rubber gasket included. Single pack.	190	185	120
AXIS TQ6806 HARD-COATED CLEAR DOME	Hard coated clear dome spare part for Q6100-E.	425	440	85
AXIS TQ6809 HARD COATED CLEAR DOME	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q60-E cameras. Weather-resistant and chemical-resistant. Rubber gasket, ring compass, ring support included. Single pack.	235	230	135
AXIS TQ6810 HARD COATED CLEAR DOME	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q6074, 75, 78-E cameras. Weather-resistant and chemical-resistant. Replacement dome only.	120	185	185
AXIS TM3810-E DOME CLEAR 4P	Spare part aspheric clear dome for AXIS M4308-PLV. Includes gasket.	120	120	95
AXIS TQ9801 CLEAR DOME	TQ9801 CLEAR DOME spare part for Q9216-SLV.	170	160	45
AXIS TP5801-E Clear Dome	Clear dome for AXIS P56 Series cameras. Hard-coated clear dome for harsh environments. It's weather-resistant and chemical-resistant.	220	233	105
AXIS Q3505-V CLEAR DOME 5P	Standard clear domes for AXIS Q35-V Series, 5 pcs	130	130	190

AXIS Q35 CLEAR DOME A 5PCS	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q3517-LV/LVE. 5x domes per pack.	160	670	85
AXIS Q3505-VE CLEAR DOME 5P	Standard clear dome for AXIS Q3505-VE. 5pcs	130	130	190
AXIS Q36-VE CLEAR DOME	Standard clear dome with anti-scratch hard coating. Compatible with AXIS P38 and Q36 Series.	190	185	120
AXIS Q37 CLEAR DOME A	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q3708-PVE and Q3709-PVE. Single pack.	190	185	120
AXIS Q6000-E CLEAR DOME	Clear dome for AXIS Q6000-E	425	435	90
AXIS Q603X HD DOME KIT	HD optimized dome kit for AXIS Q603X as spare part. Includes a clear bubble mounted on dome ring and a separate smoked bubble.	290	290	230
AXIS Q3517-SLVE CLEAR DOME 2P	Original clear dome in polycarbonate with anti-scratch hard coating. IK10+ vandal-resistant and high chemical resistance. Compatible with AXIS Q3517-SLVE. 2x domes per pack.	160	160	200
AXIS Q60-S CLEAR DOME A	Original clear dome in a special nylon blend with superior stress and chemical resistance. Compatible with AXIS Q604x-S and Q6055-S, Q6075-S, Q6075-SE cameras. Single-pack.	190	250	105
AXIS A8105-E CLEAR DOME 5PCS	AXIS A8105-E Clear Dome is sold as spare parts to the AXIS A8105-E Network Video Door Station and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	105	155	35
AXIS TP3801 WHITE CASING 4P	Original white casing for selected AXIS P32 indoor cameras. 4pcs bulk pack.	160	212	158
AXIS TP3801-E WHITE CASING 4P	Original white casing for selected AXIS M32 and P32 outdoor cameras. Pre-assembled with anti-loss screws. 4pcs bulk pack.	160	212	158
AXIS TP3802 CLEAR DOME 4P	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS P32 indoor cameras. 4pcs bulk pack.	194	294	70
AXIS TP3802-E CLEAR DOME 4P	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS M32 and P32 outdoor cameras. 4pcs bulk pack.	194	294	70
AXIS TP3803-E CLEAR DOME	This is a spare part clear dome for AXIS P3715-PLVE.	140	230	90
AXIS TP3807 DOME COVER WHITE 4P	4 pack white dome cover for AXIS P3935-LR. Replaces the standard white dome cover.	282	192	199
AXIS TP3823-E WEATHERSHIELD 2P	Outdoor spare part weathershield for AXIS P3265-LVE, P3267-LVE, P3268-LVE. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Anti-loss screws included. Bulk 2 pack.	135	204	74
AXIS TP3820 CASING WHITE 4P	Original spare part white casing for AXIS P3265-LV, P3265-V indoor cameras. 4pcs bulk pack.	160	212	158
AXIS TP3820-E CASING WHITE 4P	Original spare part white casing for AXIS P3265-LVE 9 mm outdoor camera. Pre-assembled with anti-loss screws. 4pcs bulk pack.	160	212	158
AXIS TP3821-E CASING WHITE 4P	Original white spare part casing for AXIS P3265-LVE 22 mm, P3267-LV, P3267-LVE, P3268-LV, P3268-LVE outdoor cameras. 4pcs bulk pack.	160	212	158
AXIS TP3824-E DOME CLEAR 4P	Spare part clear dome with anti-scratch hard coating. Compatible with AXIS P3265-LVE 22 mm, P3267-LV, P3267-LVE, P3268-LV, P3268-LVE. 4pcs bulk pack.	295	294	74

AXIS TP3812-E TOP CASING	Complete spare part top casing for AXIS P3925-LRE including aluminum top casing with tempered glass window with antireflective coating, heater, connector board, screws and re-painting window mask.	168	140	95
AXIS TP3002-E MOUNTING BRACKET 4P	Spare part mounting bracket for AXIS P3267-LV, P3268-LV. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	145	145	82
AXIS TP3003-E MOUNTING BRACKET 4P	Spare part mounting bracket for AXIS P3265-LVE 22 mm, P3267-LVE, P3268-LVE. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	200	205	165
AXIS TP3815-E CLEAR DOME COVER	Clear dome spare part for AXIS P3717-PLE, AXIS P3719-PLE, AXIS P3727-PLE. The dome and the casing are included.	115	320	340
AXIS TQ3802-E COVER WEATHERSHIELD	Cover weathershield for P3818-PVE. Includes anti loss screws.	190	200	80
AXIS TQ3803-E COVER TOP	Cover top replacement for Q3819-PVE including anti loss screws and holder magnet.	210	230	95
AXIS TQ3001-E MOUNTING BRACKET 5P	Spare part mounting bracket in 5p for AXIS Q3536-LVE, AXIS Q3538-LVE.	185	188	190
AXIS TQ3807-E DOME CLEAR 5P	Spare part clear dome for AXIS Q3536-LVE, AXIS Q3538-LVE in a 5p (anti-scratch hard coating).	275	380	100
AXIS TQ3808-E WEATHERSHIELD 5P	Spare part weathershield in a 5p for AXIS Q3536-LVE, AXIS Q3538-LVE. Anti loss screws and gasket included.	133	280	25
AXIS TM5801 DOME COVER WHITE	Spare part white dome cover for AXIS M5000 & AXIS M5000-G. Includes dome and cover, 4 SCREW TX+ 8 DOME FLANGE, and 2 spring clips.	255	265	157
AXIS TM3818 CASING WHITE 4p	4 pack spare part white casing replacing original out of the box. Compatible with M3085-V, M3086-V, M3088-V.	135	140	135
AXIS TM3815-E DOME CLEAR 4P	Standard clear dome spare part replacing original out of the box with anti-scratch hard coating. Compatible with: AXIS M3215-LVE, AXIS M3216-LVE. 4pcs bulk pack.	295	295	70
AXIS TP3819-E DOME CLEAR	AXIS TP3819-E Dome Clear, is spare part clear dome for AXIS P4705-PLVE and P4707-PLVE.	120	200	65
AXIS TP3825-E WEATHERSHIELD WHITE	AXIS TP3825-E Weathershield White, is a spare part (white) weathershield for AXIS P4705-PLVE and P4707-PLVE.	170	240	80
AXIS TQ3809-E Dome Clear	Spare part standard clear dome with anti-scratch hard coating. Compatible with Q3626/8-VE.	145	145	95
AXIS TM3821 CASING WHITE 4P	Spare part original white casings for AXIS M42 series. Easy to repaint. 4-piece bulk pack.	130	135	135
AXIS TM3819 CASING WHITE 4P	Spare cover top casing white for AXIS M4327-P and AXIS M4328-P. Comes in 4 Pack.	150	110	110
AXIS TI8903 Clear Dome 5P	AXIS TI8903 Clear Dome is sold as spare parts to the AXIS I8116-E Network Video Intercom and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	100	145	35
AXIS TP5802-E DOME CLEAR	Clear dome spare for AXIS P5676-LE. Hard-coated clear dome for harsh environments. It's weather-resistant and chemical-resistant.	185	185	125
AXIS TP3831-E Dome Cover Clear	Spare part clear dome for: AXIS P3735-PLE, AXIS P3737-PLE, AXIS P3738-PLE. The dome and cover are included.	350	325	115

AXIS TM3822 Casing White 4 pcs	4 pack spare part white casing replacing original out of the box. Compatible with AXIS M3086-V Mic.	105	140	105
AXIS TM5804-E DOME CLEAR	Spare part clear dome in polycarbonate. IK09 vandal resistant. Compatible with AXIS M5525-E, AXIS 5526-E. Single pack. 4 anti-loss TX20 screws in pack.	170	170	100
AXIS TQ9803 Dome Clear	Spare part dome for Q9307-LV.	142	142	95
AXIS TQ9802 Casing White	Spare part casing for Q9307-LV.			
AXIS TP3834-E CASING WHITE 4 pcs	Original white spare part casing for AXIS P3267-LVE Mic. 4pcs bulk pack.	160	210	155
AXIS TP3835-E DOME CLEAR 4 pcs	Spare part clear dome with anti-scratch hard coating. Compatible with AXIS P3267-LVE Mic. 4pcs bulk pack.	295	295	75
AXIS TM3828-E Casing Black 4 pcs	Spare part 4P Black casing for M312x-LVE series.			
AXIS TM3828-E Casing White 4 pcs	Spare part 4P white casing for M312x-LVE series.			
TM5803 CLEAR DOME COVER	Spare part dome for : AXIS M5054, AXIS M5055, AXIS M5065, AXIS M5074, AXIS M5075, AXIS M5075-G.			
ACC ALLEN-KEY M3 TAMP PROOF 10PACK	Allen-key for AXIS 209FD-R 10-pack	145	230	5
AXIS D20 MOUNT BRACKET KIT A	Original stainless steel mounting bracket for AXIS D2050-VE. Includes two pipe adapters, anti-loss screws, two gray cable gaskets, three black cable gaskets, and an M20 cable gland.	280	180	55
AXIS Q604X RECESSED MOUNT	Spare part indoor recessed mount for mounting AXIS Q60 indoor cameras in drop ceilings.	280	275	56
AXIS F82A06 ANGLED PINHOLE MT 5PCS	Mounting bracket that allows AXIS FA1125 Sensor Unit to be mounted behind a thin metal/plastic/glass panel. 5 pcs.	107	155	35
AXIS M501X MOUNTING KIT	Original ceiling mount kit for both hard- and drop ceilings for the AXIS M501X.	165	180	40
AXIS T98A MOUNTING BRACKET	Original stainless steel mounting bracket for AXIS T98A-VE Surveillance Cabinet series.	230	350	110
AXIS STEEL STRAPS TX30 570MM 1PAIR	1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Length 570mm (22.5"). Width 14.3mm (0.57"). Thickness 0.68mm (0.03"). Compatible with a wide range of Axis pole mounts. Pole diameter range 50-150mm (2"-6") when used with AXIS T91B47 Pole Mount.	168	164	21
AXIS STEEL STRAPS TX30 1450MM 1PAIR	1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Length 1450mm (57"). Width 14.3mm (0.57"). Thickness 0.68mm (0.03"). Compatible with a wide range of Axis pole mounts. Pole diameter range 100-410mm (4"-16") when used with AXIS T91B47 Pole Mount.	168	164	21
STAINLESS STEEL STRAPS 1450MM 1 PAIR	Original stainless steel straps for AXIS T91A47 110-400 mm. The straps also fit the AXIS T91A67. Mounting tool (P/N 21776) is required.	210	255	20
AXIS T94B02S MOUNTING BRACKET 5P	Spare part mounting brackets for AXIS M20 Series, 5-pack. Includes 5x mounting brackets with 5x Gasket C M20.	110	215	100
AXIS T94F01S MOUNTING BRACKET	Standard mount bracket for AXIS M3006-V, AXIS M3007-P/-PV, AXIS M3024-LVE/3025-VE/3026-VE	165	180	40
AXIS T94G01S MOUNTING PLATE	Sparepart mounting bracket for AXIS Q1765-LE, Q1931-E, Q1932-E	165	180	40
AXIS T94M01S MOUNTING BRACKET 4P	Sparepart mounting bracket for AXIS Q3505-VE. 4 pcs	230	115	350
AXIS T94S01S MOUNTING BRACKET 4P	Sparepart mounting bracket for AXIS P32-V Series. 4 pcs	165	190	75

AXIS T94T02S MOUNTING BRACKET	Spare part mounting brackets for AXIS M3057/58-PLVE, single pack. Includes spring clips for ease-of-installation.	180	165	45
AXIS T94V01S MOUNTING BRACKET	Standard mounting bracket for AXIS Q36 Series Network Cameras.	180	190	205
AXIS 3/4" CONDUIT LOCKNUT A 4P	4-pack of 3/4" conduit locknut. Suitable for AXIS T91B53 Telescopic Ceiling Mount.	65	60	37
AXIS T94U02S MOUNTING BRACKET	Standard mounting bracket for AXIS Q3505-SVE made of stainless steel. Including gasket.	210	210	210
AXIS TP3001 MOUNTING BRACKET 4P	Spare part mounting bracket for selected AXIS M32 and P32 cameras. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	145	145	82
AXIS TP3001-E MOUNTING BRACKET 4P	Spare part mounting bracket for selected AXIS P32 outdoor cameras. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	200	205	165
AXIS TQ3902 MOUNT BRACKET	Mount bracket for Q3819-PVE. Includes conduit lid to cover conduit entry not used.	320	210	100
AXIS TM2801 WEATHER SHIELD KIT	Spare part weather shield for AXIS M2035-LE and M2036-LE. Includes cover and holder.	143	230	63
AXIS TM1001 Wall Mount 5 pcs	5 pack spare part wall mount for: AXIS M1055-L and AXIS M1075-L.	160	240	80
AXIS TQ3002-E Mounting Bracket	Spare part standard mounting bracket for AXIS Q3626/8-VE Network Cameras.	195	180	65
AXIS P91 CLEAR DOME A 2P	Standard clear dome with anti-scratch hard coating. Rubber gaskets included. Compatible with AXIS P9106-V. 2-piece bulk pack.	120	130	95
AXIS P91 SKIN COVER A BRUSHED STEEL	Spare part skin cover for AXIS P9106-V. Brushed stainless steel finish. Easy to repaint. Magnetically attached. Suitable for both AXIS P9106-V White and Brushed Steel models.	160	180	110
RJ12 PLUG SHIELDED 10 PCS	Shielded RJ12 connectors for use with AXIS modular cameras. 10-pack.	165	180	40
ACC MAINS ADAPTOR PS-P	Power supply PS-P for AXIS 215 PTZ	165	240	80
AXIS MAINS ADAPTER 12V DC 40W	Standard power supply for AXIS FA54. IEC-C13 mains cable is not included.	165	180	45
AXIS MAINS ADAPTER 48V DC 90W	Standard power supply for AXIS S3008 and AXIS Companion Recorder. IEC-C13 mains cable is not included. This adapter is not compatible with AXIS S3008 Mk II or AXIS W800.	165	180	45
MAINS CABLE IEC-C13	Mains cable for AXIS One-Port Midspan, AXIS T8123/24, AXIS 291, AXIS Q7900, AXIS Video Server Rack, AXIS PoE Midspan 8-Port/16-Port, Power Supply AXIS T8412.	200	150	50
AXIS PATCH CABLE A 200MM 6PCS	Set of patch cables for AXIS T8085 PS57 RACK MOUNT 500W 1U to connect AXIS T8646 POE+ OVER COAX BLADE	105	280	15
CABLE GLAND A M16 5PCS	M16 cable gland for cable diameter of 4.5 to 10mm. IP68. 5 pcs.	100	170	2
CONN KIT AXIS P1311	Kit for the AXIS P13XX-series. Content: one terminal connector 4P str 250mm BP LF and one 2P STR 3.81MM BP LF.	60	80	10
CONN KIT AXIS Q7404	Terminal connectors for AXIS Q7404. Includes 8 pcs 2P 2.50MM, 4 pcs 4P 2.50MM and one 2P 3.81MM. In total 13 connectors.	63	95	20
AXIS TM3807 WHITE CASING 4P	AXIS M3115/16-LVE WHITE CASING 4P sold as a spare part and comes in pack of four. It enables easy on-site replacement in case the original case has been damaged.	175	225	110
LENS M12 2.8MM F2.0 10PCS	Standard lens for AXIS F4005-E, AXIS F1005-E and AXIS P1214-E.	165	240	85
AXIS T93F TOP COVER	Spare part top part of the housing including window.	130	160	390

LENS CS 2.8-8MM F1.2 DC-I MP	CS mounted Varifocal 2.8-8 mm DC-iris megapixel lens. Original lens for AXIS M1114.	120	130	95
LENS CS VF 2.8-8MM F1.2 P-IRIS	Original CS mounted varifocal P-Iris lens 2.8-8mm for AXIS Q1604/14 and AXIS P1355/57	120	130	95
LENS CS VF 2.8-8MM F1.2 DC-IR	Original CS mounted varifocal DC-Iris lens 2.8-8mm for AXIS Q1602/04 and AXIS P1354/55	120	130	95
AXIS LENS FUJINON CS 2.8-8MM P-IRIS	Standard CS mounted varifocal P-Iris lens 2.8-8mm for AXIS Q1615.	120	130	95
LENS CS 2.8-8.5MM P-IRIS	Standard CS mounted varifocal P-Iris lens 2.8-8.5mm for AXIS P1364.	120	130	95
LENS CS 2.9-8.2MM F1.4 DC SVGA	Varifocal 2.9-8.2mm CS mounted SVGA DC-iris lens. Original lens for AXIS M1113	120	130	95
LENS CS 4-10MM P-IRIS	Standard lens for AXIS Q1635-E.	120	130	95
AXIS LENS TAMRON C 4-13MM DC-IRIS	Standard C mounted varifocal DC-Iris lens 4-13mm for AXIS Q1635.	120	130	95
TAMRON 5MP LENS P-IRIS 8-50 MM F1.6	Varifocal 8-50 MM, 5 MP telephoto IR-corrected lens with P-Iris. Recommended for AXIS P1367 and AXIS P1367-E.	120	130	95
LENS CS 2.8 - 10 MM F1.2 P-IRIS 2MP	Lens CS-mount 2.8 - 10 mm. F1.2 P-IRIS 2MP resolution Computar. Spare part for AXIS P1375 / -E	90	120	120
LENS M12 2.8 MM F1.6 IR 10P	Standard lens for AXIS P3925-R and AXIS P3935-LR. 10 pack.	163	240	77
LENS M12 2.9MM F2.0 1P	LENS M12 2.9MM F2.0 for Q6010-E and Q6100-E.	165	180	45
LENS CS 3.9 - 10 MM F1.5 P-IRIS 8MP	Spare varifocal CS lens for AXIS P1378/-LE.	120	120	90
AXIS Q872x-E SUNSHIELD KIT	Sunshield for AXIS Q872x-E as sparepart. Including screws and washer	290	850	280
SPR BRACKET KIT AXIS Q60XX/P55XX	Bracket kit for surface mounting a camera on a hard ceiling. Compatible with Q603X and P553X. Content: Bracket, screws with washers and wave springs.	165	180	40
SPR CONN KIT AXIS Q7401	Connectors for AXIS Q7410 as spare parts. Includes two 2pin STR 2.50MM, one 6pin STR 2.50MM and one 2pin STR 3.81MM. In total 4 connectors.	100	60	10
SPR CONN PUSH PULL PLUG IDC-8 IP67	Spare RJ45 connector plug for AXIS Q603X-E & AXIS P55XX-E. IP67 rated.	150	200	2
NETWORK CABLE WITH GASKET 5M	Shielded outdoor network cable 5 meter. Pre mounted rubber gasket and male RJ45 connectors. For use with AXIS M11-E series, AXIS P13-E series, AXIS Q16-E series, AXIS Q1755-E, AXIS Q19-E series, AXIS P33-VE series and AXIS T92/3-E housings.	200	300	20
AXIS T91G61/T91L61 SCREW KIT	Screw kit for installing AXIS P55-E Series with either AXIS T91L61 or AXIS T91G61 Wall Mounts. Single-pack includes 3x bayonet screws, 3x securing screws, 3x springs and an installation guide.	100	150	50
AXIS P5544 LENS KIT	Spare part lens kit for AXIS P5544	250	250	210
AXIS T96B05 FRONT KIT 5 PCS	Spare part window and window holder for AXIS T96B05 Outdoor Housing and AXIS P3905-RE. 5 Pcs. Includes screws.	165	240	80
AXIS Q60XX-C COOLING MODULE	Peltier element, inside and outside fan for AXIS Q60XX-C	165	240	80
AXIS T8005 POWER SUPPLY 5V 5W USB	Switching power supply, 5W with microUSB connector. Including interchangeable regional power plugs for world wide use.	165	180	45
SPR POWER SUPPLY 1U 300W BL. FRONT	Replacement power supply for AXIS Q7920 Video Encoder Chassis	210	325	100
AXIS T93G TOP COVER	Spare part top part of the AXIS T93G housing including window.	295	490	155
AXIS T92G FRONT WINDOW KIT A	Replacement front window assembly for AXIS T92G Outdoor Housing and AXIS Q16-LE Fixed Box Cameras. Includes front window, adjacent IR windows, mounting screws and sealing gasket.	150	210	75

AXIS T92G WEATHERSHIELD KIT A	Original outdoor weathershield for AXIS T92G Outdoor Housing and AXIS Q16-LE cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from IR LEDs and other light source. Mounting screws included.	225	490	155
AXIS T92G20 CAMERA HOLDER	Spare Camera Holder for AXIS T92G20 Outdoor Housing and for AXIS Q1645/7-LE Network Cameras. The holder makes it possible to mount AXIS P13 Network Camera Series into AXIS T92G20 Outdoor Housing.	190	185	120
AXIS SUNSHIELD B	Sunshield compatible with AXIS Q1765-LE, Q1931-E/32-E/41-E and Q2901-E	120	225	55
SUNSHIELD AXIS Q603X-E	Sunshield for AXIS Q603X-E.	310	275	210
AXIS Q6010-E Solo kit	Kit for making a stand-alone AXIS Q6010-E installation without PTZ camera inside. Includes a metal cover lid, IP66-rated RJ45 push-pull connector, and a connector plug. Use this kit together with an AXIS Q6010-E network camera (not included) and the AXIS T8133 Midspan 30 W 1-port (not included).	275	280	57
AXIS Q62 IMPACT PROTECTION BRACKET	Protection of front window on AXIS Q62-LE camera. Provides IK10 rating on product. Includes bracket and mounting screws.	105	155	30
AXIS Q62 FRONT WINDOW KIT A	Original front window assembly for AXIS Q6215-LE, IK09 rated. Includes a complete front window glass assembly with mounting screws and sealing gasket; and a wiper arm (long-life, UV-resistant silicone rubber included). Note: IR window available separately.	115	115	40
AXIS Q62 WIPER KIT A 4P	Bulk pack (4 pcs) of replacement wiper arms (rubber included) for AXIS Q62-LE. Made from long-life, UV-resistant silicone rubber.	115	115	40
AXIS Q62 IR WINDOW KIT A	Original IR window assembly for AXIS Q62-LE. Includes a complete IR Window assembly with mounting screws and sealing gasket. Note: clear front window available separately.	115	115	40
SUNSHIELD KIT T92E	Sunshield for AXIS P134X-E, AXIS Q1755-E and AXIS Q192X-E. Includes mounting screws and Torx key.	195	520	195
AXIS WEATHERSHIELD KIT D	Weathershield with screws for protecting the dome of an AXIS Q35-VE camera from rain, snow and sun.	165	190	75
AXIS WEATHERSHIELD KIT E	Weathershield with screws for protecting the dome of an AXIS P32-VE camera from rain, snow and sun.	120	130	95
AXIS TP3805 WEATHERSHIELD 2P	Outdoor weathershield for selected AXIS M32 and P32 cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Anti-loss screws included. Bulk 2 pack.	135	204	74
AXIS TP3904 CLAMP BRACKET MOUNT	Replacement clamp bracket mount for AXIS P3717-PLE, AXIS P3719-PLE and AXIS P3727-PLE. Pack of 10pcs.	83	125	40
FRONT GLASS KIT AXIS T92E20/21	Complete Front Kit for AXIS T92E20/21. Content: Front Cover, Front Glass, Gasket & Screws.	165	180	40
ELECTRONIC KIT AXIS T92E20	Sparepart including the electronics module of the AXIS T92E20 housing including fan and screws.	165	418	93
AXIS T92E EXTENSION KIT	Extension front for AXIS T92E20 outdoor housing, allowing longer lenses than the standard housing. The kit includes aluminum front and extension part, window, gasket and screws.	165	180	45

AXIS P13 WEATHERSHIELD KIT A	Standard weather shield for selected AXIS P13 series. For protection from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use near IR LEDs.	165	420	75
AXIS P13-E TOP COVER A	Replacement top cover with front window for selected AXIS P13-E cameras. Original weathershield is not included but available separately.	155	380	130
AXIS P14 WEATHERSHIELD A	Standard weather shield for selected AXIS P14 series. For protection from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use with camera's built-in IR LEDs.	105	260	60
AXIS TP1801-E Front Window Kit	Standard front window kit for selected AXIS P145x-LE series. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.	127	145	75
AXIS TP1802-E Front Window Kit 29mm	Spare part front window kit for AXIS P1455-LE 29 mm and AXIS P1455-LE-3. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.			
AXIS Q17 FRONT WINDOW KIT A	Original front glass window assembly for AXIS Q1785/86-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	180	160	30
AXIS Q17 FRONT WINDOW KIT C	Original front glass window assembly for AXIS Q1700-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	160	170	40
AXIS Q1798-LE WEATHERSHIELD	Original outdoor weathershield for AXIS Q1700-LE camera. Color: Black	310	180	150
AXIS Q1765-LE FRONT KIT	Spare part front window for AXIS Q1765-LE	165	180	40
AXIS T98A05 CABINET DOOR	Cabinet door for AXIS T98A Surveillance Cabinet. Stand alone. Used in T98A15-VE Cabinets.	370	320	60
AXIS T98A06 CABINET DOOR	Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS M111X-E, AXIS P13XX-E, AXIS Q16XX-E, AXIS Q17XX-E, AXIS Q191X-E, AXIS Q192X-E. Used in T98A16-VE Cabinets.	370	320	60
AXIS T98A07 CABINET DOOR	Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS P33-VE/-LVE and the outdoor bullet-style Q1765 and Q1931 cameras. Used in T98A17-VE Cabinets.	370	320	60
AXIS T98A08 CABINET DOOR	Cabinet door for T98A. Compatible products: AXIS T91A61 Wall bracket for use with AXIS P55 and Q60-series or fixed dome pendant kits. Used in T98A18-VE Cabinets.	370	320	60
AXIS P135X CONN KIT	Terminal connectors for AXIS P135X-series. Includes 1 pcs TERMINAL CONNECTOR 4P STR 2.50MM, 1 pcs TERMINAL CONNECTOR 2P STR 3.81MM, 2 pcs TERMINAL CONNECTOR 2P STR 2.50MM	62	100	10
AXIS T8123/4-E MIDSPAN SPARE KIT	2pcs RJ-45 waterproof plugs and 1pcs grounding wire for outdoor midspan T8123/4-E	70	110	21
FRONT KIT 60MM AXIS Q872X-E	Frontkit for AXIS Q872X-E with 60mm lens as spare part.	255	160	53
FRONT KIT 35MM AXIS Q872X-E	Frontkit for AXIS Q872X-E with 30mm lens as spare part	255	160	53
PT IR ILLUMINATOR KIT B	Spare part illuminator kit for AXIS Q8665-LE. NOTE: it is not possible to upgrade a Q8665-E to become LE version	310	525	225

AXIS Q86 FRONT KIT A	Replacement front window assembly for AXIS Q8685-E/-LE. Window in clear tempered glass. Includes built-in heater, wiper mechanism, and heat sink.	127	160	100
AXIS Q86 WIPER KIT A 5P	Replacement wiper blades for selected AXIS Q86, Q87 and Q1656 outdoor cameras. Made from long-life, UV-resistant silicone rubber. 5pcs per pack.	107	152	34
AXIS Q86-E LIGHT SENSOR BOX 230 V	Light sensor box with integrated power supply for controlling IR illuminators and power AXIS Q8665-LE. Input power 230V AC.	430	430	190
AXIS Q8665-LE BASE UNIT 24V AC	Spare part base unit for AXIS Q86-LE 24 V AC.	140	260	200
AXIS Q8665-E BASE UNIT 230V	AXIS Q8665-E BASE UNIT 230 V AC	140	260	200
AXIS Q8631-E/32-E HOUSING TOP	Spare part top housing with germanium window for AXIS Q8631-E/32-E.	195	530	150
AXIS Q8665 HOUSING TOP	Spare part top housing with glass window for AXIS Q8665-E/-LE.	195	530	145
AXIS Q8631/32/65 SUNSHIELD	Spare parte sunshield for AXIS Q8631-E/32-E/65-E/65-LE	195	530	145
AXIS Q8665 WIPER	Spare part wiper blade for AXIS Q8665-E/-LE including the stainless steel holder	83	110	53
AXIS Q8721-E/22-E BASE	Base assembly for the AXIS Q8721-E/22-E.	260	140	200
AXIS TM1802 TOP COVER KIT	Replacement top cover with front window for selected AXIS M11-E cameras. Original weathershield included.	360	260	150
AXIS WEATHERSHIELD S	Weathershield from UV-resistant plastics for protecting camera against rain, snow and sun.	270	385	120
AXIS CONNECTOR A 2P2.5 STR 10PCS	Axis male connector for legacy IO port . Pitch: 2.50 mm. 2pos terminal block. 10pack.	100	60	10
AXIS CONNECTOR A 4P2.5 STR 10PCS	Axis male connector for limited and full IO port . Pitch: 2.50 mm. 4pos terminal block. 10pack.	62	100	10
AXIS CONNECTOR A 6P2.5 STR 10PCS	Axis male connector for extended IO port . Pitch: 2.50 mm. 6pos terminal block. 10pack	100	60	10
AXIS CONNECTOR A 2P3.81 STR 10PCS	Axis male connector for low voltage power. Pitch: 3.81 mm. 2pos terminal block. 10pack	100	60	10
AXIS CONNECTOR A 3P3.81 STR 10PCS	Axis male connector for low voltage power. Pitch: 3.81 mm. 3pos terminal block. 10pack	60	95	10
AXIS CONN A 4P3.81 STR IN/OUT 10P	Axis male connector for audio. Pitch: 3.81 mm. 2+2pos terminal block. 10pack	100	175	20
AXIS CONNECTOR A 4P3.81 STR 10PCS	Axis male connector for low voltage power. Pitch: 3.81 mm. 4pos terminal block. 10pack	100	170	2
AXIS CONNECTOR A 2P5.08 STR 10PCS	Axis male connector for low voltage power. Pitch: 5.08 mm. 2pos terminal block. 10pack	70	120	12
SPR 5 PORT GB ETHERNET SWITCH KIT	Spare part internal switch for the AXIS Q8721-E/22-E Dual cameras,including brackets.	165	240	80
AXIS Q1765 FOOT CHASSIS	Sparepart foot chassis for AXIS Q1765-LE and AXIS Q193X-E. Note. This sales part does not include the mounting bracket (5506-081 AXIS T94G01S Mounting plate)	165	180	40
AXIS ADAPTER RJ45 MALE TO MALE	Adapter for connecting Q6000-E to PTZ camera	120	175	35
AXIS ACI CONDUIT COVER A 10PCS	Spare part plastic side covers for compatible AXIS T91- and AXIS T94- series of mounting accessories. 10 pcs per pack.	380	130	80
AXIS Q60 PCB POWER REPAIR BOARD A	Replacement PCB power board for AXIS Q6032, Q6034, Q6035, Q6042, Q6044, Q6045, Q6054 and Q6055	165	180	45
AXIS Q60-E PCB POWER REPAIR BOARD A	Replacement PCB power board for AXIS Q6032-E, Q6034-E, Q6035-E, Q6042-E, Q6044-E, Q6045-E, Q6054-E and Q6055-E	165	180	45
AXIS TP1903 PCBA Housing T92	Sparepart including the electronics module of the AXIS T92G20 housing.	80	135	27
AXIS TP3903-E FRONT WINDOW	Spare part front window kit for AXIS P3925-LRE including tempered glass window with anti-reflective coating, gasket and window holder bracket screws.	162	235	78

AXIS TP3811 Weathershield	Spare part original outdoor weathershield for AXIS P3715-PLVE. The underside of the cover is specially coated with black anti-reflective coating to prevent reflections from external light sources. Includes gasket and anti-loss screw.	165	240	85
AXIS TQ1801 WEATHERSHIELD	Original outdoor weathershield for AXIS Q1785/86-LE cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Includes weathershield slider and anti-loss screw.	305	210	80
AXIS TQ1802 WEATHERSHIELD	KIT WEATHER SHIELD spare part Q1700-LE E1.	160	160	140
AXIS TQ1803 FRONT WINDOW KIT	Original front glass window assembly for AXIS Q1700-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	170	170	20
AXIS TQ1804-E TOP COVER WITH WIPER	Spare top cover including wiper for AXIS Q1656-LE, AXIS Q1656-BLE	210	560	220
AXIS TQ1804-BE TOP COVER	Spare top cover for AXIS Q1656-BE. No wiper	210	560	220
AXIS TQ1806 WEATHERSHIELD	KIT WEATHER SHIELD spare part for Q1785, 6 – LE, and Q1798-LE. Additional ring for Q1798-LE.	160	160	150
AXIS TQ1810-E FRONT KIT	Replacement front kit for AXIS Q1951-E, AXIS Q1952-E. Includes window in germanium, heater, cover and gasket.	140	100	60
AXIS TQ1906-E FRONT WINDOW KIT	Spare front glass window for AXIS Q1656-LE and AXIS Q1656-BLE. Support for wiper	130	160	35
AXIS TQ1907-E FRONT WINDOW KIT	Spare front plastic window for AXIS Q1656-BE. No support for wiper	130	160	35
AXIS TQ6902-E WEATHER SHIELD	Spare part weather shield for Q6315-LE. Includes anti loss screws	246	250	50
AXIS TQ6808-E HARD-COAT CLEAR DOME	Spare part hard coated clear dome for Q6315-LE. Standard clear dome with anti-scratch hard coating. Includes dome ring, cover IR block.	202	202	137
AXIS TQ8809-E WIPER KIT	Replacement wiper kit with wiper arm (rubber included) for AXIS Q8752-E. Made from long-life, UV-resistant silicone rubber. For a front window. It includes a wiper arm with four blades for an easy replacement.	105	153	40
AXIS TI8902 GLASS REPLACEMENT KIT	Glass replacement kit sold as a spare part to AXIS I8016-LVE Network Video Intercom. It enables easy on-site replacement in case the original cover has been damaged or vandalized.	105	150	35
LENS I-CS 1/1.8" 3.9-10 mm F1.5	Spare varifocal i-CS lens for AXIS Q1656, AXIS Q1656-LE, EXCAM XF Q1645, EXCAM XF P1377 and F101-A XF P1377. Also compatible with AXIS Q1645/-LE and AXIS Q1647/-LE	125	130	95
LENS CS 4-10MM F0.9	Optional extremely light-sensitive lens. CS-Mount 4-10 mm F0.9 with P-Iris. IR-corrected. Compatible with AXIS Q1656/-B/-BE/-BLE and AXIS P1375/-E, AXIS P1377/-LE.	120	130	95
AXIS TM2001 MOUNT BRACKET	Spare part mounting bracket for AXIS M2035-LE, M2036-LE. Includes a mounting bracket and gasket for cable.	143	230	63
AXIS TM2802 FRONT KIT A	Spare part front window assembly for AXIS M2035-LE, M2036-LE. The kit comes with a black front cover ring. Includes a window assembly kit (light guide IR filter, window gasket).	143	230	63

AXIS TQ1807-VE CABINET DOOR	Spare part cabinet door for AXIS TQ1808-VE Surveillance Cabinet. Stand alone. Can be used with any T98A surveillance cabinets if the front door wants to be replaced with a bigger front door that will allow for more components to be placed in them. Back box has had no changes.	295	400	155
AXIS TQ6812-E Solo Kit	Kit for making a stand-alone AXIS Q6100-E installation without PTZ camera inside. Includes a thermo plastic cover lid, IP66-rated RJ45 push-pull connector, and a connector plug. Use this kit together with an AXIS Q6100-E network camera (not included) and the AXIS High PoE Midspan 60 W (not included).	205	220	45
AXIS TP3828-E Dome Cover White	AXIS TP3818-E Dome Cover White, is a spare part kit including a white casing, clear dome and screws for AXIS P4705-PLVE and P4707-PLVE.	140	230	95
LENS M12 2MM F2.0	Lens M12 2mm F2.0 is a bulk pack of 4p replacement lenses for AXIS F2135-RE Fisheye lenses.	105	150	35
LENS M12 3.1MM F2.0	Lens M12 3.1mm F2.0 is a bulk pack of 4x replacement lenses for AXIS F2105-RE standard sensor.	105	150	35
AXIS TP1803-E Front Window Kit	Spare part front window kit for AXIS P1467-LE and AXIS P1468-LE. Abrasion and UV resistant for long service life. Includes cover front, window front, and rubber window gasket.	110	170	50
AXIS TP1804-E Front Window Kit	Spare part front window kit for AXIS P1465-LE 9 mm. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.	115	115	43
AXIS TU6001 CONN 3-PIN 3.81MM 10P	AXIS TU6001 Conn 3-pin 3.81mm 10p is a bulk pack of 10x AXIS TU6001 Conn 3-pin 3.81mm. AXIS TU6001 Conn 3-pin is compatible with the 2nd generation of F-series Main units: F9111, F9114, and F9104-B and F9114-B. AXIS TU6001 Conn 3-pin 3.81mm helps connecting AXIS F91 main units to the DC power.	105	150	38
AXIS TQ8901-E Wiper Kit	Replacement wiper kit with wiper arm/blade (rubber included) for AXIS Q8615-E. Made from long-life, UV-resistant silicone rubber.	110	50	40
AXIS TQ1502-E Front Window Kit	Original front window assembly for AXIS Q62-LE, IK09 rated. Includes a complete front window glass assembly with mounting screws and sealing gasket; and a wiper arm (long-life, UV-resistant silicone rubber included). Note: IR window available separately.	115	115	40
AXIS TQ3810-E Weathershield	Spare part standard weather shield for Axis Q3626/8-VE, protecting the dome from rain, snow and sun.	180	270	80
LENS I-CS 3.5-10 MM F1.8	Spare i-CS lens for AXIS M1135/-E MK II i-CS and AXIS M1137/-E MK II i-CS	85	120	60
AXIS TP3907 Clamp Bracket Mount 10P	10 pack spare part clamp bracket mount. Compatible with: AXIS P3735-PLE, AXIS P3737-PLE, AXIS P3738-PLE.	125	80	40
AXIS TS3902 RAIL KIT	AXIS TS3902 RAIL KIT is a full rail kit compatible with AXIS S3016 Recorder only. It allows the product to be mounted in server racks with a post to post distance between 376mm (14.8in) and 499mm (19.6in). The rail kit is not compatible with other products such as AXIS S12 Recording Server Series or AXIS S22 Appliance Series.	63	475	62

AXIS Mains Adapter 48V DC 180W	Standard power supply for AXIS S3008 Mk II. IEC-C13 mains cable is not included. This adapter is not compatible with AXIS S3008 or AXIS W800.	165	240	80
AXIS TQ1929-E Front Window Kit	Spare part front window kit compatible with AXIS Q1805-LE, AXIS Q1806-LE. Includes 4 TX10 screws and window assembly.	115	115	25
AXIS TQ1931-E Front Window Kit	Spare part compatible with: AXIS Q1808-LE 150 mm. Includes 4 TX10 screws, window assembly including gasket and window IR.	115	115	25
AXIS TQ1933-E Front Window Kit	Spare part compatible with AXIS Q1808-LE. Includes 4 TX10 screws and window assembly.	115	115	25
AXIS TQ1934-E Weathershield	Spare part weathershield compatible with: AXIS Q1805-LE, AXIS Q1806-LE, AXIS Q1808-LE 150 mm. Including holder, anti loss screws, and cover.	270	130	70
AXIS TQ1935-E Weathershield	Spare part weathershield compatible with: AXIS Q1808-LE. Including holder, anti loss screws, and cover.	270	130	70
AXIS TM5901-E Adapter	Spare part ADAPTER BAYONETTE compatible with M5525-E, and M5526-E. Made of brass.	198	189	45
AXIS TP1901 Allen Key 10 pcs	A 10 pack T6 Allen Key set sold as a spare part since products it is compatible with come with it out of the box. Products compatible with: P13, Q17, Q16.	165	180	45
AXIS TI8906 Glass Replacement Kit	Glass replacement kit sold as a spare part to AXIS I7010-VE Network Intercom. It enables easy on-site replacement in case the original cover has been damaged or vandalized.	118	65	28
AXIS TQ1816-VE Cabinet Door	Spare part cabinet door for AXIS TQ1817-VE Surveillance Cabinet. Stand alone. Can be used with any T98A surveillance cabinets if the front door wants to be replaced with a bigger front door that will allow for more components to be placed in them. Back box has had no changes. Compatible with dome, fixed, thermal cameras.	400	300	150
AXIS TQ8802-E Top Cover Zoom	This is a replacement top cover assembly for AXIS Q8752-E Zoom 30 fps, AXIS Q8752-E Zoom 8.3 fps.			
AXIS TQ8801-E Top Cover 35 mm	This is a replacement top cover assembly for AXIS Q8752-E Zoom 30 fps and AXIS Q8752-E Zoom 8.3 fps.			
AXIS DEVICE MICROPHONE A	AXIS Device Microphone A is an omnidirectional microphone to enable audio recording and/or audio analytics with AXIS devices that support audio but do not include a microphone. The product is compatible with devices that support 3.5 mm audio input, like AXIS indoor Q35 series or P33 series together with AXIS TP3201 Recessed Mount.	150	110	30
AXIS T8351 MK II MICROPHONE 3.5MM	AXIS T8351 Mk II Microphone 3.5mm is an omnidirectional microphone with a 3.5mm connector, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. Flexible to install, AXIS T8351 adapts to different installation scenarios thanks to a vast range of included accessories and to its dust-and-water proof casing.	105	150	40

AXIS T8355 DIGITAL MICROPHONE	AXIS T8355 Digital Microphone is an omnidirectional microphone compatible with Axis network product with digital in and ring power supporting both a 3.5mm jack and audio terminal block for microphone input. Axis T8355 could be placed up to 100m (328 ft) away from Axis network products, generating flexibility for installation without deterioration of the audio signal.	105	150	40
AXIS TP3901 MICROPHONE KIT	Casing with built-in microphone for selected AXIS P32-LV cameras. Color: Axis white.	153	168	62
AXIS TP3906 MICROPHONE KIT	Accessory casing with built-in microphone for AXIS P3267-LV, AXIS P3268-LV,M3215-LVE, M3216-LVE includes microphone and casing with mic hole coming in Axis white.	153	168	62
AXIS DEVICE MICROPHONE B	AXIS Device Microphone B is an omnidirectional microphone to enable audio recording and/or audio analytics with AXIS devices that support audio but do not include a microphone. The product includes a Terminal Block to 3.5 mm Audio Extension allowing it to be installed together with our latest AXIS P32 series.	150	105	38
AXIS TU1001-VE Microphone	AXIS TU1001 -VE is an outdoor analog microphone which has to be connected over 3,5mm jack to an AXIS camera or AXIS device with Audio IN support. AXIS TU1001 -VE is IK10 and IP66 rated to withstand challenges in outdoor environments. AXIS TU1001 -VE can be wall or ceiling mounted.	105	153	81
AXIS TU1002-VE MICROPHONE KIT	AXIS TU1002-VE Microphone Kit, is an IP66, IK10 enclosure with embedded microphone. AXIS TU1002-VE fits a metallic mesh windscreen as well as dual weatherproofing membranes.The product is designed to fit an AXIS C8033 Audio Bridge, that combined with AXIS TU1002-VE will form a network microphone solution.	140	255	60
AXIS TU1001-V Microphone	TU1001 -V is an indoor analog microphone for single gang box. TU1001 -V is IK10 rated.	105	150	38
POE SPLITTER 5V	PoE Splitter 5 V can be used together with a network device that has no built-in support for Power over Ethernet (PoE). The product splits PoE into separate 5 V DC and data outputs. The product is IEEE 802.3af compliant.	75	135	40
AXIS POE MIDSPAN 8-PORT	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to eight Axis Network cameras/video servers. Metal casing.	320	520	110
AXIS POE MIDSPAN 16-PORT	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to sixteen Axis Network cameras/video servers. Metal casing.	320	520	110
AXIS T8120 15W MIDSPAN 1-PORT	Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf.	145	205	50
AXIS T8120 15W MIDSPAN 10PCS	Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf. 10 pcs.	360	550	280

AXIS T8607 MEDIA CONV SWITCH 24VDC	Media converter switch . 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Two I/O ports and a combined communication and powering port for the camera. Temp spec. -40 °C to 75 °C (-40 °F to 167 °F). 12 V DC power input. Shelf or DIN-rail mount. 24 V DC power in.	160	240	85
AXIS 30W MIDSPAN	Single port midspan for Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4 products	95	210	55
AXIS 30 W MIDSPAN AC/DC	AXIS 30 W Midspan AC/DC is ideal for installations where mains power is not an option. By means of either 10-28 V DC or 24 V AC power input the midspan can provide up to IEEE 802.3at (30 W) to a network device. AXIS 30W Midspan AC/DC 24 V is plug-and-play and offers a wide compatibility with AXIS products.	84	190	45
AXIS 90 W MIDSPAN AC/DC	AXIS 90 W Midspan AC/DC is ideal for installations where mains power is not an option. By means of either 20-26.4 V DC or 24 V AC power input the midspan can provide both IEEE 802.3bt (90 W & 60 W) and AXIS High PoE 60 W to a network device. AXIS 90W Midspan AC/DC is plug-and-play and offers a wide compatibility with AXIS products.	90	220	55
AXIS 30W OUTDOOR MIDSPAN	AXIS 30 W Outdoor Midspan is an outdoor ready IP66-/IP67-rated midspan compliant with IEEE802.3af and 802.3at. With built in 6kV surge protection. Delivers up to 30W. Temperature specification: 40°C to 65°C (-40°F to 149°F) for 30W.	175	280	85
AXIS T8611 SFP MODULE LC.LX	Small Form Factor Pluggable (SFP) transceiver module. Single mode 1310nm, 10km. Industrial grade.	105	155	35
AXIS T8612 SFP MODULE LC.SX	Small Form Factor Pluggable (SFP) transceiver module. Multi mode 850nm, 550m. Industrial grade.	105	155	35
AXIS T8613 SFP MODULE 1000BASE-T	Small Form Factor Pluggable (SFP) transceiver module. Ethernet RJ-45 . Industrial grade	105	155	35
AXIS T8134 MIDSPAN 60W	High PoE 1-port midspan 60W. Compliant with 802.3.at and PoE 802.3af.	215	70	120
AXIS T8144 60W INDUSTRIAL MIDSPAN	Industrial midspan with extended temperature range, PoE 60W and dual DC 12/24 V DC power input for redundancy. Operating temperature - 40 to +75 degC or -40 to +167 °F. DIN and wall mount included.	115	160	40
AXIS TU8002-E 90 W MIDSPAN	AXIS TU8002-E is an outdoor ready IP66-rated midspan with up to 90 W power budget. The product is ideal for environmental challenging installations of PTZ and other devices with high power needs. The midspan support both IEEE802.3bt and HighPoE.	235	125	300
AXIS T8125 AC 24V MIDSPAN 60W	60W PoE midspan for 24V AC input.	95	230	97
POWER SUPPLY DIN CP-D 12/2.1 25W	DIN power supply. 12V DC, 2.1 A. For use in T98A to power cameras, media converters etc.	90	140	70
POWER SUPPLY DIN CP-D 24/4.2 100 W	DIN power supply. 24V DC, 4.2 A. For use in AXIS Surveillance Cabinets to power cameras, media converters etc.	140	110	90
POWER SUPPLY PS24 240 W	24V DC power supply with 240 W output power.	114	310	110
AXIS T8127 60 W SPLITTER 12/24 V DC	PoE splitter. Can deliver both 12 and 24 V DC (user selectable) from High PoE 60W midspan. Useful to power and connect non-PoE devices like IP cameras, magnetic locks for access control systems, WiFi AP, thin clients etc.	90	200	50

POWER SUPPLY DIN PS24 480W	Power supply for AXIS Q86, Q87 & T99A product lines. 480W 24V 20A for DIN rail mounting.	145	170	145
AXIS POWER SUPPLY DIN PS56 240W	Power supply for AXIS T8504-R Industrial PoE Switch. 240W 56V 5A for DIN rail mounting.	104	193	250
AXIS T8129 POE EXTENDER	Power over Ethernet extender repeats the data signal and forward the PoE to the camera, PoE+ compliant it is compatible with all Axis cameras. No additional power supply is required. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	180	120	40
AXIS T8129-E OUTDOOR POE EXTENDER	AXIS T8129-E Outdoor PoE Extender repeats the data signal and PoE to the camera. AXIS T8129-E is PoE+ compliant with all Axis cameras and does not require an additional power supply. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	85	150	40
ACC CABLE I/O AUDIO 5M P3343-VE	Audio and I/O extension cable for AXIS P33 Series. Includes 4 pin terminal connector 2.5mm Female to Male, 2 x stereo plug 3.5mm Male to Female. 5 meter.	165	240	80
AXIS LONG RANGE POE EXTENDER KIT	AXIS Long range PoE Extender kit offers a smart and easy-to-install solution for extending the range of your network and PoE up to 1000m (3280ft.). Connect the product in-line with the CAT5e or CAT6 cable and power and data are forwarded to your Axis network devices. AXIS Long range PoE Extender kit supports both IEEE 802.3af and IEEE 802.3at compliant devices and can withstand challenging temperatures. The product is NEMA TS2 compatible.	120	170	35
AXIS DIGITAL AUDIO EXTENSION KIT	AXIS Digital Audio Extension Kit enables AXIS T8355 Digital Microphone to extend to distances up to 100m (328 ft).	105	150	33
AXIS AUDIO EXTENSION CABLE B 5M	Audio extension cable for Axis 3.5mm mono microphones. Length 5m (197 in).	105	150	33
AXIS T8516 PoE+ NETWORK SWITCH	PoE+ managed gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 16 PoE+ ports with 250W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products.	300	525	90
AXIS T8524 POE+ NETWORK SWITCH	PoE+ managed gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 24 PoE+ ports with 370W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products.	520	300	90
TERMINAL BLOCK TO 3.5MM AUDIO EXT	3.5mm audio jack extension for Axis Network Video products with terminal block audio connection.	105	150	33
AXIS MULTICABLE A I/O AUDIO PWR 1M	Multi-connector cable for power (12VDC), audio and I/O port. 1m (40 in)	180	280	55

AXIS T8640 POE+ OVER COAX ADAP	Pair of Ethernet over COAX adapters that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. Powered by either PoE or power supply, dependent on power requirement at the device end. Diagnostics LEDs for power and link status in both base and device unit. Connectors: BNC and RJ45 connector and power input (for optional power supply). The package contains one base unit and one device unit.	175	130	30
AXIS MULTICABLE A I/O AUDIO PWR 5M	Multi-connector cable for power (12VDC), audio and I/O port. 5m (197 in)	200	225	110
AXIS T8641 POE+ OVER COAX BASE	Single Base unit of Ethernet over COAX adapter. The package contains one base unit.	165	240	80
AXIS MULTICABLE B I/O AUDIO PWR 2.5M	Multi-connector cable for AC/DC power, audio in/out and I/O connectivity. 2.5m (8.2 ft)	178	279	57
AXIS T8642 POE+ OVER COAX DEVI	Single Device unit of Ethernet over COAX adapter. The package contains one device unit.	165	240	80
AXIS MULTICABLE C I/O AUDIO PWR 1M	Multi-connector cable for power, audio and I/O connectivity. 1m (3.3 ft)	120	60	310
AXIS T8643 POE+ OVER COAX COMPACT	AXIS T8643 PoE+ over Coax Compact enables legacy coax cabling to be kept when converting an analog system to digital. The design allows for improved installation and cable management as it can easily be integrated in housings and backboxes. It delivers standard Power over Ethernet (PoE) and centrally-sourced power through existing coax cabling.	160	110	30
AXIS MULTICABLE C I/O AUDIO PWR 5M	Multi-connector cable for power, audio and I/O connectivity. 5m (16.4 ft)	190	190	75
AXIS T8645 PoE+ COAX COMPACT KIT	AXIS T8645 PoE+ over Coax Compact Kit enables legacy coax cabling to be kept when converting an analog system to digital, and comprises AXIS T8641 PoE+ Over Coax Base and AXIS T8643 PoE+ over Coax Compact. It delivers standard Power over Ethernet (PoE) and centrally-sourced power through existing coax cabling. The compact design of the AXIS T8643 PoE+ over Coax Compact allows for improved installation and cable management as it can easily be integrated in housings and backboxes.	200	140	30
AXIS OUTDOOR RJ45 CABLE 5M	Outdoor CAT6 Ethernet cable for outdoor AXIS PTZ and panoramic cameras. IP66-rated male push pull connector on one end, IP20 rated male RJ45 connector on the other end. Length: 5m (16ft). Color: black.	200	225	110
AXIS OUTDOOR RJ45 CABLE 15M	Outdoor CAT6 Ethernet cable for outdoor AXIS PTZ and panoramic cameras. IP66-rated male push pull connector on one end, IP20 rated male RJ45 connector on the other end. Length: 15m (50ft). Color: black.	280	255	135
AXIS CABLE 24 VDC/24-240 VAC 22M	Heavy duty power cable, 22m (72ft) in length, 3-wire, 12AWG, jacket diameter 10mm (0.4in). Suitable for outdoor installation. UL20626 up to 90°C (194°F) ambient temperature. Designed for use with AXIS Positioning Cameras and Positioning Units, such as AXIS Q8685-E. Material: TPE insulation, copper wire, PVC-free and halogen-free. Color: Black.	222	222	131
NETWORK CABLE COUPLER INDOOR	Female/female RJ45 coupler. For indoor use. Perfect when you need to extend a pre-terminated cable.	120	80	20

NETWORK CABLE COUPLER INDOOR SLIM	Female/female RJ45 coupler. Slim and compact size. For indoor use. Perfect when you need to extend a pre-terminated cable.	600	100	10
AXIS T98A15-VE MEDIA CONVERTER CABINET A (230 V AC)	Pre-assembled T98A Surveillance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	327	378	169
AXIS T98A16-VE MEDIA CONVERTER CABINET A (230 V AC)	Pre-assembled T98A Surveillance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	327	378	169
AXIS T98A17-VE MEDIA CONVERTER CABINET A (230 V AC)	Pre-assembled T98A Surveillance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	327	378	169
AXIS T98A18-VE MEDIA CONVERTER CABINET A (230 V AC)	Pre-assembled T98A18-VE Surveillance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3) AXIS T8604 Media Converter, (4) Power cable and DIN clip for midspan AXIS T8124, (5) Internal cables and mounts. Tested and verified with Axis cameras.	327	378	169
ACC MAINS ADAPTOR AXIS PS24	24VAC power adapter for outdoor use. Output max 63VA.	270	200	310
AXIS T8008 PS24	24V DC power supply 250W with extended temperature (-40 to +75C (-40 to 167F)).	210	325	100
AXIS T8051 Power Converter AC/DC to DC	AC/DC to DC power converter for AXIS Q35-VE, 24 V AC or 12/24 V DC input. Backbox designed to match perfectly with camera.	205	190	80
AXIS TU8001 Ethernet Surge Protector	AXIS TU8001 Ethernet Surge Protector helps reduce downtime, service and maintenance of your system by shielding your PoE devices against transient voltage spikes in the Ethernet cable. The product protects up to 10 kV surge, with data rates up to 1 Gbps. AXIS TU8001 is IEC 61643-21 complaint and can handle extended temperature ranges. Its compact form factor is ideal for surface or DIN-rail installations, in e.g. electrical cabinets. A high-quality product validated to work seamlessly with Axis devices.	55	110	40
AXIS T8061 ETHERNET SURGE PROTECTOR	Protect your Ethernet networks device, i.e. cameras, switches, midspans, etc..., from lighting. Protects up to 10KV surge, IP66 and UL certified.	91	233	45
CONNECTOR M12 MALE 4P 10PCS	Rugged, male D-coded M12 connector compatible with AXIS M31XX-R M12 and Connector M12 Female 4P . Field installable with screw-in contacts. 10 pcs	165	240	80
AXIS 10-PIN PUSH-PULL SYSTEM CONN	10-pin system connector for power, audio and I/O.	120	190	40

RJ45 FIELD CONNECTOR 10 PCS	RJ45 Field Connector (10 PCS) for easy assembly in the field without the need for special tools. Due to its compact size, it has a wide compatibility with Axis devices, like AXIS P32 Series or Network Cable Coupler IP66. Ready to be used with CAT6a ethernet cabling, AWG 26-22. Suitable for IEEE 802.3af, 802.3at, 802.3bt and Axis HighPoE solution.	140	90	50
AXIS STEREO-TO-MONO ADAPTER	AXIS Stereo-to-mono Adapter. Spare part to AXIS F44 Dual Audio Input Main Unit. Allows two microphones or line inputs to be connected to AXIS F44 Dual Audio Input.	105	155	35
AXIS POWER CABLE 24 V 7m (23ft)	AXIS Power Cable 24V 7m (23ft) helps extending the operating temperature of AXIS Q6010 / Q6100 -E up to -50° (-58°F) when installed in extreme cold environments. The power cable requires a 24V DC mains adapter (Not included).	165	190	75
AXIS TD8902 SFP+ MODULE LC.SR.X	AXIS TD8902 SFP+ Module LC.SR.X is an enhanced small form-factor pluggable (SFP+) transceiver that supplies network devices, such as switches or routers, with a fiber optic network connection. It is industrial grade with a wide temperature range, and it includes link-loss that enable network redundancy. Complying with SFP+ Multisource Agreement (MSA), it is easy to install into compliant ports at any time without interrupting the online operation of the host equipment. Short wavelength (850 nm) VCSEL laser diodes enable data transmission up to 400 m on a multimode 50/125 <u>um optical fiber</u>	50	105	20
AXIS TD8901 SFP+ MODULE LC.LR.X	Small Form Factor Pluggable (SFP+) transceiver module. Single mode 1310nm, 10km. Industrial grade.	50	105	20
POWER SUPPLY DIN PS56 480 W	Power supply for D8208-R Industrial PoE++ Switch, 480W and for DIN rail mounting.	195	195	140
AXIS T8154 60W SFP MIDSPAN	bt. compliant 60 W Midspan with additional SFP port	110	205	90
AXIS TU8004 90 W Midspan	AXIS TU8004 is a single port 90 W midspan, compliant with IEEE 802.3bt and High PoE devices. Power over Ethernet (PoE) offers an easy, fast and cost-effective solution for powering network products. In a single network cable, a PoE midspan injects power and data to the network device with built-in PoE support. No need to replace existing Ethernet switches and cabling infrastructure. The midspan can be installed on a wall, shelf or DIN rail with AXIS T91A03 DIN Rail Clip A. Note: AXIS TU6011 Mains Cable is sold separately.	93	220	60
AXIS TU8003 90 W CONNY MDSPN	AXIS TU8003 90 W Connectivity Midspan with portcast technology uses the camera's IP address to provide seemingly camera-integrated audio and I/O connectivity. This enables audio and video in one stream over the network with no extra VMS license. It supports Axis PTZ cameras using up to 90 W (IEEE 802.3bt). Plus, it's compatible with PTZ cameras using IEEE 802.3af/at and Axis High PoE.	140	205	60
AXIS TQ1936 POE PATCH CABLE 5 pcs	5 pack poe patch cables compatible with: AXIS Q1805-LE, AXIS Q1806-LE, AXIS Q1808-LE. CABLE NETWORK L=115MM CAT5E RJ45	65	175	25

AXIS TU8010 2-port PoE Extender	AXIS TU8010 2-port PoE Extender add additional PoE ports within a system, allowing for more devices to be connected. In addition to this they also extend the length of PoE cabling that you can use by 100 meters. The new PoE extenders will enhance the ease of installation by minimizing the number of PoE ports used and the amount of cabling needed.	150	200	55
AXIS TU8011 4-port PoE Extender	AXIS TU8011 4-port PoE Extender add additional PoE ports within a system, allowing for more devices to be connected. In addition to this they also extend the length of PoE cabling that you can use by 100 meters. The new PoE extenders will enhance the ease of installation by minimizing the number of PoE ports used and the amount of cabling needed.	225	175	55
AXIS TD8910 Console Cable	Added primarily for the D8308 Fiber Aggr Switch to allow for easier and flexible set up.	105	150	40
AXIS TD8911 SFP28 Module LC.LR.X	SFP28 module added primarily to be used with the D8308 Fiber Aggr Switch.	50	105	20
AXIS TD8912 SFP28 Module LC.SR.X	SFP28 module added primarily to be used with the D8308 Fiber Aggr Switch.	50	105	20
AXIS SURVEILLANCE CARD 64 GB	AXIS Surveillance Card 64 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	110	155	35
AXIS SURVEILLANCE CARD 64 GB 10P	AXIS Surveillance Card 64 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter. 10pack.	110	155	35
AXIS SURVEILLANCE CARD 128 GB	AXIS Surveillance Card 128 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	75	115	57
AXIS SURVEILLANCE CARD 128 GB 10P	The 10 pack variant of the AXIS Surveillance Card 128 GB, a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras.	10	60	40

AXIS SURVEILLANCE CARD 256GB	AXIS Surveillance Card 256 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	120	75	55
AXIS SURVEILLANCE CARD 256GB 10PCS	AXIS Surveillance Card 256 GB (10pcs) are high endurance microSDXC™ cards optimized for video surveillance. They have support for health status monitoring with Axis cameras. The cards enable flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapters.	120	75	55
AXIS SURVEILLANCE CARD 512GB	AXIS Surveillance Card 512 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	70	60	15
AXIS SURVEILLANCE CARD 512GB 10PCS	AXIS Surveillance Card 512 GB (10pcs) are high endurance microSDXC™ cards optimized for video surveillance. They have support for health status monitoring with Axis cameras. The cards enable flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapters.	80	115	50
AXIS SURVEILLANCE CARD 1TB	AXIS Surveillance Card 1 TB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	70	60	15

AXIS SURVEILLANCE CARD 1TB 10PCS	AXIS Surveillance Card 1 TB (10pcs) are high endurance microSDXC™ cards optimized for video surveillance. They have support for health status monitoring with Axis cameras. The cards enable flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapters.	80	115	50
SURVEILLANCE HARD DRIVE 4TB	Surveillance Hard Drive 4TB is a 3.5-inch internal drive designed and tested for 24/7 reliable video surveillance. It is optimized for high-definition continuous or event triggered recordings and high write-cycle workloads. Suitable for storage expansion of compatible appliances, it enables for flexible storage solutions. Storage needs can be estimated with AXIS Site Designer 2 and appropriate recommendation will be provided.	150	230	80
SURVEILLANCE HARD DRIVE 6TB	Surveillance Hard Drive 6TB is a 3.5-inch internal drive designed and tested for 24/7 reliable video surveillance. It is optimized for high-definition continuous or event triggered recordings and high write-cycle workloads. Suitable for storage expansion of compatible appliances, it enables for flexible storage solutions. Storage needs can be estimated with AXIS Site Designer 2 and appropriate recommendation will be provided.	150	230	80
ENTERPRISE HARD DRIVE 4TB	Enterprise Hard Drive 4 TB is a 3.5-inch internal hard drive designed and tested for 24/7 reliable video surveillance. It is optimized for ultra-high-definition continuous or event-triggered recording at high workloads. Enterprise Hard Drive 4 TB can be added to an existing RAID array composed of drives of the same capacity. It is suitable for storage expansion of most products in AXIS S11 Series and AXIS S12 Series. Storage needs can be estimated with AXIS Site Designer and appropriate recommendation will be provided. Enterprise Hard Drive 4 TB is sold together with the HDD tray.	180	220	160
ENTERPRISE HARD DRIVE 8TB	Enterprise Hard Drive 8 TB is a 3.5-inch internal hard drive designed and tested for 24/7 reliable video surveillance. It is optimized for ultra-high-definition continuous or event-triggered recording at high workloads. Enterprise Hard Drive 8 TB can be added to an existing RAID array composed of drives of the same capacity. It is suitable for storage expansion of most products in AXIS S11 Series and AXIS S12 Series. Storage needs can be estimated with AXIS Site Designer and appropriate recommendation will be provided. Enterprise Hard Drive 8 TB is sold together with the HDD tray.	180	220	160
AXIS TU9001 Control Board	AXIS TU9001 Control Board is a modular system with separate joystick and keypad units. The modular system allows you to choose a simple solution such as only the joystick, or a complete solution with the two modules for both camera and video management.	220	240	260

AXIS TU9002 Joystick	AXIS TU9002 Joystick gives responsive and accurate control of all Axis PTZ cameras. It is a 3-axis joystick with a turn knob and six application-defined hotkeys. Plus, you can use AXIS TU9002 as a computer mouse. The joystick is constructed in durable materials and has a professional and modern look that adapts to a surveillance room design. It is designed for both left-hand and right-hand use and is easy to install with a USB interface.	230	215	170
AXIS TU9003 Keypad	With AXIS TU9003 Keypad, you can quickly navigate between workspaces, cameras, views, and PTZ presets. It has 10 application-defined hotkeys and 12 preset keys. It's equipped with an LCD display allowing the operator to see, for instance, the number of the camera he or she is looking at. The keypad is constructed in durable materials that are PVC free and has a professional and modern look that adapts to a surveillance room design. It is designed for both left-hand and right-hand use and is easy to install with a USB interface.	230	215	75
AXIS T8604 MEDIA CONVERTER SWITCH	Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (-40°F to 167°F).	210	150	35
AXIS T8606 MEDIA CONV SWITCH 24VDC	Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (-40°F to 167°F). 24 V DC power in.	160	240	85
AXIS T8353A MICROPHONE 3.5MM	AXIS T8353A Microphone 3.5mm is an omnidirectional microphone with a 3.5mm adaptor, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. AXIS T8353A Microphone offers great details and resolution, the capsule has a neutral sonic character and is very natural sounding. The discreet microphone is very reliable even in demanding environments.	105	155	35
AXIS T8353 MOUNT	Mounting accessory for AXIS T8353 Microphones	60	100	5
AXIS T8415 WIRELESS INSTALLATION TOOL	Camera installation made easy. Battery driven Wi-Fi access point with PoE+ to camera for use with AXIS Installation application on your iOS or Android device.	400	240	205
AXIS T8415 WIRELESS INST TOOL KIT	Kit including AXIS T8415 Wireless Installation Tool, one extra AXIS Installation Tool Battery 12V3.4Ah and one AXIS Installation Bag.	420	400	270
AXIS P55/Q60 MULTI CONN CABLE 5M	Multi-connector cable for power, audio and I/O. Used for Indoor AXIS P55-series and Indoor Q60-series PTZ Dome Network Camera.	280	255	135
AXIS T8415 INSTALLATION BAG	Durable soft bag to carry the AXIS T8415 Wireless Installation Tool, with space for extra battery, charger, network cables etc.	160	395	135
AXIS INSTALLATION TOOL BATTERY 12V3.4Ah	Additional battery for AXIS T8415 Wireless Installation Tool.	145	235	155
ACC MAINS ADAP PS-P T-C	Power supply PS-P T-C for AXIS Q1755 and AXIS Q7404	165	240	80
AXIS INSTALLATION CHARGER ADAPTOR 12V1A	Charging adaptor for AXIS T8415 Wireless Installation Tool.	120	80	60

AXIS P8221	Network I/O and audio module. Eight digital ports configurable as inputs or outputs. Two-way audio configurable to simplex, half or full duplex. Built-in pre-amp, phantom power and gain control for a balanced microphone. Line and speaker output. Serial port RS-232/422/485. Power over Ethernet enabled. Includes power supply.	190	250	105
AXIS D3110 Connectivity Hub	AXIS D3110 gives sensor and audio capabilities to network video systems or other IoT systems that do not have them or need additional ones. The product comes with 2x Audio IN, Audio Out, 8x Configurable I/Os, Relay and RS485/422. The product can be Powered over Ethernet or through DC. AXIS D3110 supports MQTT, Vapix® and SIP. The product comes with Built-in cybersecurity functionality preventing unauthorized access.	160	155	70
AXIS T8006 PS12	Power supply with extended temperature specification -40°C to +75°C (-40°F to +167°F) providing 12 V DC to units such as AXIS T8604 and AXIS Q7424-R.	165	240	80
NETWORK CABLE COUPLER IP66	Compact IP66-rated female/female RJ45 cable coupler. Perfect when you need to extend a pre-terminated outdoor cable.	130	155	30
ACC MAINS ADAP PS-K TERM-CONN	Power supply for AXIS P1311/43/44 and AXIS Q7401 as a spare part.	165	240	80
AXIS T8003 PS57	Power supply for the AXIS T8640 Coax Over Ethernet Adapter. If connected to the base end COAX adapter part, it powers up the connection, the device end unit and the PoE camera and thereby removes the need for a separate midspan. Can also be connected to the device end, to secure enough power (max 30W) to the connected PoE camera (COAX cable quality/long distance).	205	145	55
AXIS T8008 PS12	Power supply for AXIS Q60XX-C series -40 to +75C (-40 to 167F). In 90-264V AC 47-63Hz. Out 12,5V DC 85W.	210	325	100
AXIS T8085 PS57 500W 1U	Power supply 500W for use with AXIS T8646 POE+ OVER COAX BLADE in a 1U rack.	0	0	0
AXIS T90C20 FIXED DOME IR-LED	IR-illuminator for AXIS P334X-VE cameras. PoE IEEE802.3af compliant. Operating temperature - 40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, vandal resistant. Premounted 5m network cable cable with gaskets.	365	225	80
AXIS T90D20 IR-LED	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 36m to 144m (118 ft to 472 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	150	245	120
AXIS T90D20 POE IR-LED	PoE powered IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 36m to 144m (118 ft to 472 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature - 50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	150	245	120

AXIS T90D25 W-LED	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 25 m to 110 m (80 ft to 360 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input	150	245	120
AXIS T90D25 POE W-LED	PoE powered white LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 25 m to 110 m (80 ft to 360 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	150	245	120
AXIS T90D30 IR-LED	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 70m to 350m (230ft to 1150 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	150	245	120
AXIS T90D30 POE IR-LED	PoE powered IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 70m to 350m (230ft to 1150 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	195	305	115
AXIS T90D35 W-LED	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 35m to 180m (115ft to 590ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	195	310	115
AXIS T90D35 POE W-LED	PoE powered white LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 35m to 180m (115ft to 590ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F).PoE+ IEEE 802.3at required.	195	305	115
AXIS T90D40 IR-LED	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°-140° beam angles. Beam distance ranges 105m to 500m (345ft to 1640ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	184	335	266
AXIS WL LENS B 120 DEG	Accessory lens providing 120° beam angle, beam distance is 15 m (49 ft). Compatible with AXIS T90B25 W-LED.	120	230	18
AXIS IR LENS B 120 DEG	Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B20 IR-LED.	120	230	18
AXIS WL LENS C 120 DEG	Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B35 W-LED.	120	230	18

AXIS IR LENS C 120 DEG	Accessory lens compatible with AXIS T90B30 IR-LED providing 120° beam angle, beam distance 30 m (98 ft). Also compatible with AXIS T90B40 IR-LED (two lenses are required as the illuminator has two panels). The beam angle can be adjusted between 120° and 180°, with a beam distance stretching from 65 m to 45 m (213 ft to 148 ft). This sales part includes one lens.	120	230	18
AXIS IR LENS D 120 DEG	Accessory lens providing 120° beam angle	120	230	18
AXIS T90B REMOTE CONTROL	The remote control is compatible with all Axis T90B illuminators and provides the possibility to adjust settings of light intensity, photocell sensitivity and more conveniently from the ground level. No lift or ladder required. The remote control feature can be disabled after the installation is finalized to avoid tampering.	0	0	0
AXIS T90 WALL-AND-POLE MOUNT	Mounting bracket for AXIS T90 illuminators.	136	185	85
AXIS T90 SINGLE BRACKET	Mounting bracket for AXIS T90 illuminators.	130	170	30
AXIS T90 MULTI BRACKET	Mounting bracket for AXIS T90 illuminators.	142	395	32
AXIS DOOR SWITCH A	Intrusion door switch for AXIS T98A, connection to I/O port.	165	180	40
AXIS DOME INTRUSION SWITCH C	AXIS Dome Intrusion Switch C can be placed in compatible Axis dome cameras and devices to trigger an event upon removal of the casing. Connects directly to the I/O port.	105	155	30
AXIS FIXED BOX IR ILLUMINATOR KIT A	AXIS Fixed Box IR Illuminator Kit A for AXIS P1375-E. For mounting on AXIS P13 Series camera. Range of reach 50 m (164 ft) or more depending on the scene. Powered by AXIS P13 Series camera. Requires Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4 midspan power for AXIS P13 Series camera.	88	120	50
AXIS TQ1901-E IR ILLUMINATOR KIT	Illuminator Kit for AXIS P13 Series and AXIS Q1656-BE. Offers both and 850nm or 940nm wavelength. Powered by the camera. Camera requires Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4 midspan power for AXIS P13 Series and AXIS Q1656-BE camera. AXIS TQ1901-E IR ILLUMINATOR KIT is included in AXIS Q1656-LE and AXIS Q1656-BLE	90	120	50
AXIS I/O INDICATION LED 4P	AXIS I/O Indication LED is an easy to install signaling accessory for all AXIS devices that support 12 V I/O and can be setup through the event handling of the device to address desired deterrence or privacy concerns. The LED comes with IP44 rating. Up to three LEDs could be installed with AXIS devices that support 50 mA load on their I/O ports. This product comes in a 4-pack.	105	140	35
AXIS CAMERA HEATER POWER SUPPLY	AXIS Camera Heater Power Supply helps extending the operating temperature of AXIS Q6010 / Q6100 -E up to -50°C (-58°F) when installed in extreme cold environments.	165	190	75

AXIS TQ1902-E IR ILLUMINATOR KIT	Illuminator Kit compatible with: AXIS P1375-E, AXIS P1377-LE, AXIS P1378-LE, AXIS Q1656-BE, AXIS Q1656-BLE, AXIS Q1656-LE. Offers IR with White light module – 840nm with white leds. Powered by the camera. Camera requires Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4 midspan. Note there is a similar illuminator kit for same cameras: 02194-001 and the difference is only the White light, where: 02194-001 – IR with IR modules – 840nm with 940nm.	50	90	120
AXIS TM3812 Tamper-resistant Cover	4 pack accessory casing to prevent tampering. Offer a secure way by a screw to increase the tamper resistance by replacing standard cover with the new Tamper Cover. It require special tools (resitorx) to open the cover. Allen key, TX6 screw, cover, cover top hatch come in the package. Compatible with M3085-V, M3086-V, M3088-V.	105	131	105
AXIS TM3817 TAMPER-RESISTANT COVER	4 pack accessory casing to prevent tampering. Offer a secure way by a screw to increase the tamper resistance by replacing standard cover with the new Tamper Cover. It require special tools (resitorx) to open the cover. Allen key, TX6 screw, cover, cover top hatch come in the package. Compatible with M4216-LV/V.	110	150	110
AXIS TQ1937-E IR ILLUMINATOR KIT	AXIS TQ1937-E IR Illuminator Kit has a powerful IR and is designed to fit AXIS Q16 Series and AXIS P13 Series. The improved IR has 4 lenses: 2 wide-angle lenses for zoomed-out views and 2 tele lenses for zoomed-in views. It enables cost-efficient surveillance in pitch darkness and includes power-efficient, long-life 850 nm IR with a range of reach of 50 m (164 ft). The IP66/67 and IK10-rated IR can easily be mounted on the bottom of the outdoor models in AXIS Q16 Series and AXIS P13 Series. AXIS TQ1937-E IR Illuminator Kit is included in Q1686-DLE.	90	120	55
AXIS D4100-E NETWORK STROBE SIREN	AXIS D4100-E Network Strobe Siren helps deter intruders and improve operations with the power of light and sound. Flexible to configure with a combination of RGBA light patterns and sounds up to 110 dB. Easy to setup through two configurable I/O ports, VAPIX, MQTT or SIP. Power over Ethernet. IP66 and IK10 outdoor ready, vandal-resistant casing. Includes mounting bracket for wall/ceiling or junction boxes.	195	180	95

AXIS D2110-VE	AXIS D2110-VE Security Radar, 24.05–24.25 GHz, FMCW, for wall mounting outdoor. Reliable 180 degrees horizontal field of detection 24/7 with built-in analytics including classification of humans and vehicles. Complement to video surveillance enables filtering on distance, customized detection zones, and auto-tracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light source for deterrence. Open API for software integration, microSD/SDHC memory card slot for edge storage, 30W PoE out to power an additional device, 4 input/output ports, 24 V DC relay port. Powered by PoE+ (IEEE 802.3at, Type 2 Class 4) or DC 8-28V. IP66, IK08 and NEMA 4. Operating conditions -40°C to 60°C (-40°F to 140°F).	397	267	200
AXIS D2210-VE Radar White	AXIS D2210-VE Security Radar, White front. 61.0–61.5 GHz, FMCW, for pole and wall mount. Reliable 95 degrees horizontal field of detection 24/7 with built-in analytics including classification of humans and vehicles. Optimized for both area monitoring and traffic monitoring. Complement to video surveillance enables filtering on distance, customized detection zones, Radar Autotracking and Radar Autotracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light source for deterrence. Integrated dynamic LEDs for deterrence. Open API for software integration, microSD/SDHC memory card slot for edge storage. 30W PoE out to power an additional device, 1 input and 1 output ports, 24 V DC. Powered by PoE (IEEE 802.3bt, Type 3 Class 6) or DC 8-28V. IP66, IK08 and NEMA 4. Operating conditions -40°C to 60°C (-40°F to 140°F).	255	225	195
AXIS D2210-VE Radar Black	AXIS D2210-VE Security Radar, Black front. 61.0–61.5 GHz, FMCW, for pole and wall mount. Reliable 95 degrees horizontal field of detection 24/7 with built-in analytics including classification of humans and vehicles. Optimized for both area monitoring and traffic monitoring. Complement to video surveillance enables filtering on distance, customized detection zones, Radar Autotracking and Radar Autotracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light source for deterrence. Integrated dynamic LEDs for deterrence. Open API for software integration, microSD/SDHC memory card slot for edge storage. 30W PoE out to power an additional device, 1 input and 1 output ports, 24 V DC. Powered by PoE (IEEE 802.3bt, Type 3 Class 6) or DC 8-28V. IP66, IK08 and NEMA 4. Operating conditions -40°C to 60°C (-40°F to 140°F).	255	225	195
AXIS D8004 UNMANAGED POE SWITCH	AXIS D8004 Unmanged PoE Switch is a 4 channel 10/100 Mbps PoE+ switch with plug & play installation. The unmanaged switch comes with a 60 W power budget and is perfect as an entry-level switch for small systems with PoE requirements.	155	235	65

AXIS T8504-E OUTDOOR POE SWITCH	Outdoor 4-port managed PoE switch for surveillance applications. 4 PoE ports with up to 60W PoE per port and one SFP port for uplink. Robust metal enclosure with wide temperature range , IP67 and surge protection for demanding installations. Managed switch for remote configuration and management.	240	375	105
AXIS T8504-R INDUSTRIAL POE SWITCH	AXIS T8504-R Industrial PoE Switch is a 4-port managed industrial PoE++ Gigabit switch. In addition, the switch is equipped with 2 x RJ45 and 2x SFP data ports that allows for extra devices to be connected. The switch uses the same intuitive administrator interface as AXIS T85 PoE Network Switch Series, is ruggedized with a wide temperature range and NEMA TS2 compliant.	210	255	85
AXIS D8208-R INDUSTRIAL PoE++ SWITCH	AXIS D8208-R Industrial PoE Switch is a 8-port managed industrial PoE++ Gigabit switch. In addition, the switch is equipped with 2 x RJ45 and 2x SFP data ports that allows for extra devices to be connected. The switch uses the same intuitive administrator interface as AXIS T85 PoE Network Switch Series, is ruggedized with a wide temperature range and NEMA TS2 compliant.	170	270	85
AXIS T8508 POE+ NETWORK SWITCH	PoE+ managed fanless gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 8 PoE+ ports with 130W power supply. Built in DHCP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products	360	330	90
AXIS D8248 MANAGED PoE++ SWITCH	This 48 port network switch is optimized for surveillance solutions. With a unique web graphic user interface, it offers a topology for easy overview and management of all devices in the system.	470	570	105
AXIS D8308 Fiber Aggr Switch	Switch at aggregation level, instead of access (edge) level Fiber switch, no PoE with 8 SFP ports (SFP+ and SFP28) Long distance installations enabler.	300	525	85
AXIS P8221 BULK 10PCS	AXIS P8221 in 10-pack/bulk. Cannot be sold separately as single pack. NO midspans. Power supplies not included.	360	550	280
AXIS T6101 MKII Audio and I/O Interface	AXIS T6101 MKII Audio and I/O Interface enabling external two-way audio and configurable supervised inputs / digital outputs for Axis cameras even when they do not have such functionality built-in. Powered by standard Power over Ethernet and PoE passthrough to camera. Allows the connected camera to provide one stream for audio and video, without the need for any additional IP address.	84	128	35
AXIS T6112 MKII Audio and I/O Interface	AXIS T6112 MKII Audio and I/O Interface combines AXIS T6101 MKII Audio and I/O Interface with two microphones in a discreet casing suitable for indoor installation on wall or ceiling. Powered by standard Power over Ethernet and PoE passthrough to camera. Two-way audio and configurable supervised inputs / digital outputs for Axis cameras even when they do not have such functionality built-in. Allows the connected camera to provide one stream for audio and video, without the need for any additional IP address.	140	230	55

AXIS TW1100 Clip Mount 5P	AXIS TW1100 Clip Mount 5P 5 pack mount for the Klick Fast adaptor on the Axis body worn cameras. The clip mount is an easy to use, versatile mount suitable for many types of clothing.	200	120	45
AXIS TW1101 MOLLE Mount 5P	AXIS TW1101 MOLLE Mount 5P. 5 pack mount for the Klick Fast adaptor on the Axis body worn cameras. The MOLLE mount is especially suitable for the MOLLE system found on tactical equipment and such.	220	130	35
AXIS TW1103 Chest Harness Mount 5P	AXIS TW1103 Chest Harness Mount 5P 5 pack mount for the Klick Fast adaptor on the Axis body worn cameras. The chest harness mount holds the camera independent of choice of clothing.	165	240	80
AXIS TW1104 MAGNET MOUNT 5P	5 pack mount for the Klick Fast adaptor on the Axis body worn cameras. The magnet mount is a rugged, versatile mount suitable for many types of clothing. This updated version perfectly follows the shape of the camera and has an improved stability to the camera.	90	95	75
AXIS TW1105 HARNESS CENTER MOUNT 5P	5 pack mount for the Klick Fast adaptor on the Axis body worn camera. The harness center mount holds the camera independent of choice of clothing. It features a large, soft mount pad, centered on the body, and its elastic bands makes it easy to adjust and comfortable to wear.	330	210	100
AXIS TW1106 Magnet Mount 5P	For flexible and light wearing of the AXIS W110 Body Worn Camera on any fabric. Comes in 5-pack.	70	88	117
AXIS TW1107 Magnet Mount 5 pcs	AXIS W110 Body Worn Camera mount for secure wearing compatible with all Klick Fast mounts. Comes in 5-pack.	105	150	36
AXIS TW1108 Screw-on Mount 5P	AXIS TW1108 Screw-on Mount offers secure mounting of the body worn camera on any type of garment. With four screws the front of the mount is screwed together with the back through the fabric of the garment. Sold in 5-pack.	300	200	50
AXIS TW1200 BW MINI BULLET SENSOR	As an accessory to the Axis body worn cameras the AXIS TW1200 Body Worn Mini Bullet Sensor is designed to offer a flexible recording position. It supports the Picatinny mounting system, making it compatible with many kinds of available gear, and especially suitable for helmets. AXIS TW1200 offers the same optical performance as the body worn camera with sharp images even in challenging conditions. Mounting options are included.	145	155	40
AXIS TW1201 BW MINI CUBE SENSOR BLACK	As an accessory to the Axis body worn cameras the AXIS TW1201 Body Worn Mini Cube Sensor is designed to offer a flexible on-chest recording position. Its less prominent form factor, very low weight and flexible magnet mount makes it suitable to wear on lighter clothing, like a t-shirt or even on the lapel of a blazer, and is perfect for usage outside law enforcement. AXIS TW1201 offers the same optical performance as the body worn camera with sharp images even in challenging conditions. Magnet mount included.	82	132	40

AXIS TW1201 BW MINI CUBE SENSOR WHITE	As an accessory to the Axis body worn camera the AXIS TW1201 Body Worn Mini Cube Sensor is designed to offer a flexible on-chest recording position. Its less prominent form factor, very low weight and flexible magnet mount makes it suitable to wear on lighter clothing, like a t-shirt or even on the lapel of a blazer, and is perfect for usage outside law enforcement. AXIS TW1201 offers the same optical performance as the body worn camera with sharp images even in challenging conditions. Magnet mount included.	82	132	40
AXIS TW1900 ADHESIVE PICATINNY RAIL 5P	5 pack adhesive picatinny rail to mount the AXIS TW1200 Body Worn Mini Bullet Sensor on general equipment.	110	150	40
AXIS TW1901 CABLE HOLDER 5P	5 pack replacement cable holder to securely connect the AXIS TW1200 Body Worn Mini Bullet Sensor cable to the Axis body worn cameras.	110	150	40
AXIS TW1902 LENS PROTECTOR 5P	5 pack replacement lens protector for AXIS TW1200 Body Worn Mini Bullet Sensor.	110	150	40
AXIS TW1904 Body Worn Mount Flight	Demonstration kit consisting of 3 mounts, 1 of each AXIS TW1101, AXIS TW1102 and AXIS TW1103.	240	165	85
AXIS TW1905 MINI CUBE MAGNET MOUNT 5P	5 pack mount for the AXIS TW1201 Body Worn Mini Cube Sensor. The magnet mount is a light and versatile mount suitable for many types of clothing and positions.	116	151	38
AXIS TW1906 Battery Replacement Kit 5P	The AXIS 1906 Battery Replacement kit includes everything needed to safely replace the battery in the AXIS W100 Body Worn Camera or the AXIS W101 Body Worn Camera. Included in the kit are 5x replacement batteries, a plastic camera opening tool, a Torx T6 and spare screws.	165	110	50
AXIS TW1908 Stud Mount 10 pcs	AXIS TW1908 Stud Mount is a sparepart for our body worn cameras using Klick Fast solution and is sold in 10-pack.	60	80	50
AXIS TW8100 RACK MOUNT	The AXIS TW8100 Rack Mount is an accessory that makes it possible to conveniently place multiple AXIS W800 System Controller:s in a 19-inch rack. This mount therefore enables easy placement of the Axis body worn system's controllers in a server room with controlled physical access and operational environment. The TW8100 Rack Mount is flexible and allows both horizontal and vertical placement of devices. In horizontal placement, up to 2 pcs of W800 System Controller are supported and will occupy 2U in height. In vertical placement, up to 6 pcs of controllers are supported and will occupy only 5U in height. NB: Vertical mounting is only compatible with the AXIS W800 System Controller of revision 2 (R2).	560	460	80

AXIS W101 BODY WORN CAMERA BLACK	AXIS W101 Body Worn Camera is a robust and easy-to-use body worn camera featuring the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. Axis Zipstream technology lowers bandwidth and storage requirements without compromising video quality. AXIS W101 offers over 12 hours of battery time at 1080p and charging with any USB-C® charger. Recording is activated automatically upon unholstering and person down. And the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking). Built-in Bluetooth®, and network technologies provide wireless communication with, for example, the AXIS Body Worn Assistant mobile app. TW1100 Clip Mount included; docking stations and system controller are sold separately	120	155	40
AXIS W101 BODY WORN CAMERA WHITE	AXIS W101 Body Worn Camera is a robust and easy-to-use body worn camera featuring the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. Axis Zipstream technology lowers bandwidth and storage requirements without compromising video quality. AXIS W101 offers over 12 hours of battery time at 1080p and charging with any USB-C® charger. Recording is activated automatically upon unholstering and person down. And the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking). Built-in Bluetooth®, and network technologies provide wireless communication with, for example, the AXIS Body Worn Assistant mobile app. TW1100 Clip Mount included; docking stations and system controller are sold separately	120	155	40
AXIS W102 Body Worn Camera Black	AXIS W102 features inbuilt WiFi and Bluetooth®, enabling direct streaming of video and audio with AXIS Body Worn Live. It's LCD screen provides the wearer with detailed status information. It is robust and easy-to-use, and features the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. And Electronic Image Stabilization guarantees highest forensic value. AXIS W102 offers up to 12,5 hours of battery time at 1080p and it is possible to charge on the go with any USB-C® charger. Recording can be automatically activated upon unholstering, and the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking).	100	130	40

AXIS W102 Black 5 pcs	AXIS W102 features inbuilt WiFi and Bluetooth®, enabling direct streaming of video and audio with AXIS Body Worn Live. It's LCD screen provides the wearer with detailed status information. It is robust and easy-to-use, and features the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. And Electronic Image Stabilization guarantees highest forensic value. AXIS W102 offers up to 12,5 hours of battery time at 1080p and it is possible to charge on the go with any USB-C® charger. Recording can be automatically activated upon unholstering, and the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking). 5-pack	110	275	110
AXIS W102 Black 24 pcs	AXIS W102 features inbuilt WiFi and Bluetooth®, enabling direct streaming of video and audio with AXIS Body Worn Live. It's LCD screen provides the wearer with detailed status information. It is robust and easy-to-use, and features the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. And Electronic Image Stabilization guarantees highest forensic value. AXIS W102 offers up to 12,5 hours of battery time at 1080p and it is possible to charge on the go with any USB-C® charger. Recording can be automatically activated upon unholstering, and the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking). 24-pack	350	375	130
AXIS W102 Body Worn Camera White	AXIS W102 features inbuilt WiFi and Bluetooth®, enabling direct streaming of video and audio with AXIS Body Worn Live. It's LCD screen provides the wearer with detailed status information. It is robust and easy-to-use, and features the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. And Electronic Image Stabilization guarantees highest forensic value. AXIS W102 offers up to 12,5 hours of battery time at 1080p and it is possible to charge on the go with any USB-C® charger. Recording can be automatically activated upon unholstering, and the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking).	100	130	40
AXIS W101 BODY WORN CAMERA BLK 24P	24 pack of AXIS W101 Body Worn Camera, Black. Mounts, docking stations and system controller are sold separately.	350	370	110

AXIS W110 BODY WORN CAMERA GRAY	AXIS W110 Body Worn Camera is made for a safer workplace and is used to deter, protect, and document events. It's sleek and friendly design opens for use in all segments outside law enforcement. With a compact formfactor and low weight together with innovative mounts using strong magnets for flexible mounting. AXIS W110 offers excellent image and audio quality with exceedingly sharp images and clear audio for forensic usability. Built-in Bluetooth®, and network technologies provide wireless communication with, for example, live streaming with AXIS Body Worn Live or the AXIS Body Worn Assistant mobile app. Recording can be activated automatically using Bluetooth® beacons.	110	100	45
AXIS W110 Gray 5 pcs	AXIS W110 Body Worn Camera is made for a safer workplace and is used to deter, protect, and document events. It's sleek and friendly design opens for use in all segments outside law enforcement. With a compact formfactor and low weight together with innovative mounts using strong magnets for flexible mounting. AXIS W110 offers excellent image and audio quality with exceedingly sharp images and clear audio for forensic usability. Built-in Bluetooth®, and network technologies provide wireless communication with, for example, live streaming with AXIS Body Worn Live or the AXIS Body Worn Assistant mobile app. Recording can be activated automatically using Bluetooth® beacons.	100	230	85
AXIS W110 BODY WORN CAMERA BLACK	AXIS W110 Body Worn Camera is made for a safer workplace and is used to deter, protect, and document events. It's sleek and friendly design opens for use in all segments outside law enforcement. With a compact formfactor and low weight together with innovative mounts using strong magnets for flexible mounting. AXIS W110 offers excellent image and audio quality with exceedingly sharp images and clear audio for forensic usability. Built-in Bluetooth®, and network technologies provide wireless communication with, for example, live streaming with AXIS Body Worn Live or the AXIS Body Worn Assistant mobile app. Recording can be activated automatically using Bluetooth® beacons.	110	100	45
AXIS W110 Black 5 pcs	AXIS W110 Body Worn Camera is made for a safer workplace and is used to deter, protect, and document events. It's sleek and friendly design opens for use in all segments outside law enforcement. With a compact formfactor and low weight together with innovative mounts using strong magnets for flexible mounting. AXIS W110 offers excellent image and audio quality with exceedingly sharp images and clear audio for forensic usability. Built-in Bluetooth®, and network technologies provide wireless communication with, for example, live streaming with AXIS Body Worn Live or the AXIS Body Worn Assistant mobile app. Recording can be activated automatically using Bluetooth® beacons.	100	230	85

AXIS W120 Body Worn Camera Black	AXIS W120 Body Worn Camera is our first fully connected wearable camera. It features inbuilt LTE modem, WiFi and Bluetooth®, enabling direct streaming of video and audio with AXIS Body Worn Live. It's LCD screen provides the wearer with detailed status information. It is robust and easy-to-use, and features the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. And Electronic Image Stabilization guarantees highest forensic value. AXIS W120 offers up to 12,5 hours of battery time at 1080p and it is possible to charge on the go with any USB-C® charger. Recording can be automatically activated upon unholstering, and the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking).	95	140	40
AXIS W120 Black 5 pcs	AXIS W120 Body Worn Camera is our first fully connected wearable camera. It features inbuilt LTE modem, WiFi and Bluetooth®, enabling direct streaming of video and audio with AXIS Body Worn Live. It's LCD screen provides the wearer with detailed status information. It is robust and easy-to-use, and features the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. And Electronic Image Stabilization guarantees highest forensic value. AXIS W120 offers up to 12,5 hours of battery time at 1080p and it is possible to charge on the go with any USB-C® charger. Recording can be automatically activated upon unholstering, and the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking). 5-pack.	105	275	110
AXIS W120 Black 24 pcs	AXIS W120 Body Worn Camera is our first fully connected wearable camera. It features inbuilt LTE modem, WiFi and Bluetooth®, enabling direct streaming of video and audio with AXIS Body Worn Live. It's LCD screen provides the wearer with detailed status information. It is robust and easy-to-use, and features the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. And Electronic Image Stabilization guarantees highest forensic value. AXIS W120 offers up to 12,5 hours of battery time at 1080p and it is possible to charge on the go with any USB-C® charger. Recording can be automatically activated upon unholstering, and the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking). 24-pack.	345	380	135

AXIS W120 Body Worn Camera White	AXIS W120 Body Worn Camera is our first fully connected wearable camera. It features inbuilt LTE modem, WiFi and Bluetooth®, enabling direct streaming of video and audio with AXIS Body Worn Live. It's LCD screen provides the wearer with detailed status information. It is robust and easy-to-use, and features the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. And Electronic Image Stabilization guarantees highest forensic value. AXIS W120 offers up to 12,5 hours of battery time at 1080p and it is possible to charge on the go with any USB-C® charger. Recording can be automatically activated upon unholstering, and the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking).	95	140	40
AXIS Body Worn Live	1-year license for AXIS Body Worn Live, used to stream live video, audio and metadata from our body worn cameras. Secure and reliable, it supports informed decision making by operators and provides an added sense of safety for the camera wearers. AXIS Body Worn Live has several layers of security and the transmission is protected by full end-to-end encryption, ensuring that customer owns their encryption keys. It offers 24-hour data retention, and stream gap retrieval ensures that the customer never miss a thing despite any temporary connection dropout. Being a web-based application it's compatible with PCs, tablets and Android mobile devices and works independently of the user's choice of video or evidence management system. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
AXIS Body Worn Manager Pro	1-year license for AXIS Body Worn Manager Pro, a windows software to take control of, manage and track several body worn systems. Allowing for more advanced features and large installations to be deployed and maintained easily. AXIS Body Worn Manager Pro also comes with Active Directory integration for easy maintenance of large wearer groups. Delivered as eLicense key. One license key per order line. Note: eLicenses are non-cancellable, non-changeable and non-returnable.			
AXIS W800 SYSTEM CONTROLLER	AXIS W800 System Controller is the central integration and management point of the body worn solution. It ensures a high speed and supervised data offloading from the cameras and has built in temporary storage. A single AXIS W800 supports up to five docking stations and 40 cameras and larger body worn systems can easily be extended with additional system controllers. Power adaptor and mounting bracket are included.	225	195	135

AXIS W700 Mk II DOCKING STATION 1 BAY	AXIS W700 MkII Docking Station 1 Bay charges the battery and ensures easy data offloading of a single body worn camera. Power adaptor included.	100	296	50
AXIS W701 MkII DOCKING STATION 8 BAY	AXIS W701 MkII Docking Station 8 Bay charges the batteries and ensures easy data offloading of up to eight body worn cameras. Power adaptor included.	140	445	90
AXIS W702 DOCKING STATION 1 BAY	AXIS W702 Docking Station 1 Bay charges the battery and ensures easy data offloading of a single AXIS W110 body worn camera. Power adaptor included.	300	110	50
AXIS W703 DOCKING STATION 8 BAY	AXIS W703 Docking Station 8 Bay charges the batteries and ensures easy data offloading of up to eight AXIS W110 body worn cameras. Power adaptor included.	135	460	90