

Cisco MS350-48FP-HW Meraki MS350-48FP L3 Stck Cld-Mngd 48

SKU / Model: MS350-48FP-HW

Product overview

Cisco Meraki MS350-48FP-HW Meraki MS350-48FP-HW 48 Ports Ethernet Switch - Gigabit Ethernet - 1000Base-X - 3 Layer Supported SPECIFICATIONS Performance Non-blocking fabric 2.5 microsecond latency Jumbo frame support (9600 byte Ethernet frame) Layer 3 (MS320/350 series) Static routing DHCP Helper OSPFv2 3Warm Spare for L3 gateway redundancy DHCP server Automatic DHCP failover in warm spare mode Power Power input: 100 - 240 VAC, 47-63 Hz Power consumption: 5-888W Mounting Rack-mountable with included rack mount hardware (except MS220-8/P) Desktop-mountable with included feet Wall-mountable on MS220-8/P Kensington lock on MS220-8/P Environment Operating temperature: 32 °F to 104 °F (0 °C to 40 °C), 45 °C for MS350 Humidity: 5 to 95% non-condensing Low acoustic noise for office environments; fanless for MS220-8/P and MS220-24

Important notice

This information may include AI-assisted content and is provided for reference only. Specifications, images and availability may change without notice. All trademarks, logos and product information belong to their respective owners. Bizgram does not accept liability for inaccuracies or decisions based solely on this document. Confirm final specifications, compatibility, price, stock and lead time with Bizgram before purchase.