

			
Bizgram Asia Pte Ltd Retail Wholesale Factory Outlet Address : #05-50 Sim Lim Square 1 Rochor Canal Road Singapore 188504 Operating Hours : Mon to Sun – 10am to 7.30pm Public Holidays – OPEN Tel : +65-63346455 / 63341373 Fax : NO MORE FAX SMS / Whatsapp : +65 – 8777 6955			
Series	Model	Size	Description (WHILST STOCKS LAST PRICING)
UHD Commercial TV	55UR640S	55"	Brightness: 300cd/m ² - 43", 400cd/m ² - 50",55,65", 330 cd/m ² - 75" & 86" Resolution : ULTRA HD (3,840 x 2,160) Improved Design with Slim Depth webOS-based High Performance Easy Content Management/Group Management SuperSign Control / CMS Compatibility No VGA, 3 x HDMI Thickness 57.5 mm
UHD Commercial TV	65UR640S	65"	Brightness: 300cd/m ² - 43", 400cd/m ² - 50",55,65", 330 cd/m ² - 75" & 86" Resolution : ULTRA HD (3,840 x 2,160) Improved Design with Slim Depth webOS-based High Performance Easy Content Management/Group Management SuperSign Control / CMS Compatibility No VGA, 3 x HDMI Thickness 57.5 mm
Series	Model	Description	
Small Signage	22SM3G	FHD Resolution Brightness(Typ.): 250 cd/m ² Bezel : 16.3mm Depth : 53.8mm Interface : HDMI(2) / USB 2.0 / RS232C / RJ45 / IR / Audio USB Plug & Play, Built-in Wi-Fi	
Small Signage	32SM5I-B	FHD Resolution Brightness(Typ.): 400 cd/m ² HDMI/RJ45/IR, USB Plug & Play, Built-in Wi-Fi Support Landscape / Portrait Mode	
UHD Series	43UL3I-N	Glossy Ultra HD Series Brightness(Typ.): 300 cd/m ² Surface Treatment (Haze) : 1% Interface : HDMI(3)/ USB 2.0(2)/ RS232C/ RJ45/ Audio/ IR Built-in Speaker	
UHD Series	50UL3I-N	Glossy Ultra HD Series Brightness(Typ.): 400 cd/m ² Surface Treatment (Haze) : 2% Interface : HDMI(3)/ USB 2.0(2)/ RS232C/ RJ45/ Audio/ IR Built-in Speaker	
UHD Series	55UL3I-N	Glossy Ultra HD Series Brightness(Typ.): 400 cd/m ² Surface Treatment (Haze) : 1% Interface : HDMI(3)/ USB 2.0(2)/ RS232C/ RJ45/ Audio/ IR Built-in Speaker	
UHD Series	65UL3I-B	Glossy Ultra HD Series Brightness(Typ.): 400 cd/m ² Surface Treatment (Haze) : 1% Interface : HDMI(3)/ USB 2.0(2)/ RS232C/ RJ45/ Audio/ IR Built-in Speaker	
UHD Series	75UL3I-B	Glossy Ultra HD Series Brightness(Typ.): 330 cd/m ² Surface Treatment (Haze) : 1% Interface : HDMI(3)/ USB 2.0(2)/ RS232C/ RJ45/ Audio/ IR Built-in Speaker	
UHD Series	86UL3I-N	Glossy Ultra HD Series Brightness(Typ.): 330 cd/m ² Surface Treatment (Haze) : 1% Interface : HDMI(3)/ USB 2.0(2)/ RS232C/ RJ45/ Audio/ IR Built-in Speaker Does Not Support Portrait	
UHD Series	98UM5K	Brightness(Typ.): 500 cd/m ² Surface Treatment (Haze) : 25% Interface : HDMI x 3, DP in, DVI-D, Audio In, RS-232C, RJ45, IR In, USB 2.0 Type A Built-in Speaker	
UHD Series	110UM5K	Brightness(Typ.): 500 cd/m ² Surface Treatment (Haze) : 1% Interface : HDMI x 3, DP in, DVI-D, Audio In, RS-232C, RJ45, IR In, USB 2.0 Type A Built-in Speaker	

UHD Series	43UH5N-M	Non-Glare Ultra HD Series Brightness(Typ.) : 500 cd/m ² Surface Treatment (Haze) : 25% Input : HDMI In (3, 3,840 × 2,160 @ 60 Hz, HDCP 2.2/1.4), DP In (3,840 × 2,160 @ 60 Hz, HDCP 2.2/1.3), RS-232C In (4 Pin Phone-jack), RJ45 (LAN) In, IR In, USB 2.0 Type A (2) Output: Audio Out, RS-232C Out (4 Pin Phone-jack) Built-in Speaker 30° Tilting Installation Conformal Coating	
UHD Series	55UH5N-M	Non-Glare Ultra HD Series Brightness(Typ.) : 500 cd/m ² Surface Treatment (Haze) : 25% Input : HDMI In (3, 3,840 × 2,160 @ 60 Hz, HDCP 2.2/1.4), DP In (3,840 × 2,160 @ 60 Hz, HDCP 2.2/1.3), RS-232C In (4 Pin Phone-jack), RJ45 (LAN) In, IR In, USB 2.0 Type A (2) Output: Audio Out, RS-232C Out (4 Pin Phone-jack) Built-in Speaker 30° Tilting Installation Conformal Coating IP5X Certified	
UHD Series	65UH5N-M	Non-Glare Ultra HD Series Brightness(Typ.) : 500 cd/m ² Surface Treatment (Haze) : 28% Input : HDMI In (3, 3,840 × 2,160 @ 60 Hz, HDCP 2.2/1.4), DP In (3,840 × 2,160 @ 60 Hz, HDCP 2.2/1.3), RS-232C In (4 Pin Phone-jack), RJ45 (LAN) In, IR In, USB 2.0 Type A (2) Output: Audio Out, RS-232C Out (4 Pin Phone-jack) Built-in Speaker 30° Tilting Installation	
UHD Series	75UH5J-M	Non-Glare Ultra HD Series Brightness(Typ.) : 500 cd/m ² Surface Treatment (Haze) : 28% Input : HDMI(3)/ DP/ DVI-D/ USB 2.0/ RS232C/ RJ45/ Audio/ IR Output: HDMI/Audio/RS232 Built-in Speaker 30° Tilting Installation Conformal Coating IP5X Certified	
UHD Series	86UH5J-H	Non-Glare Ultra HD Series Brightness(Typ.) : 500 cd/m ² Surface Treatment (Haze) : 28% Input : HDMI(3)/ DP/ DVI-D/ USB 2.0/ RS232C/ RJ45/ Audio/ IR Output: HDMI/Audio/RS232 Built-in Speaker 30° Tilting Installation Conformal Coating IP5X Certified	
UHD Series	98UH5J-H	Non-Glare Ultra HD Series Brightness(Typ.) : 500 cd/m ² Surface Treatment (Haze) : 28% Input : HDMI(3)/ DP/ DVI-D/ USB 2.0/ RS232C/ RJ45/ Audio/ IR Output: HDMI/Audio/RS232 Built-in Speaker 30° Tilting Installation Conformal Coating IP5X Certified	
Incell Touch OpenFrame	32TNF5J	Openframe Incell Touch Resolution FHD 1920 x 1080 Brightness 500nits Inbuilt 8GB memory Max 10 multi touch points Supports 45 degree Tilt Installation	
In-Built IR Touch with Embedded Writing Solution	55TR3DK	Brightness (w/ Glass) : 390 nit (Typ.) Touch Type : IRMulti Touch Point : Max 40 Points Interface : HDMI (3, HDCP 2.2), RGB (VGA), Audio In, RS-232C In, RJ45 (LAN), USB 3.0 Type A (4), USB 2.0 Type A, USB Type C (USB-PD, DP-Alt), HDMI Out, Audio Out (1, Optical 1 (SPDIF)), Touch USB (2), RJ45 (LAN)	
In-Built IR Touch with Embedded Writing Solution	65TR3DK	Brightness (w/ Glass) : 390 nit (Typ.) Touch Type : IRMulti Touch Point : Max 40 Points Interface : HDMI (3, HDCP 2.2), RGB (VGA), Audio In, RS-232C In, RJ45 (LAN), USB 3.0 Type A (4), USB 2.0 Type A, USB Type C (USB-PD, DP-Alt), HDMI Out, Audio Out (1, Optical 1 (SPDIF)), Touch USB (2), RJ45 (LAN)	
In-Built IR Touch with Embedded Writing Solution	75TR3DK	Brightness (w/ Glass) : 390 nit (Typ.) Touch Type : IRMulti Touch Point : Max 40 Points Interface : HDMI (3, HDCP 2.2), RGB (VGA), Audio In, RS-232C In, RJ45 (LAN), USB 3.0 Type A (4), USB 2.0 Type A, USB Type C (USB-PD, DP-Alt), HDMI Out, Audio Out (1, Optical 1 (SPDIF)), Touch USB (2), RJ45 (LAN)	
In-Built IR Touch with Embedded Writing Solution	86TR3DK	Brightness (w/ Glass) : 390 nit (Typ.) Touch Type : IRMulti Touch Point : Max 40 Points Interface : HDMI (3, HDCP 2.2), RGB (VGA), Audio In, RS-232C In, RJ45 (LAN), USB 3.0 Type A (4), USB 2.0 Type A, USB Type C (USB-PD, DP-Alt), HDMI Out, Audio Out (1, Optical 1 (SPDIF)), Touch USB (2), RJ45 (LAN)	

Videowall	55VL5F	Brightness(Typ.) : 500 cd/m ² Bezel : 2.25 mm (T/L), 1.25 mm (B/R) Depth : 93.1 mm Interface : HDMI (2) / DP / DVI-D / USB / RS232C / RJ45 / Audio / IR
Videowall	55VM5J-H	1.8mm Bezel to Bezel Video Wall Monitor, Direct LED IPS Resolution Full HD Brightness 500nit Interface : HDMI / DVI / IR, Daisy-chain (DP, RS232C, RJ45) WebOS 4.1
Videowall	55VH7J-H	Brightness(Typ.) : 700 cd/m ² Surface Treatment(Haze): 44% Bezel : 0.9 mm (Even) Depth : 86.5 mm Interface : HDMI(2) / DP / DVI-D / USB 2.0 / RS232C / RJ45 / Audio / IR
Videowall	55VSM5J-H	Brightness(Typ.) : 500 cd/m ² Surface Treatment(Haze): 28% Bezel : 0.44 mm (Even) Interface : HDMI(2) / DP / DVI-D / USB 2.0 / RS232C / RJ45 / Audio / IR Smart Calibration
Videowall	55VSH7J	0.88mm Bezel to Bezel Video Wall Monitor, Direct LED IPS Resolution Full HD Brightness 700 nit DP 1.2 Daisy Chain WebOS 4.0
Stretched	86BHSF-M	Ultra Stretch Signage Brightness(Typ.) : 500 cd/m ² Aspect Ratio: 58:9 Bezel: 4.4 mm(L/R), 5.9 mm(T/B) Depth: 81.7mm Interface: HDMI (3), DP, USB(2), Audio, DVI-D, RS232C, RJ45, IR
Stretched	105BM5N	Stretch Signage Resolution: 5120 x 2160 (5K) Brightness(Typ.) : 400 cd/m ² Surface Treatment (Haze) : 25% Aspect Ratio: 21:9 Proximity Sensor; Wireless ScreenShare; OPS Slot Full Toughening, Thermal Tempering and 5% Anti-Reflective 4mm Shatter-Proof Protection Glass Bezel: 3.5 mm(T/L/R), 23 mm(B)
Outdoor	22XE1J	Brightness (Typ, w/ Glass) : 1,500 nits IP56 Rated Dust / Water Proof 21.5" of Versatile Display Size Wide Operating Temperature Range webOS Smart Platform Web-based Monitoring Solution
Outdoor	49XF3E	Minimum Brightness : 3000cd/m2 Temperature sensor & auto brightness sensor FHD Resolution Internal 8GB(System 4GB + Available 4GB) WebOS 1.0
Outdoor	55XF3E	Minimum Brightness : 3000cd/m2 Temperature sensor & auto brightness sensor FHD Resolution Internal 8GB(System 4GB + Available 4GB) WebOS 1.0
Outdoor	75XF3ES	Brightness: 3000cd/m Life Time : 50,000 hours Interface: HDMI (2) / DP / DVI / RJ45 / IR / RS232 / USB / External Speaker Out WebOS 3.0
UHD Commercial TV	43UR640S	Brightness: 300cd/m2 - 43", 400cd/m2 - 50", 55, 65", 330 cd/m2 - 75" & 86" Resolution : ULTRA HD (3,840 x 2,160) Improved Design with Slim Depth webOS-based High Performance Easy Content Management/Group Management SuperSign Control / CMS Compatibility No VGA, 3 x HDMI Thickness 57.5 mm
UHD Commercial TV	50UR640S	Brightness: 300cd/m2 - 43", 400cd/m2 - 50", 55, 65", 330 cd/m2 - 75" & 86" Resolution : ULTRA HD (3,840 x 2,160) Improved Design with Slim Depth webOS-based High Performance Easy Content Management/Group Management SuperSign Control / CMS Compatibility No VGA, 3 x HDMI Thickness 57.5 mm
UHD Commercial TV	55UR640S	Brightness: 300cd/m2 - 43", 400cd/m2 - 50", 55, 65", 330 cd/m2 - 75" & 86" Resolution : ULTRA HD (3,840 x 2,160) Improved Design with Slim Depth webOS-based High Performance Easy Content Management/Group Management SuperSign Control / CMS Compatibility No VGA, 3 x HDMI Thickness 57.5 mm

UHD Commercial TV	65UR640S	Brightness: 300cd/m2 - 43", 400cd/m2 - 50", 55, 65", 330 cd/m2 - 75" & 86" Resolution : ULTRA HD (3,840 x 2,160) Improved Design with Slim Depth webOS-based High Performance Easy Content Management/Group Management SuperSign Control / CMS Compatibility No VGA, 3 x HDMI Thickness 57.5 mm
UHD Commercial TV	75UR640S	Brightness: 300cd/m2 - 43", 400cd/m2 - 50", 55, 65", 330 cd/m2 - 75" & 86" Resolution : ULTRA HD (3,840 x 2,160) Improved Design with Slim Depth webOS-based High Performance Easy Content Management/Group Management SuperSign Control / CMS Compatibility No VGA, 3 x HDMI Thickness 57.5 mm
UHD Commercial TV	86UR640S	Brightness: 300cd/m2 - 43", 400cd/m2 - 50", 55, 65", 330 cd/m2 - 75" & 86" Resolution : ULTRA HD (3,840 x 2,160) Improved Design with Slim Depth webOS-based High Performance Easy Content Management/Group Management SuperSign Control / CMS Compatibility No VGA, 3 x HDMI Thickness 57.5 mm
Commercial TV	65UR751C	Glossy Ultra HD Series Brightness(Typ.) : 360 cd/m ² Interface : HDMI(3)/(HDMI CEC)/ USB 2.0/ Audio/ IR Built-in Speaker No RS232/LAN Control Inbuilt Airplay/Miracast/Intel Widi capability Inbuilt Appstore No Hotel Mode
Commercial TV	86UR801C	Glossy Ultra HD Series Brightness(Typ.) : 350 cd/m ² Interface : HDMI(4)/(HDMI CEC)/ USB 2.0/ Audio/ IR Built-in Speaker No RS232/LAN Control Inbuilt Airplay/Miracast/Intel Widi capability Inbuilt Appstore No Hotel Mode
Accessories	WP600	WebOS Media Player
Software	LWSMB	Supersign CMS (Previously know as Premium / W)
Software	LPBD	Supersign WB (Calibration Software)